

TRAFFIC IMPACT STUDY

FOR

**HARTMAN DISTRIBUTION CENTER
UNINCORPORATED COBB COUNTY, GA**

Prepared For:

Oakmont Industrial Group
3520 Piedmont Road - Suite 100
Atlanta, Ga. 30305

Prepared by:



2470 Sandy Plains Rd
Marietta, Georgia 30066

March 10, 2014

TABLE OF CONTENTS

EXECUTIVE SUMMARY	4
PROJECT DESCRIPTION.....	4
EXISTING CONDITIONS-2014.....	5
Traffic Volumes	5
Roadway Conditions	6
Intersection Geometry	6
Level of Service	8
FUTURE BACKGROUND CONDITIONS-(2016) Without Development.....	9
Future Traffic Volumes	9
Future Background Level of Service	9
PROPOSED DEVELOPMENT.....	11
Trip Generation	11
Trip Distribution and Assignment.....	11
FUTURE CONDITONS-(2016) WITH PROPOSED DEVELOPMENT	14
Future Traffic Volumes	14
Future Level of Service	14
CONCLUSIONS AND RECOMMENDATIONS	16

LIST OF TABLES

Table 1 : Level of Service for Un-Signalized Intersections.....	8
Table 2 : Level of Service for Signalized Intersections.....	8
Table 3: Existing Year-2014 Level of Service	9
Table 4: Future Background Level of Service w/o Proposed Development	9
Table 5: Trip Generation - Proposed Development.....	11
Table 6: Future Background Level of Service with Proposed Development	14

LIST OF FIGURES

Figure 1: Location Map	5
Figure 2: Existing Year 2014 Peak Hour Volume.....	7
Figure 3: Future Year 2016 Background Peak Hour Volume	10
Figure 4: Site Generated Traffic.....	12
Figure 5 Lane Configuration & Traffic Control.....	13
Figure 6: Future Year 2016 Peak Hour Volume with Proposed Development	15

APPENDICIES

Appendix A: Site Development Plan	
Appendix B: Traffic Count Summary Sheets	
Appendix C: Trip Generation	
Appendix D: Existing Year-2014 Intersection Capacity Analyses Sheets (ICAS)	
Appendix E: Year-2016 Background ICAS without the Development	
Appendix F: Year-2016 ICAS with the Development	

EXECUTIVE SUMMARY

This traffic impact study has been conducted to determine the traffic impacts expected from the proposed Hartman Distribution Center development near the City of Austell, GA. The development is planned to be completed in 2016. The development is located south of Interstate 20 in Cobb County, GA on White Road between the intersections of Factory Shoals Road and Riverside Parkway. The development will be accessed via these two intersections and by one new full access driveway on White Road.

Capacity analyses and level of service evaluations of the two intersections in the vicinity of the development were conducted for the existing condition; future condition without the development; and future condition with the proposed development. Analysis of the new driveway was conducted for the future condition with the proposed development. The evaluations were used to determine any potential mitigation that might be recommended to resolve any traffic issues resulting from the proposed development.

All studied intersections are expected to continue to operate at an acceptable level of service with the full build out of the development as proposed. The proposed development does not significantly impact the operations or capacity of the intersections. The intersection Riverside Parkway and White Road should be improved to provide a flared right turn for southbound vehicles. The development will construct a right-turn deceleration lane on White Road for the new driveway. The study concluded that with the proposed development there is no need for any additional lanes at any of the intersections, and that the intersections operate at an acceptable level of service as side street stop controlled.

PROJECT DESCRIPTION

A traffic impact study has been conducted for the proposed Hartman Distribution Center that is planned on White Road between Factory Shoals Road and Riverside Parkway near the City of Austell, Georgia in Cobb County. The proposed development will have approximately 620,000 SF of general warehouse space and is planned to be completed in 2016. The development will create a new driveway on White Road, which will serve as the sole access point for the development. The conceptual site plan of the development is included in the appendix.

The traffic impacts with the development as proposed will be compared to the traffic impacts on the surrounding roadway network in the future without the development. The development is in an urban area. The traffic impact study includes capacity analyses and level of service evaluations of two major intersections in the vicinity of the development and the new driveway. The study intersections for the development are:

- Factory Shoals Road at White Road
- Riverside Parkway at White Road
- Hartman Distribution Center Driveway at White Road

The study intersections were analyzed for the existing condition, future background condition without the development, and future condition with the proposed development.

All analyses conducted as part of this study have been based on the data collected for the existing condition and an assumed growth rate for this area estimated based on

historical traffic counts and future growth potential of the area. Any variations to the existing database and the assumptions made may affect the results of the study.

Figure 1 is a map of the vicinity of the proposed development.



Figure 1: Location Map

EXISTING CONDITIONS-2014

The study area consists of the intersections of Factory Shoals Road at White Road and Riverside Parkway at White Road. Pedestrian facilities are not present at either of the study intersections. Riverside Parkway connects to I-20 northeast of the proposed development site and the intersection of Riverside Parkway at White Road. Adjacent to the site are industrial and residential facilities.

Traffic Volumes

Turning Movement Counts (TMC) were collected at the intersections of Factory Shoals Road at White Road and Riverside Parkway at White Road. The counts were collected on Tuesday January 21, 2014 during the AM & PM peak hour periods of 7:00am – 9:00am and 4:00pm - 6:00pm. The morning peak hour for the intersection of Factory Shoals Road at White Road occurred from 7:15 AM to 8:15 AM. The morning peak hour for the intersection of Riverside Parkway at White Road occurred from 7:00 AM to 8:00

AM. The afternoon peak hour occurred from 5:00 PM to 6:00 PM for both intersections. Figure 2 shows the existing peak hour traffic volumes at the study intersections.

Also collected were 24-hour bi-directional volume counts on Factory Shoals Road north of I-20 and on Riverside Parkway south of Twin Hill Road. Georgia DOT (GDOT) daily, monthly, and axle traffic factors were used to adjust the short-term traffic counts. The Average Annual Daily Traffic (AADT) on Factory Shoals Road was 5,570 vehicles per day (vpd) and truck traffic was 4% of vehicles on the road. The AADT for Riverside Parkway was 13,815 vpd and truck traffic was 19% of vehicles on the road. The full count data is included in the appendix.

Roadway Conditions

Factory Shoals Road

Factory Shoals Road is currently a two lane roadway. According to GDOT, Factory Shoals Road is functionally classified as an Urban Local Road. Factory Shoals Road travels generally in the northeast-southwest direction with a posted speed limit of 40 mph. The average annual daily traffic volume (AADT) was 5,570 vehicles per day (vpd) on Factory Shoals Road north of I-20. The truck percentage on the road was 4%.

Riverside Parkway

Riverside Parkway is currently a two lane roadway. According to GDOT, Riverside Parkway is functionally classified as an Urban Minor Arterial. Riverside Parkway travels generally in the northeast-southwest direction, with a posted speed limit of 45 mph. The AADT was 13,815 vehicles per day (vpd). The truck percentage on the road was 19%.

White Road

White Road is a two lane roadway that runs generally north-south connecting Factory Shoals Road to Riverside Parkway. According to GDOT, White Road is functionally classified as an Urban Local Road with a posted speed limit of 35 mph.



Intersection Geometry

Factory Shoals Road at White Road

This is a three-legged intersection and is side street stop controlled with Factory Shoals Road being the main street. All approaches have a single lane. The northbound approach is the northern terminus for White Road.

Riverside Parkway at White Road

This is a three-legged intersection and is side street stop controlled with Riverside Parkway being the main street. All approaches have a single lane. The southbound approach is the southern terminus for White Road.



Legend: AM (PM)

EXISTING YEAR 2014
PEAK HOUR VOLUME
HARTMAN DISTRIBUTION CENTER DRI

FIGURE 2

Project No.	047-13-133
Design By:	CM
Drawn By:	CM
Checked By:	BAH
Date:	02/14/2014
Scale:	NTS

SEI
SOUTHEASTERN ENGINEERING
2470 Sandy Plains Road
Marietta, Georgia • 30066
tel: 770-321-3936 fax: 770-321-3935

Level of Service

Intersection capacity analyses were performed at two intersections to determine the existing traffic conditions within the study area. Intersection capacity analyses were performed using the methodology outlined in the 2010 Highway Capacity Manual (HCM). This methodology is the industry standard for the evaluation of intersection capacity and delay. In order to facilitate the analysis, a computer software Synchro was used. This software conforms to the methodology of the HCM. The vehicular delay value that results from the Synchro analysis is used to determine the level of service of an intersection. Level of service (LOS) is a letter designation used to describe traffic operating conditions, on a declining scale from A to F. LOS "A" represents free-flow traffic conditions and LOS "F" represents extreme delays with stopped traffic conditions. Tables 1 & 2 below indicate the relationship between delay and level of service for un-signalized & signalized intersections.

Table 1 : Level of Service for Un-Signalized Intersections	
Level of Service	Control Delay Per Vehicle (sec)
A	≤ 10
B	> 10 and ≤ 15
C	> 15 and ≤ 25
D	> 25 and ≤ 35
E	> 35 and ≤ 50
F	> 50

Table 2 : Level of Service for Signalized Intersections	
Level of Service	Control Delay Per Vehicle (sec)
A	≤ 10
B	> 10 and ≤ 20
C	> 20 and ≤ 35
D	> 35 and ≤ 55
E	> 55 and ≤ 80
F	> 80

The results of the existing intersection capacity analyses are summarized in Table 3 below. Side Street Stop Control has been reported for both intersections. For Side Street Stop Control intersections, delay and LOS are given for the minor street only. The intersection capacity analyses worksheets are included in the appendix.

Table 3: Existing Year-2014 Level of Service			
Intersection	Type of Control*	Existing-2014	
		AM-Peak Delay (LOS)	PM-Peak Delay (LOS)
Factory Shoals Road at White Road	Side Street Stop	13.0 (B)	12.3 (B)
Riverside Parkway at White Road	Side Street Stop	17.1 (C)	17.3 (C)

*For side street stop control intersections, delay and LOS are given for minor street only

Under existing conditions, all system intersections are operating at an acceptable level of service during AM and PM peak hours, well above the minimum LOS D.

FUTURE BACKGROUND CONDITIONS-(2016) Without Development

Future Traffic Volumes

To estimate the volumes that will exist in the vicinity of the proposed development during the anticipated full build out year of 2016, current traffic trends were evaluated. Based on GDOT's STARS information Factory Shoals Road and Riverside Parkway have shown some negative growth. For the purpose of this study and to provide the most conservative analysis an assumed growth rate of 1% is used to estimate future traffic volumes in the project area. The future background traffic volumes are shown in Figure 3.

Future Background Level of Service



The level of service for the future background condition was determined using the same method as discussed previously in the Existing Conditions – Level of Service section. Intersection capacity analyses were performed on the future background traffic volumes. The LOS for all the intersections was similar to the existing conditions.

The results of the intersection capacity analysis for the 2016 future background year are summarized in Table 4. The study worksheets are included in the appendix.

Table 4: Future Background Level of Service w/o Proposed Development			
Intersection	Type of Control*	Future Year-2016 Without Development	
		AM-Peak Delay (LOS)	PM-Peak Delay (LOS)
Factory Shoals Road at White Road	Side Street Stop	13.1 (B)	12.4 (B)
Riverside Parkway at White Road	Side Street Stop	17.4 (C)	17.6 (C)

*For side street stop control intersections, delay and LOS are given for minor street only

Under future background conditions, all system intersections are operating at an acceptable level of service during AM and PM peak hours, well above the minimum LOS D.



Legend: AM (PM)

YEAR 2016 BACKGROUND
PEAK HOUR VOLUME
HARTMAN DISTRIBUTION CENTER DRI

FIGURE 3

Project No.	047-13-133
Design By:	CM
Drawn By:	CM
Checked By:	BAH
Date:	02/14/2014
Scale:	NTS

 **SEI**
SOUTHEASTERN ENGINEERING
2470 Sandy Plains Road
Marietta, Georgia • 30066
tel: 770-321-3936 fax: 770-321-3935

PROPOSED DEVELOPMENT

The proposed Hartman Distribution Center development will have approximately 620,000 SF of General Warehouse Space. The development is planned to be completed in 2016. One full access driveway will be built on White Road for the Distribution Center.

Approximately 85 percent of the site is already zoned Heavy Industrial. The northern end of the site will be being rezoned to Heavy Industrial, from R-20, to match the southern portion of the site. Cobb County's comprehensive land use plan calls for this area to be industrial in nature.

The proposed development was analyzed with the intersections of Factory Shoals Road at White Road, Riverside Parkway at White Road, and the new Distribution Center Driveway on White Road as the access development's points. The site development plan is attached in the appendix; this plan shows the highlighted fifteen percent of the site that is currently zoned R-20.

Trip Generation

It is anticipated that the proposed development will reach full build-out by 2016. The expected number of gross trips for this land use was determined using Trafficware's Trip Generation software. This software estimates trips generated by the proposed land use in accordance with the Institute of Transportation Engineers (ITE) *Trip Generation Manual*, 9th Edition, 2012. Full build-out and occupancy of the development was assumed when applying the trip generation rates and equations. The net new trips for the proposed mixed use development are provided in the Table 5. The trip generation worksheet and future volume data worksheet are attached in the appendix.


To provide the most conservative analysis the proposed development was analyzed as a 625,000 SF General Warehouse, even though the proposed development will be less than 620,000 SF.

Table 5: Trip Generation - Proposed Development						
Land Use	ITE Code	24-Hr Two-Way Volume	AM-Peak (7-9)		PM-Peak (4-6)	
			Enter	Exit	Enter	Exit
625,000 SF General Warehouse	150	2225	171	92	53	228
Total		2225	171	92	53	228

Source: ITE Trip Generation, 9th Edition, 2012

Trip Distribution and Assignment

The trip distribution for the proposed development has been determined based on the existing traffic flow patterns experienced in the area and the type of adjacent development. The site-generated traffic was assigned to the study intersections according to the expected trip distributions. The site generated traffic for the proposed development at the study intersections are shown in Figure 4. The lane geometry of the study intersections and the proposed site access are shown in Figure 5. The trip distribution percentages are attached in the appendix.




Legend: AM (PM)

SITE GENERATED
PEAK HOUR VOLUME
HARTMAN DISTRIBUTION CENTER DRI

FIGURE 4

Project No.	047-13-133
Design By:	CM
Drawn By:	CM
Checked By:	BAH
Date:	02/14/2014
Scale:	NTS





Legend: AM (PM)

FUTURE YEAR 2016 DEVELOPED LANE CONFIGURATION HARTMAN DISTRIBUTION CENTER DRI	FIGURE 5	Project No. 047-13-133	
		Design By: CM Drawn By: CM Checked By: BAH Date: 02/14/2014 Scale: NTS	

FUTURE CONDITONS-(2016) WITH PROPOSED DEVELOPMENT

Future Traffic Volumes

The future traffic volumes were determined by adding the site generated traffic estimated for the Hartman Distribution Center development to the future background traffic volumes. To provide a conservative analysis no pass-by reductions or internal trip captures were used in determining the future volume assignments. The future traffic volumes for the proposed development are shown in Figure 6.

Future Level of Service

The level of service for the future condition with the proposed development was determined using the same methods as discussed previously in the Existing Condition-Level of Service section. Intersection capacity analyses were performed on calculated future traffic volumes with the proposed development.


The intersections were first analyzed using their existing geometry and Side Street Stop Control. All intersections, with the exception of Riverside Parkway at White Road, continue to operate at acceptable levels of service, well above the minimum LOS D, in the future with the development as proposed. The intersection at the new Distribution Center Driveway was analyzed as the driveway having a shared left-thru-right lane, and single lane approaches on White Road. Additionally, a right-turn deceleration lane will be constructed for the northbound approach on White Road at the driveway due to the high volume of right-turning vehicles.

The intersection of Riverside Parkway at White Road was analyzed again with the proposed improvement of a flared right-turn on White Road and remaining Side Street Stop Controlled. This will allow right-turning vehicles to navigate around the left-turning vehicles waiting for a gap. With the flared right-turn addition on White Road the intersection operates at acceptable level of service, well above the minimum LOS D, in the future with the development as proposed.

With the recommended improvement at the intersection of Riverside Parkway and White Road, all the intersections operate at an acceptable level of service in the future with the development as proposed. All intersections continue to operate at an acceptable level of service as Side Street Stop Controlled. The results of the intersection capacity analysis for the 2016 future year with the development are summarized in the Table 6. The intersection capacity analyses worksheets are included in the appendix.

Table 6: Future Background Level of Service with Proposed Development					
Intersection	Type of Control*	Future Year-2016 With Development		Future Year-2016 Development w/ Improvements	
		AM-Peak Delay (LOS)	PM-Peak Delay (LOS)	AM-Peak Delay (LOS)	PM-Peak Delay (LOS)
Factory Shoals Road at White Road	Side Street Stop	13.9 (B)	14.4 (B)	-	-
Riverside Parkway at White Road	Side Street Stop	34.5 (D)	37.4 (E)	26.0 (C)	19.4 (C)
Hartman Distribution Center	Side Street Stop	7.8 (A)	8.0 (A)	-	-

*For side street stop control intersections, delay and LOS are given for minor street only



Legend: AM (PM)

CONCLUSIONS AND RECOMMENDATIONS

The study intersections currently operate at acceptable levels of service. When the intersections were analyzed for the future year 2016 background peak hour volumes without the proposed development they continue to operate at an acceptable level of service, well above the minimum LOS D.

With the proposed development the study intersections are expected to continue to operate at acceptable levels of service with the site generated traffic. Based on the analyses conducted in the study, the traffic impacts of the proposed development on the surrounding roadway network were determined to be negligible. The level of service for the study intersections are expected to remain at acceptable levels in the future with the development as proposed, well above the minimum LOS D.

The Factory Shoals Road and White Road intersection is expected to operate at an acceptable level of service, LOS B, in the future with the development as proposed. The existing roadway lane configuration is adequate for the future conditions with the development. The intersection should continue to operate as Side Street Stop Controlled.

The Hartman Distribution Center Driveway and White Road intersection is expected to operate at an acceptable level of service, LOS A, in the future with the development as proposed. The existing roadway geometry of White Road is adequate for the future conditions with the development, but a right-turn deceleration lane will be constructed for the northbound approach on White Road to accommodate the high volume of right-turning vehicles into the new driveway. A single lane full access driveway will serve as the sole driveway for the development. The intersection should operate as Side Street Stop Controlled.

The Riverside Drive and White Road intersection is expected to operate at an acceptable level of service, LOS C, in the future with the development and intersection improvements as proposed on White Road. The single lane southbound approach on White Road should be improved to provide a flared right-turn, upon completion of the development. The intersection should continue to operate as Side Street Stop Controlled.

Hartman Distribution Center City of Austell, Cobb County, GA Traffic Study Appendix

Appendix A: Site Development Plan

Appendix B: Traffic Count Summary Sheets

Appendix C: Trip Generation and Distribution

Appendix D: Existing Year-2014 Intersection Capacity Analyses Sheets (ICAS)

Appendix E: Year-2016 Background ICAS without the Development

Appendix F: Year-2016 ICAS with the Development

Appendix A: Site Development Plan

Appendix B: Traffic Count Summary Sheets

Project ID: 14-9014-012
Location: White Rd & Factory Shoals Rd
City: Austell

Day: Tuesday
Date: 1/21/2014

Peak Start Times	
AM	7:00 AM
MD	12:00 AM
PM	4:00 PM

Groups Printed - Cars, PU, Vans - Heavy Trucks

	White Rd Northbound					White Rd Southbound					Factory Shoals Rd Eastbound					Factory Shoals Rd Westbound					
Start Time	Left	Thru	Rgt	Peds	App. Total	Left	Thru	Rgt	Peds	App. Total	Left	Thru	Rgt	Peds	App. Total	Left	Thru	Rgt	Peds	App. Total	Int. Total
7:00 AM	0	0	8	0	8	0	0	0	0	0	0	76	2	0	78	2	33	0	0	35	121
7:15 AM	0	0	0	0	0	0	0	0	0	0	0	89	2	0	91	5	31	0	0	36	127
7:30 AM	3	0	4	0	7	0	0	0	0	0	0	110	4	0	114	3	61	0	0	64	185
7:45 AM	1	0	3	0	4	0	0	0	0	0	0	92	1	0	93	5	49	0	0	54	151
Total	4	0	15	0	19	0	0	0	0	0	0	367	9	0	376	15	174	0	0	189	584
8:00 AM	0	0	1	0	1	0	0	0	0	0	0	84	2	0	86	3	56	0	0	59	146
8:15 AM	1	0	3	0	4	0	0	0	0	0	0	54	1	0	55	4	38	0	0	42	101
8:30 AM	0	0	5	0	5	0	0	0	0	0	0	45	0	0	45	3	30	0	0	33	83
8:45 AM	1	0	4	0	5	0	0	0	0	0	0	27	3	0	30	1	17	0	0	18	53
Total	2	0	13	0	15	0	0	0	0	0	0	210	6	0	216	11	141	0	0	152	383
BREAK																					
4:00 PM	1	0	8	0	9	0	0	0	0	0	0	36	5	0	41	7	42	0	0	49	99
4:15 PM	2	0	8	0	10	0	0	0	0	0	0	44	5	0	49	8	27	0	0	35	94
4:30 PM	1	0	9	0	10	0	0	0	0	0	0	44	1	0	45	13	48	0	0	61	116
4:45 PM	2	0	7	0	9	0	0	0	0	0	0	43	3	0	46	7	59	0	0	66	121
Total	6	0	32	0	38	0	0	0	0	0	0	167	14	0	181	35	176	0	0	211	430
5:00 PM	3	0	5	0	8	0	0	0	0	0	0	54	2	0	56	5	84	0	0	89	153
5:15 PM	1	0	3	0	4	0	0	0	0	0	0	74	2	0	76	9	60	0	0	69	149
5:30 PM	8	0	3	0	11	0	0	0	0	0	0	56	3	0	59	8	79	0	0	87	157
5:45 PM	3	0	1	0	4	0	0	0	0	0	0	49	3	0	52	11	63	0	0	74	130
Total	15	0	12	0	27	0	0	0	0	0	0	233	10	0	243	33	286	0	0	319	589
Grand Total	27	0	72	0	99	0	0	0	0	0	0	977	39	0	1016	94	777	0	0	871	1986
Apprch %	27.3	0.0	72.7	0.0		0.0	0.0	0.0	0.0		0.0	96.2	3.8	0.0		10.8	89.2	0.0	0.0		
Total %	1.4	0.0	3.6	0.0	5.0	0.0	0.0	0.0	0.0	0.0	0.0	49.2	2.0	0.0	51.2	4.7	39.1	0.0	0.0	43.9	
Cars, PU, Vans	21	0	66	0	87	0	0	0	0	0	0	973	31	0	1004	93	771	0	0	864	1955
% Cars, PU, Vans	77.8	0.0	91.7	0.0	87.9	0.0	0.0	0.0	0.0	0.0	0.0	99.6	79.5	0.0	98.8	98.9	99.2	0.0	0.0	99.2	98.4
Heavy Trucks	6	0	6		12	0	0	0		0	0	4	8		12	1	6	0		7	31
%Heavy Trucks	22.2	0.0	8.3	0.0	12.1	0.0	0.0	0.0	0.0	0.0	0.0	0.4	20.5	0.0	1.2	1.1	0.8	0.0	0.0	0.8	1.6

Project ID: 14-9014-012
Location: White Rd & Factory Sho
City: Austell

PEAK HOURS

Day: Tuesday
Date: 1/21/2014

AM

	White Rd Northbound				White Rd Southbound				Factory Shoals Rd Eastbound				Factory Shoals Rd Westbound				
Start Time	Left	Thru	Rgt	App. Total	Left	Thru	Rgt	App. Total	Left	Thru	Rgt	App. Total	Left	Thru	Rgt	App. Total	Int. Total
Peak Hour Analysis from 07:00 AM to 09:00 AM																	
Peak Hour for Entire Intersection Begins at 07:15 AM																	
7:15 AM	0	0	0	0	0	0	0	0	0	89	2	91	5	31	0	36	127
7:30 AM	3	0	4	7	0	0	0	0	0	110	4	114	3	61	0	64	185
7:45 AM	1	0	3	4	0	0	0	0	0	92	1	93	5	49	0	54	151
8:00 AM	0	0	1	1	0	0	0	0	0	84	2	86	3	56	0	59	146
Total Volume	4	0	8	12	0	0	0	0	0	375	9	384	16	197	0	213	609
% App. Total	33.3	0.0	66.7	100	0.0	0.0	0.0	0	0.0	97.7	2.3	100	7.5	92.5	0.0	100	
PHF	0.429				0.000				0.842				0.832				
Cars, PU, Vans	3	0	2	5	0	0	0	0	0	375	6	381	16	196	0	212	598
% Cars, PU, Vans	75.0	0.0	25.0	41.7	0.0	0.0	0.0	0.0	0.0	100.0	66.7	99.2	###	99.5	0.0	99.5	98.2
Heavy Trucks	1	0	6	7	0	0	0	0	0	0	3	3	0	1	0	1	11
%Heavy Trucks	25.0	0.0	75.0	58.3	0.0	0.0	0.0	0.0	0.0	0.0	33.3	0.8	0.0	0.5	0.0	0.5	1.8

PM

	White Rd Northbound				White Rd Southbound				Factory Shoals Rd Eastbound				Factory Shoals Rd Westbound				
Start Time	Left	Thru	Rgt	App. Total	Left	Thru	Rgt	App. Total	Left	Thru	Rgt	App. Total	Left	Thru	Rgt	App. Total	Int. Total
Peak Hour Analysis from 04:00 PM to 06:00 PM																	
Peak Hour for Entire Intersection Begins at 05:00 PM																	
5:00 PM	3	0	5	8	0	0	0	0	0	54	2	56	5	84	0	89	153
5:15 PM	1	0	3	4	0	0	0	0	0	74	2	76	9	60	0	69	149
5:30 PM	8	0	3	11	0	0	0	0	0	56	3	59	8	79	0	87	157
5:45 PM	3	0	1	4	0	0	0	0	0	49	3	52	11	63	0	74	130
Total Volume	15	0	12	27	0	0	0	0	0	233	10	243	33	286	0	319	589
% App. Total	55.6	0.0	44.4	100	0.0	0.0	0.0	0	0.0	95.9	4.1	100	10.3	89.7	0.0	100	
PHF	0.614				0.000				0.799				0.896				
Cars, PU, Vans	13	0	12	25	0	0	0	0	0	233	10	243	33	284	0	317	585
% Cars, PU, Vans	86.7	0.0	###	92.6	0.0	0.0	0.0	0.0	0.0	100.0	###	100.0	###	99.3	0.0	99.4	99.3
Heavy Trucks	2	0	0	2	0	0	0	0	0	0	0	0	0	2	0	2	4
%Heavy Trucks	13.3	0.0	0.0	7.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.7	0.0	0.6	0.7

Project ID: 14-9014-013

Location: Bob White Rd & Riverside Pkwy

City: Austell

Day: Tuesday

Date: 1/21/2014

Peak Start Times

AM	7:00 AM
MD	12:00 AM
PM	4:00 PM

Groups Printed - Cars, PU, Vans - Heavy Trucks

	Bob White Rd Northbound					Bob White Rd Southbound					Riverside Pkwy Eastbound					Riverside Pkwy Westbound					
Start Time	Left	Thru	Rgt	Peds	App. Total	Left	Thru	Rgt	Peds	App. Total	Left	Thru	Rgt	Peds	App. Total	Left	Thru	Rgt	Peds	App. Total	Int. Total
7:00 AM	0	0	0	0	0	2	0	4	0	6	8	177	0	0	185	0	59	4	0	63	254
7:15 AM	0	0	0	0	0	4	0	15	0	19	5	189	0	0	194	0	72	2	0	74	287
7:30 AM	0	0	0	0	0	3	0	5	0	8	8	172	0	0	180	0	81	3	0	84	272
7:45 AM	0	0	0	0	0	3	0	9	0	12	5	182	0	0	187	0	76	2	0	78	277
Total	0	0	0	0	0	12	0	33	0	45	26	720	0	0	746	0	288	11	0	299	1090
8:00 AM	0	0	0	0	0	5	0	4	0	9	6	139	0	0	145	0	67	4	0	71	225
8:15 AM	0	0	0	0	0	5	0	8	0	13	3	104	0	0	107	0	66	7	0	73	193
8:30 AM	0	0	0	0	0	3	0	2	0	5	1	96	0	0	97	0	57	3	0	60	162
8:45 AM	0	0	1	0	1	6	0	1	0	7	4	90	0	0	94	1	51	3	0	55	157
Total	0	0	1	0	1	19	0	15	0	34	14	429	0	0	443	1	241	17	0	259	737
BREAK																					
4:00 PM	0	0	0	0	0	4	0	8	0	12	9	78	0	0	87	0	116	6	0	122	221
4:15 PM	0	0	0	0	0	7	0	7	0	14	2	54	0	0	56	0	90	7	0	97	167
4:30 PM	0	0	0	0	0	3	0	3	0	6	4	76	0	0	80	0	105	13	0	118	204
4:45 PM	0	0	0	0	0	4	0	1	0	5	6	93	0	0	99	0	90	7	0	97	201
Total	0	0	0	0	0	18	0	19	0	37	21	301	0	0	322	0	401	33	0	434	793
5:00 PM	0	0	0	0	0	6	0	4	0	10	4	88	0	0	92	0	140	9	0	149	251
5:15 PM	2	0	0	0	2	3	0	14	0	17	5	88	0	0	93	0	137	6	0	143	255
5:30 PM	0	0	0	0	0	3	0	11	0	14	2	60	1	0	63	1	143	6	0	150	227
5:45 PM	0	0	0	0	0	2	0	11	0	13	6	80	0	0	86	0	130	7	0	137	236
Total	2	0	0	0	2	14	0	40	0	54	17	316	1	0	334	1	550	28	0	579	969
Grand Total	2	0	1	0	3	63	0	107	0	170	78	1766	1	0	1845	2	1480	89	0	1571	3589
Apprch %	66.7	0.0	33.3	0.0		37.1	0.0	62.9	0.0		4.2	95.7	0.1	0.0		0.1	94.2	5.7	0.0		
Total %	0.1	0.0	0.0	0.0	0.1	1.8	0.0	3.0	0.0	4.7	2.2	49.2	0.0	0.0	51.4	0.1	41.2	2.5	0.0	43.8	
Cars, PU, Vans	2	0	1	0	3	23	0	72	0	95	42	1658	1	0	1701	2	1386	43	0	1431	3230
% Cars, PU, Vans	####	0.0	####	0.0	100.0	36.5	0.0	67.3	0.0	55.9	53.8	93.9	####	0.0	92.2	100.0	93.6	48.3	0.0	91.1	90.0
Heavy Trucks	0	0	0	0	0	40	0	35	0	75	36	108	0	0	144	0	94	46	0	140	359
%Heavy Trucks	0.0	0.0	0.0	0.0	0.0	63.5	0.0	32.7	0.0	44.1	46.2	6.1	0.0	0.0	7.8	0.0	6.4	51.7	0.0	8.9	10.0

Project ID: 14-9014-013
Location: Bob White Rd & Riversir
City: Austell

PEAK HOURS

Day: Tuesday
Date: 1/21/2014

AM

	Bob White Rd Northbound				Bob White Rd Southbound				Riverside Pkwy Eastbound				Riverside Pkwy Westbound				
Start Time	Left	Thru	Rgt	App. Total	Left	Thru	Rgt	App. Total	Left	Thru	Rgt	App. Total	Left	Thru	Rgt	App. Total	Int. Total
Peak Hour Analysis from 07:00 AM to 12:00 AM																	
Peak Hour for Entire Intersection Begins at 07:00 AM																	
7:00 AM	0	0	0	0	2	0	4	6	8	177	0	185	0	59	4	63	254
7:15 AM	0	0	0	0	4	0	15	19	5	189	0	194	0	72	2	74	287
7:30 AM	0	0	0	0	3	0	5	8	8	172	0	180	0	81	3	84	272
7:45 AM	0	0	0	0	3	0	9	12	5	182	0	187	0	76	2	78	277
Total Volume	0	0	0	0	12	0	33	45	26	720	0	746	0	288	11	299	1090
% App. Total	0.0	0.0	0.0	0	26.7	0.0	73.3	100	3.5	96.5	0.0	100	0.0	96.3	3.7	100	
PHF	0.000				0.592				0.961				0.890				
Cars, PU, Vans	0	0	0	0	3	0	20	23	18	697	0	715	0	263	4	267	1005
% Cars, PU, Vans	0.0	0.0	0.0	0.0	25.0	0.0	60.6	51.1	69.2	96.8	0.0	95.8	0.0	91.3	36.4	89.3	92.2
Heavy Trucks	0	0	0	0	9	0	13	22	8	23	0	31	0	25	7	32	85
%Heavy Trucks	0.0	0.0	0.0	0.0	75.0	0.0	39.4	48.9	30.8	3.2	0.0	4.2	0.0	8.7	63.6	10.7	7.8

PM

	Bob White Rd Northbound				Bob White Rd Southbound				Riverside Pkwy Eastbound				Riverside Pkwy Westbound				
Start Time	Left	Thru	Rgt	App. Total	Left	Thru	Rgt	App. Total	Left	Thru	Rgt	App. Total	Left	Thru	Rgt	App. Total	Int. Total
Peak Hour Analysis from 04:00 PM to 06:00 PM																	
Peak Hour for Entire Intersection Begins at 05:00 PM																	
5:00 PM	0	0	0	0	6	0	4	10	4	88	0	92	0	140	9	149	251
5:15 PM	2	0	0	2	3	0	14	17	5	88	0	93	0	137	6	143	255
5:30 PM	0	0	0	0	3	0	11	14	2	60	1	63	1	143	6	150	227
5:45 PM	0	0	0	0	2	0	11	13	6	80	0	86	0	130	7	137	236
Total Volume	2	0	0	2	14	0	40	54	17	316	1	334	1	550	28	579	969
	2	0	0		14.14	0	40.4	54.54	17.2	319	1		1	556	28.28		
% App. Total	####	0.0	0.0	100	25.9	0.0	74.1	100	5.1	94.6	0.3	100	0.2	95.0	4.8	100	
PHF	0.250				0.794				0.898				0.965				
Cars, PU, Vans	2	0	0	2	4	0	35	39	8	287	1	296	1	526	12	539	876
% Cars, PU, Vans	####	0.0	0.0	100.0	28.6	0.0	87.5	72.2	47.1	90.8	####	88.6	####	95.6	42.9	93.1	90.4
Heavy Trucks	0	0	0	0	10	0	5	15	9	29	0	38	0	24	16	40	93
%Heavy Trucks	0.0	0.0	0.0	0.0	71.4	0.0	12.5	27.8	52.9	9.2	0.0	11.4	0.0	4.4	57.1	6.9	9.6

VOLUME

Riverside Pkwy s/o Twin Hill Rd/S Service Rd

Day: Tuesday
Date: 1/21/2014

City: Austell
Project #: GA14_9015_001

DAILY TOTALS					NB	SB	EBWB					Total
					6,699	5,986						0
AM Period	NB	SB	EB	WB	TOTAL	PM Period	NB	SB	EB	WB	TOTAL	
00:00	19	7	0	0	26	12:00	126	91	0	0	217	
00:15	15	21	0	0	36	12:15	92	79	0	0	171	
00:30	9	16	0	0	25	12:30	75	86	0	0	161	
00:45	18	61	14	58	32	12:45	89	382	118	374	207	
01:00	15	6	0	0	21	13:00	93	99	0	0	192	
01:15	12	13	0	0	25	13:15	82	67	0	0	149	
01:30	10	19	0	0	29	13:30	86	75	0	0	161	
01:45	7	44	5	43	12	13:45	77	338	82	323	159	
02:00	6	10	0	0	16	14:00	104	78	0	0	182	
02:15	9	10	0	0	19	14:15	78	91	0	0	169	
02:30	8	5	0	0	13	14:30	107	96	0	0	203	
02:45	4	27	9	34	13	14:45	80	369	84	349	164	
03:00	3	6	0	0	9	15:00	127	75	0	0	202	
03:15	11	6	0	0	17	15:15	103	91	0	0	194	
03:30	9	25	0	0	34	15:30	128	57	0	0	185	
03:45	4	27	38	75	42	15:45	90	448	86	309	176	
04:00	14	16	0	0	30	16:00	137	83	0	0	220	
04:15	12	21	0	0	33	16:15	120	94	0	0	214	
04:30	18	34	0	0	52	16:30	175	91	0	0	266	
04:45	17	61	27	98	44	16:45	139	571	76	344	215	
05:00	27	37	0	0	64	17:00	195	89	0	0	284	
05:15	31	59	0	0	90	17:15	162	103	0	0	265	
05:30	33	91	0	0	124	17:30	149	116	0	0	265	
05:45	68	159	108	295	176	17:45	132	638	108	416	240	
06:00	75	74	0	0	149	18:00	138	89	0	0	227	
06:15	107	62	0	0	169	18:15	113	83	0	0	196	
06:30	98	96	0	0	194	18:30	90	78	0	0	168	
06:45	114	394	123	355	237	18:45	79	420	96	346	175	
07:00	119	90	0	0	209	19:00	61	72	0	0	133	
07:15	170	117	0	0	287	19:15	67	57	0	0	124	
07:30	129	112	0	0	241	19:30	80	38	0	0	118	
07:45	151	569	139	458	290	19:45	45	253	45	212	90	
08:00	113	108	0	0	221	20:00	48	40	0	0	88	
08:15	99	131	0	0	230	20:15	46	40	0	0	86	
08:30	85	121	0	0	206	20:30	63	28	0	0	91	
08:45	89	386	110	470	199	20:45	45	202	37	145	82	
09:00	72	108	0	0	180	21:00	65	24	0	0	89	
09:15	83	87	0	0	170	21:15	42	18	0	0	60	
09:30	71	97	0	0	168	21:30	31	13	0	0	44	
09:45	63	289	99	391	162	21:45	29	167	29	84	58	
10:00	74	93	0	0	167	22:00	40	18	0	0	58	
10:15	87	69	0	0	156	22:15	36	17	0	0	53	
10:30	78	70	0	0	148	22:30	27	18	0	0	45	
10:45	65	304	75	307	140	22:45	25	128	31	84	56	
11:00	70	85	0	0	155	23:00	56	18	0	0	74	
11:15	67	79	0	0	146	23:15	34	23	0	0	57	
11:30	90	91	0	0	181	23:30	39	12	0	0	51	
11:45	80	307	85	340	165	23:45	26	155	23	76	49	
TOTALS	2628	2924			5552	TOTALS	4071	3062			7133	
SPLIT %	47.3%	52.7%			43.8%	SPLIT %	57.1%	42.9%			56.2%	

DAILY TOTALS				NB	SB	EB				WB	Total
				6,699	5,986					0	0
AM Peak Hour	07:00	07:45		07:15	PM Peak Hour	16:30	17:00		17:00		
AM Pk Volume	569	499		1039	PM Pk Volume	671	416		1054		
Pk Hr Factor	0.837	0.897		0.896	Pk Hr Factor	0.818	0.853		0.928		
7 - 9 Volume	955	928	0	0	1883	4 - 6 Volume	1209	760	0	0	1969
7 - 9 Peak Hour	07:00	07:45		07:15	4 - 6 Peak Hour	16:30	17:00		17:00		
7 - 9 Pk Volume	569	499	0	0	1039	4 - 6 Pk Volume	671	416	0	0	1054
Pk Hr Factor	0.837	0.897	##	##	0.896	Pk Hr Factor	0.860	0.897	#	##	0.928

VOLUME

Factory Shoals Rd n/o I-20/GA-402 Ramps

Day: Tuesday
Date: 1/21/2014

City: Austell
Project #: GA14_9015_004

DAILY TOTALS						NB	SB	EB						WB	Total
						2,827	2,851							0	0
AM Period	NB	SB	EB	WB	TOTAL	PM Period	NB	SB	EB	WB	TOTAL				
00:00	10	4	0	0	14	12:00	42	31	0	0	73				
00:15	10	2	0	0	12	12:15	33	32	0	0	65				
00:30	4	6	0	0	10	12:30	47	34	0	0	81				
00:45	2	26	7	19	9	12:45	35	157	32	129	67	286			
01:00	2	0	0	0	2	13:00	39	43	0	0	82				
01:15	3	0	0	0	3	13:15	26	36	0	0	62				
01:30	5	2	0	0	7	13:30	35	37	0	0	72				
01:45	3	13	2	4	5	13:45	34	134	37	153	71	287			
02:00	4	0	0	0	4	14:00	39	28	0	0	67				
02:15	2	5	0	0	7	14:15	38	37	0	0	75				
02:30	1	1	0	0	2	14:30	47	68	0	0	115				
02:45	3	10	2	8	5	14:45	38	162	46	179	84	341			
03:00	3	1	0	0	4	15:00	81	53	0	0	134				
03:15	0	1	0	0	1	15:15	51	46	0	0	97				
03:30	5	6	0	0	11	15:30	68	47	0	0	115				
03:45	1	9	5	13	6	15:45	46	246	44	190	90	436			
04:00	1	3	0	0	4	16:00	57	44	0	0	101				
04:15	4	5	0	0	9	16:15	56	39	0	0	95				
04:30	7	10	0	0	17	16:30	74	62	0	0	136				
04:45	6	18	11	29	17	16:45	65	252	61	206	126	458			
05:00	7	13	0	0	20	17:00	109	58	0	0	167				
05:15	2	23	0	0	25	17:15	90	66	0	0	156				
05:30	7	52	0	0	59	17:30	90	72	0	0	162				
05:45	9	25	32	120	41	17:45	61	350	68	264	129	614			
06:00	21	30	0	0	51	18:00	53	62	0	0	115				
06:15	22	36	0	0	58	18:15	38	53	0	0	91				
06:30	42	63	0	0	105	18:30	34	37	0	0	71				
06:45	59	144	87	216	146	18:45	32	157	19	171	51	328			
07:00	92	55	0	0	147	19:00	28	28	0	0	56				
07:15	82	44	0	0	126	19:15	17	23	0	0	40				
07:30	89	97	0	0	186	19:30	53	13	0	0	66				
07:45	68	331	112	308	180	19:45	20	118	23	87	43	205			
08:00	74	63	0	0	137	20:00	26	26	0	0	52				
08:15	49	55	0	0	104	20:15	13	28	0	0	41				
08:30	46	45	0	0	91	20:30	13	15	0	0	28				
08:45	32	201	39	202	71	20:45	12	64	15	84	27	148			
09:00	20	40	0	0	60	21:00	13	13	0	0	26				
09:15	23	30	0	0	53	21:15	10	11	0	0	21				
09:30	30	31	0	0	61	21:30	7	14	0	0	21				
09:45	23	96	34	135	57	21:45	4	34	16	54	20	88			
10:00	9	20	0	0	29	22:00	9	10	0	0	19				
10:15	11	20	0	0	31	22:15	10	8	0	0	18				
10:30	27	23	0	0	50	22:30	9	14	0	0	23				
10:45	21	68	26	89	47	22:45	6	34	10	42	16	76			
11:00	21	24	0	0	45	23:00	21	6	0	0	27				
11:15	30	30	0	0	60	23:15	12	9	0	0	21				
11:30	41	32	0	0	73	23:30	13	4	0	0	17				
11:45	33	125	39	125	72	23:45	7	53	5	24	12	77			
TOTALS	10661268				2334	TOTALS	17611583				3344				
SPLIT %	45.7%54.3%				41.1%	SPLIT %	52.7%47.3%				58.9%				

DAILY TOTALS						NB	SB					EB	WB	Total	
						2,827	2,851					0	0	5,678	

AM Peak Hour	07:00	07:30			07:00	PM Peak Hour	16:45	17:15			17:00
AM Pk Volume	331	327			639	PM Pk Volume	354	268			614
Pk Hr Factor	0.899	0.730			0.859	Pk Hr Factor	0.817	0.809			0.919
7 - 9 Volume	532	510	0	0	1042	4 - 6 Volume	602	470	0	0	1072
7 - 9 Peak Hour	07:00	07:30			07:00	4 - 6 Peak Hour	16:45	17:00			17:00
7 - 9 Pk Volume	331	327	0	0	639	4 - 6 Pk Volume	354	264	0	0	614
Pk Hr Factor	0.899	0.730	0.000	0.000	0.859	Pk Hr Factor	0.812	0.917	0.000	0.000	0.919

Appendix C: Trip Generation and Distribution

Phase Time Period Trip Generation
Weekday Average Daily Trips

Project : General Warehouse
Alternative : Alternative 1
Phase : Phase 1

Open Date : 2/18/2014
Analysis Date : 2/18/2014

ITE	Land Use	Enter	Exit	Total
150	WAREHOUSE 1	1113	1112	2225
	625 Gross Floor Area 1000 SF			

Unadjusted Driveway Volume	1113	1112	2225
Unadjusted Pass-By Trips	0	0	0
Internal Vehicle Trips	0	0	0
Adjusted Driveway Volume	1113	1112	2225
Adjusted Pass-By Trips	0	0	0
Adjusted Total Volume Added to Adjacent Streets	1113	1112	2225

Phase Time Period Trip Generation
Weekday AM Peak Hour of Generator

Project : General Warehouse
Alternative : Alternative 1
Phase : Phase 1

Open Date : 2/18/2014
Analysis Date : 2/18/2014

ITE	Land Use	Enter	Exit	Total
150	WAREHOUSE 1	171	92	263
	625 Gross Floor Area 1000 SF			

Unadjusted Driveway Volume	171	92	263
Unadjusted Pass-By Trips	0	0	0
Internal Vehicle Trips	0	0	0
Adjusted Driveway Volume	171	92	263
Adjusted Pass-By Trips	0	0	0
Adjusted Total Volume Added to Adjacent Streets	171	92	263


Phase Time Period Trip Generation
Weekday PM Peak Hour of Generator

Project : General Warehouse
Alternative : Alternative 1
Phase : Phase 1

Open Date : 2/18/2014
Analysis Date : 2/18/2014

ITE	Land Use	Enter	Exit	Total
150	WAREHOUSE 1	53	228	281
	625 Gross Floor Area 1000 SF			

Unadjusted Driveway Volume	53	228	281
Unadjusted Pass-By Trips	0	0	0
Internal Vehicle Trips	0	0	0
Adjusted Driveway Volume	53	228	281
Adjusted Pass-By Trips	0	0	0
Adjusted Total Volume Added to Adjacent Streets	53	228	281



Legend: AM (PM)

SITE GENERATED TRAFFIC PEAK HOUR DISTRIBUTION

OAKMONT DRI
AUSTELL, GA

FIGURE

Project No.	047-13-133
Design By:	CM
Drawn By:	CM
Checked By:	BAH
Date:	03/04/2014
Scale:	NTS



Appendix D: Existing Year-2014 Intersection Capacity Analyses Sheets (ICAS)

TWO-WAY STOP CONTROL SUMMARY

Analyst: CMaddox
 Agency/Co.: SEI
 Date Performed: 3/3/2014
 Analysis Time Period: AM Peak
 Intersection: Factory Shoals Rd & White Rd
 Jurisdiction: Cobb Co.
 Units: U. S. Customary
 Analysis Year: 2014
 Project ID:
 East/West Street: Factory Shoals Rd
 North/South Street: White Rd
 Intersection Orientation: EW

Study period (hrs): 0.25

Vehicle Volumes and Adjustments

Major Street:	Approach Movement	Eastbound				Westbound		
		1 L	2 T	3 R		4 L	5 T	6 R
Volume			375	9		16	197	
Peak-Hour Factor, PHF			0.92	0.92		0.92	0.92	
Hourly Flow Rate, HFR			407	9		17	214	
Percent Heavy Vehicles			--	--		2	--	--
Median Type/Storage		Undivided			/			
RT Channelized?								
Lanes			1	0		0	1	
Configuration			TR			LT		
Upstream Signal?			No			No		

Minor Street:	Approach Movement	Northbound				Southbound		
		7 L	8 T	9 R		10 L	11 T	12 R
Volume		4		8				
Peak Hour Factor, PHF		0.92		0.92				
Hourly Flow Rate, HFR		4		8				
Percent Heavy Vehicles		25		75				
Percent Grade (%)			0			0		
Flared Approach: Exists?/Storage		No			/			
Lanes		0		0				
Configuration			LR					

Delay, Queue Length, and Level of Service

Approach	EB	WB	Northbound			Southbound				
Movement	1	4		7	8	9		10	11	12
Lane Config		LT			LR					
v (vph)		17			12					
C(m) (vph)		1143			461					
v/c		0.01			0.03					
95% queue length		0.05			0.08					
Control Delay		8.2			13.0					
LOS		A			B					
Approach Delay					13.0					
Approach LOS					B					

HCS+: Unsignalized Intersections Release 5.6

Phone:
E-Mail:

Fax:

TWO-WAY STOP CONTROL(TWSC) ANALYSIS

Analyst: CMaddox
 Agency/Co.: SEI
 Date Performed: 3/3/2014
 Analysis Time Period: AM Peak
 Intersection: Factory Shoals Rd & White Rd
 Jurisdiction: Cobb Co.
 Units: U. S. Customary
 Analysis Year: 2014
 Project ID:
 East/West Street: Factory Shoals Rd
 North/South Street: White Rd
 Intersection Orientation: EW

Study period (hrs): 0.25

Vehicle Volumes and Adjustments

Major Street Movements	1 L	2 T	3 R	4 L	5 T	6 R
Volume		375	9	16	197	
Peak-Hour Factor, PHF		0.92	0.92	0.92	0.92	
Peak-15 Minute Volume		102	2	4	54	
Hourly Flow Rate, HFR		407	9	17	214	
Percent Heavy Vehicles		--	--	2	--	--
Median Type/Storage	Undivided			/		
RT Channelized?						
Lanes		1	0	0	1	
Configuration			TR		LT	
Upstream Signal?		No			No	
Minor Street Movements	7 L	8 T	9 R	10 L	11 T	12 R

Volume	4		8			
Peak Hour Factor, PHF	0.92		0.92			
Peak-15 Minute Volume	1		2			
Hourly Flow Rate, HFR	4		8			
Percent Heavy Vehicles	25		75			
Percent Grade (%)		0			0	
Flared Approach: Exists?/Storage			No	/		/
RT Channelized?						
Lanes	0		0			
Configuration		LR				

Pedestrian Volumes and Adjustments

Movements	13	14	15	16
Flow (ped/hr)	0	0	0	0

Lane Width (ft)	12.0	12.0	12.0	12.0
Walking Speed (ft/sec)	4.0	4.0	4.0	4.0
Percent Blockage	0	0	0	0

Upstream Signal Data							
	Prog. Flow vph	Sat Flow vph	Arrival Type	Green Time sec	Cycle Length sec	Prog. Speed mph	Distance to Signal feet
S2 Left-Turn Through							
S5 Left-Turn Through							

Worksheet 3-Data for Computing Effect of Delay to Major Street Vehicles

	Movement 2	Movement 5
Shared ln volume, major th vehicles:		214
Shared ln volume, major rt vehicles:		0
Sat flow rate, major th vehicles:		1700
Sat flow rate, major rt vehicles:		1700
Number of major street through lanes:		1

Worksheet 4-Critical Gap and Follow-up Time Calculation

Critical Gap Calculation								
Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
t(c,base)		4.1	7.1		6.2			
t(c,hv)	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
P(hv)		2	25		75			
t(c,g)			0.20	0.20	0.10	0.20	0.20	0.10
Percent Grade			0.00	0.00	0.00	0.00	0.00	0.00
t(3,lt)		0.00	0.70		0.00			
t(c,T): 1-stage	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
2-stage	0.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
t(c) 1-stage		4.1	6.7		6.9			
2-stage								

Follow-Up Time Calculations								
Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
t(f,base)		2.20	3.50		3.30			
t(f,HV)	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
P(HV)		2	25		75			
t(f)		2.2	3.7		4.0			

Worksheet 5-Effect of Upstream Signals

Computation 1-Queue Clearance Time at Upstream Signal				
	Movement 2		Movement 5	
	V(t)	V(l,prot)	V(t)	V(l,prot)
V prog				

Total Saturation Flow Rate, s (vph)
Arrival Type
Effective Green, g (sec)
Cycle Length, C (sec)
Rp (from Exhibit 16-11)
Proportion vehicles arriving on green P
g(q1)
g(q2)
g(q)

Computation 2-Proportion of TWSC Intersection Time blocked

	Movement 2		Movement 5	
	V(t)	V(l,prot)	V(t)	V(l,prot)

alpha
beta
Travel time, t(a) (sec)
Smoothing Factor, F
Proportion of conflicting flow, f
Max platooned flow, V(c,max)
Min platooned flow, V(c,min)
Duration of blocked period, t(p)
Proportion time blocked, p

	0.000	0.000
--	-------	-------

Computation 3-Platoon Event Periods Result

p(2)	0.000
p(5)	0.000
p(dom)	
p(subo)	
Constrained or unconstrained?	

Proportion unblocked for minor movements, p(x)	(1) Single-stage Process	(2) Two-Stage Stage I	(3) Process Stage II
--	-----------------------------	--------------------------	-------------------------

p(1)
p(4)
p(7)
p(8)
p(9)
p(10)
p(11)
p(12)

Computation 4 and 5
Single-Stage Process

Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
----------	--------	--------	--------	--------	--------	---------	---------	---------

V c, x		416	660		412			
s								
Px								
V c, u, x								

C r, x
C plat, x

Two-Stage Process	7	8	10	11
-------------------	---	---	----	----

	Stage1	Stage2	Stage1	Stage2	Stage1	Stage2	Stage1	Stage2
--	--------	--------	--------	--------	--------	--------	--------	--------

V(c,x)
s
P(x)
V(c,u,x)

1500

C(r,x)
C(plat,x)

Worksheet 6-Impedance and Capacity Equations

Step 1: RT from Minor St.	9	12
---------------------------	---	----

Conflicting Flows	412	
Potential Capacity	509	
Pedestrian Impedance Factor	1.00	1.00
Movement Capacity	509	
Probability of Queue free St.	0.98	1.00

Step 2: LT from Major St.	4	1
---------------------------	---	---

Conflicting Flows	416	
Potential Capacity	1143	
Pedestrian Impedance Factor	1.00	1.00
Movement Capacity	1143	
Probability of Queue free St.	0.99	1.00
Maj L-Shared Prob Q free St.	0.98	

Step 3: TH from Minor St.	8	11
---------------------------	---	----

Conflicting Flows		
Potential Capacity		
Pedestrian Impedance Factor	1.00	1.00
Cap. Adj. factor due to Impeding mvmnt	0.98	0.98
Movement Capacity		
Probability of Queue free St.	1.00	1.00

Step 4: LT from Minor St.	7	10
---------------------------	---	----

Conflicting Flows	660	
Potential Capacity	394	
Pedestrian Impedance Factor	1.00	1.00
Maj. L, Min T Impedance factor		0.98
Maj. L, Min T Adj. Imp Factor.		0.99
Cap. Adj. factor due to Impeding mvmnt	0.99	0.97
Movement Capacity	388	

Worksheet 7-Computation of the Effect of Two-stage Gap Acceptance

Step 3: TH from Minor St.	8	11
---------------------------	---	----

Part 1 - First Stage
Conflicting Flows
Potential Capacity
Pedestrian Impedance Factor
Cap. Adj. factor due to Impeding mvmnt
Movement Capacity
Probability of Queue free St.

Part 2 - Second Stage
Conflicting Flows
Potential Capacity
Pedestrian Impedance Factor
Cap. Adj. factor due to Impeding mvmnt
Movement Capacity

Part 3 - Single Stage
Conflicting Flows
Potential Capacity
Pedestrian Impedance Factor 1.00 1.00
Cap. Adj. factor due to Impeding mvmnt 0.98 0.98
Movement Capacity

Result for 2 stage process:

a
y
C t
Probability of Queue free St. 1.00 1.00

Step 4: LT from Minor St. 7 10

Part 1 - First Stage
Conflicting Flows
Potential Capacity
Pedestrian Impedance Factor
Cap. Adj. factor due to Impeding mvmnt
Movement Capacity

Part 2 - Second Stage
Conflicting Flows
Potential Capacity
Pedestrian Impedance Factor
Cap. Adj. factor due to Impeding mvmnt
Movement Capacity

Part 3 - Single Stage
Conflicting Flows 660
Potential Capacity 394
Pedestrian Impedance Factor 1.00 1.00
Maj. L, Min T Impedance factor 0.98
Maj. L, Min T Adj. Imp Factor. 0.99
Cap. Adj. factor due to Impeding mvmnt 0.99 0.97
Movement Capacity 388

Results for Two-stage process:

a
y
C t 388

Worksheet 8-Shared Lane Calculations

Movement	7 L	8 T	9 R	10 L	11 T	12 R
Volume (vph)	4		8			
Movement Capacity (vph)	388		509			
Shared Lane Capacity (vph)		461				

Worksheet 9-Computation of Effect of Flared Minor Street Approaches

Movement	7 L	8 T	9 R	10 L	11 T	12 R
C sep	388		509			
Volume	4		8			
Delay						
Q sep						
Q sep +1 round (Qsep +1)						
n max						
C sh		461				
SUM C sep						
n						
C act						

Worksheet 10-Delay, Queue Length, and Level of Service

Movement	1	4	7	8	9	10	11	12
Lane Config		LT		LR				
v (vph)		17		12				
C(m) (vph)		1143		461				
v/c		0.01		0.03				
95% queue length		0.05		0.08				
Control Delay		8.2		13.0				
LOS		A		B				
Approach Delay				13.0				
Approach LOS				B				

Worksheet 11-Shared Major LT Impedance and Delay

	Movement 2	Movement 5
p(oj)	1.00	0.99
v(il), Volume for stream 2 or 5		214
v(i2), Volume for stream 3 or 6		0
s(il), Saturation flow rate for stream 2 or 5		1700
s(i2), Saturation flow rate for stream 3 or 6		1700
P*(oj)		0.98
d(M,LT), Delay for stream 1 or 4		8.2
N, Number of major street through lanes		1
d(rank,1) Delay for stream 2 or 5		0.1

TWO-WAY STOP CONTROL SUMMARY

Analyst: CMaddox
 Agency/Co.: SEI
 Date Performed: 3/3/2014
 Analysis Time Period: PM Peak
 Intersection: Factory Shoals Rd & White Rd
 Jurisdiction: Cobb Co.
 Units: U. S. Customary
 Analysis Year: 2014
 Project ID:
 East/West Street: Factory Shoals Rd
 North/South Street: White Rd
 Intersection Orientation: EW

Study period (hrs): 0.25

Vehicle Volumes and Adjustments

Major Street:		Eastbound			Westbound		
Approach Movement	1 L	2 T	3 R		4 L	5 T	6 R
Volume		233	10		33	286	
Peak-Hour Factor, PHF		0.92	0.92		0.92	0.92	
Hourly Flow Rate, HFR		253	10		35	310	
Percent Heavy Vehicles		--	--		2	--	--
Median Type/Storage		Undivided			/		
RT Channelized?							
Lanes		1	0		0	1	
Configuration			TR			LT	
Upstream Signal?		No				No	
Minor Street:		Northbound			Southbound		
Approach Movement	7 L	8 T	9 R		10 L	11 T	12 R
Volume	15		12				
Peak Hour Factor, PHF	0.92		0.92				
Hourly Flow Rate, HFR	16		13				
Percent Heavy Vehicles	14		2				
Percent Grade (%)		0				0	
Flared Approach: Exists?/Storage			No	/			/
Lanes	0		0				
Configuration		LR					

Delay, Queue Length, and Level of Service

Approach	EB	WB	Northbound			Southbound				
Movement	1	4		7	8	9		10	11	12
Lane Config		LT			LR					
v (vph)		35			29					
C(m) (vph)		1301			522					
v/c		0.03			0.06					
95% queue length		0.08			0.18					
Control Delay		7.8			12.3					
LOS		A			B					
Approach Delay					12.3					
Approach LOS					B					

HCS+: Unsignalized Intersections Release 5.6

Phone:
E-Mail:

Fax:

TWO-WAY STOP CONTROL(TWSC) ANALYSIS

Analyst: CMaddox
 Agency/Co.: SEI
 Date Performed: 3/3/2014
 Analysis Time Period: PM Peak
 Intersection: Factory Shoals Rd & White Rd
 Jurisdiction: Cobb Co.
 Units: U. S. Customary
 Analysis Year: 2014
 Project ID:
 East/West Street: Factory Shoals Rd
 North/South Street: White Rd
 Intersection Orientation: EW

Study period (hrs): 0.25

Vehicle Volumes and Adjustments

Major Street Movements	1 L	2 T	3 R	4 L	5 T	6 R
Volume		233	10	33	286	
Peak-Hour Factor, PHF		0.92	0.92	0.92	0.92	
Peak-15 Minute Volume		63	3	9	78	
Hourly Flow Rate, HFR		253	10	35	310	
Percent Heavy Vehicles		--	--	2	--	--
Median Type/Storage	Undivided			/		
RT Channelized?						
Lanes		1	0	0	1	
Configuration			TR		LT	
Upstream Signal?		No			No	
Minor Street Movements	7 L	8 T	9 R	10 L	11 T	12 R

Volume	15		12			
Peak Hour Factor, PHF	0.92		0.92			
Peak-15 Minute Volume	4		3			
Hourly Flow Rate, HFR	16		13			
Percent Heavy Vehicles	14		2			
Percent Grade (%)		0			0	
Flared Approach: Exists?/Storage			No	/		/
RT Channelized?						
Lanes	0		0			
Configuration		LR				

Pedestrian Volumes and Adjustments

Movements	13	14	15	16
Flow (ped/hr)	0	0	0	0

Lane Width (ft)	12.0	12.0	12.0	12.0
Walking Speed (ft/sec)	4.0	4.0	4.0	4.0
Percent Blockage	0	0	0	0

Upstream Signal Data							
	Prog. Flow vph	Sat Flow vph	Arrival Type	Green Time sec	Cycle Length sec	Prog. Speed mph	Distance to Signal feet
S2 Left-Turn Through							
S5 Left-Turn Through							

Worksheet 3-Data for Computing Effect of Delay to Major Street Vehicles

	Movement 2	Movement 5
Shared ln volume, major th vehicles:		310
Shared ln volume, major rt vehicles:		0
Sat flow rate, major th vehicles:		1700
Sat flow rate, major rt vehicles:		1700
Number of major street through lanes:		1

Worksheet 4-Critical Gap and Follow-up Time Calculation

Critical Gap Calculation								
Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
t(c,base)		4.1	7.1		6.2			
t(c,hv)	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
P(hv)		2	14		2			
t(c,g)			0.20	0.20	0.10	0.20	0.20	0.10
Percent Grade			0.00	0.00	0.00	0.00	0.00	0.00
t(3,lt)		0.00	0.70		0.00			
t(c,T): 1-stage	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
2-stage	0.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
t(c) 1-stage		4.1	6.5		6.2			
2-stage								

Follow-Up Time Calculations								
Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
t(f,base)		2.20	3.50		3.30			
t(f,HV)	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
P(HV)		2	14		2			
t(f)		2.2	3.6		3.3			

Worksheet 5-Effect of Upstream Signals

Computation 1-Queue Clearance Time at Upstream Signal				
	Movement 2		Movement 5	
	V(t)	V(l,prot)	V(t)	V(l,prot)
V prog				

Total Saturation Flow Rate, s (vph)
Arrival Type
Effective Green, g (sec)
Cycle Length, C (sec)
Rp (from Exhibit 16-11)
Proportion vehicles arriving on green P
g(q1)
g(q2)
g(q)

Computation 2-Proportion of TWSC Intersection Time blocked

	Movement 2		Movement 5	
	V(t)	V(l,prot)	V(t)	V(l,prot)

alpha
beta
Travel time, t(a) (sec)
Smoothing Factor, F
Proportion of conflicting flow, f
Max platooned flow, V(c,max)
Min platooned flow, V(c,min)
Duration of blocked period, t(p)
Proportion time blocked, p

	0.000	0.000
--	-------	-------

Computation 3-Platoon Event Periods Result

p(2)	0.000
p(5)	0.000
p(dom)	
p(subo)	
Constrained or unconstrained?	

Proportion unblocked for minor movements, p(x)	(1) Single-stage Process	(2) Two-Stage Stage I	(3) Process Stage II
--	-----------------------------	--------------------------	-------------------------

p(1)
p(4)
p(7)
p(8)
p(9)
p(10)
p(11)
p(12)

Computation 4 and 5
Single-Stage Process

Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
----------	--------	--------	--------	--------	--------	---------	---------	---------

V c, x		263	638		258			
s								
Px								
V c, u, x								

C r, x
C plat, x

Two-Stage Process	7	8	10	11
-------------------	---	---	----	----

	Stage1	Stage2	Stage1	Stage2	Stage1	Stage2	Stage1	Stage2
--	--------	--------	--------	--------	--------	--------	--------	--------

V(c,x)
s
P(x)
V(c,u,x)

C(r,x)
C(plat,x)

Worksheet 6-Impedance and Capacity Equations

Step 1: RT from Minor St.	9	12
---------------------------	---	----

Conflicting Flows	258	
Potential Capacity	781	
Pedestrian Impedance Factor	1.00	1.00
Movement Capacity	781	
Probability of Queue free St.	0.98	1.00

Step 2: LT from Major St.	4	1
---------------------------	---	---

Conflicting Flows	263	
Potential Capacity	1301	
Pedestrian Impedance Factor	1.00	1.00
Movement Capacity	1301	
Probability of Queue free St.	0.97	1.00
Maj L-Shared Prob Q free St.	0.97	

Step 3: TH from Minor St.	8	11
---------------------------	---	----

Conflicting Flows		
Potential Capacity		
Pedestrian Impedance Factor	1.00	1.00
Cap. Adj. factor due to Impeding mvmnt	0.97	0.97
Movement Capacity		
Probability of Queue free St.	1.00	1.00

Step 4: LT from Minor St.	7	10
---------------------------	---	----

Conflicting Flows	638	
Potential Capacity	422	
Pedestrian Impedance Factor	1.00	1.00
Maj. L, Min T Impedance factor		0.97
Maj. L, Min T Adj. Imp Factor.		0.97
Cap. Adj. factor due to Impeding mvmnt	0.97	0.96
Movement Capacity	411	

Worksheet 7-Computation of the Effect of Two-stage Gap Acceptance

Step 3: TH from Minor St.	8	11
---------------------------	---	----

Part 1 - First Stage
Conflicting Flows
Potential Capacity
Pedestrian Impedance Factor
Cap. Adj. factor due to Impeding mvmnt
Movement Capacity
Probability of Queue free St.

Part 2 - Second Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor
 Cap. Adj. factor due to Impeding mvmnt
 Movement Capacity

Part 3 - Single Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor 1.00 1.00
 Cap. Adj. factor due to Impeding mvmnt 0.97 0.97
 Movement Capacity

Result for 2 stage process:
 a
 y
 C t
 Probability of Queue free St. 1.00 1.00

Step 4: LT from Minor St. 7 10

Part 1 - First Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor
 Cap. Adj. factor due to Impeding mvmnt
 Movement Capacity

Part 2 - Second Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor
 Cap. Adj. factor due to Impeding mvmnt
 Movement Capacity

Part 3 - Single Stage
 Conflicting Flows 638
 Potential Capacity 422
 Pedestrian Impedance Factor 1.00 1.00
 Maj. L, Min T Impedance factor 0.97
 Maj. L, Min T Adj. Imp Factor. 0.97
 Cap. Adj. factor due to Impeding mvmnt 0.97 0.96
 Movement Capacity 411

Results for Two-stage process:
 a
 y
 C t 411

Worksheet 8-Shared Lane Calculations

Movement	7 L	8 T	9 R	10 L	11 T	12 R
Volume (vph)	16		13			
Movement Capacity (vph)	411		781			
Shared Lane Capacity (vph)		522				

Worksheet 9-Computation of Effect of Flared Minor Street Approaches

Movement	7 L	8 T	9 R	10 L	11 T	12 R
C sep	411		781			
Volume	16		13			
Delay						
Q sep						
Q sep +1 round (Qsep +1)						
n max						
C sh		522				
SUM C sep						
n						
C act						

Worksheet 10-Delay, Queue Length, and Level of Service

Movement	1	4	7	8	9	10	11	12
Lane Config		LT		LR				
v (vph)		35		29				
C(m) (vph)		1301		522				
v/c		0.03		0.06				
95% queue length		0.08		0.18				
Control Delay		7.8		12.3				
LOS		A		B				
Approach Delay				12.3				
Approach LOS				B				

Worksheet 11-Shared Major LT Impedance and Delay

	Movement 2	Movement 5
p(oj)	1.00	0.97
v(il), Volume for stream 2 or 5		310
v(i2), Volume for stream 3 or 6		0
s(il), Saturation flow rate for stream 2 or 5		1700
s(i2), Saturation flow rate for stream 3 or 6		1700
P*(oj)		0.97
d(M,LT), Delay for stream 1 or 4		7.8
N, Number of major street through lanes		1
d(rank,1) Delay for stream 2 or 5		0.3

HCS+: Unsignalized Intersections Release 5.6

Phone:
E-Mail:

Fax:

TWO-WAY STOP CONTROL(TWSC) ANALYSIS

Analyst: CMaddox
Agency/Co.: SEI
Date Performed: 3/3/2014
Analysis Time Period: AM Peak
Intersection: Riverside Pkwy & White Rd
Jurisdiction: Cobb Co.
Units: U. S. Customary
Analysis Year: 2014
Project ID:
East/West Street: Riverside Pkwy
North/South Street: White Rd
Intersection Orientation: EW

Study period (hrs): 0.25

Vehicle Volumes and Adjustments

Major Street Movements	1 L	2 T	3 R	4 L	5 T	6 R
Volume	26	720			288	11
Peak-Hour Factor, PHF	0.92	0.92			0.92	0.92
Peak-15 Minute Volume	7	196			78	3
Hourly Flow Rate, HFR	28	782			313	11
Percent Heavy Vehicles	31	--	--		--	--
Median Type/Storage	Undivided			/		
RT Channelized?						
Lanes	0	1			1	0
Configuration	LT				TR	
Upstream Signal?		No			No	
Minor Street Movements	7 L	8 T	9 R	10 L	11 T	12 R

Volume				12		33
Peak Hour Factor, PHF				0.92		0.92
Peak-15 Minute Volume				3		9
Hourly Flow Rate, HFR				13		35
Percent Heavy Vehicles				75		40
Percent Grade (%)		0			0	
Flared Approach: Exists?/Storage				/		No /
RT Channelized?						
Lanes				0		0
Configuration					LR	

Pedestrian Volumes and Adjustments

Movements	13	14	15	16
Flow (ped/hr)	0	0	0	0

Lane Width (ft)	12.0	12.0	12.0	12.0
Walking Speed (ft/sec)	4.0	4.0	4.0	4.0
Percent Blockage	0	0	0	0

Upstream Signal Data							
	Prog. Flow vph	Sat Flow vph	Arrival Type	Green Time sec	Cycle Length sec	Prog. Speed mph	Distance to Signal feet
S2 Left-Turn Through							
S5 Left-Turn Through							

Worksheet 3-Data for Computing Effect of Delay to Major Street Vehicles

	Movement 2	Movement 5
Shared ln volume, major th vehicles:	782	
Shared ln volume, major rt vehicles:	0	
Sat flow rate, major th vehicles:	1700	
Sat flow rate, major rt vehicles:	1700	
Number of major street through lanes:	1	

Worksheet 4-Critical Gap and Follow-up Time Calculation

Critical Gap Calculation								
Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
t(c,base)	4.1					7.1		6.2
t(c,hv)	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
P(hv)	31					75		40
t(c,g)			0.20	0.20	0.10	0.20	0.20	0.10
Percent Grade			0.00	0.00	0.00	0.00	0.00	0.00
t(3,lt)	0.00					0.70		0.00
t(c,T): 1-stage	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
2-stage	0.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
t(c) 1-stage	4.4					7.2		6.6
2-stage								

Follow-Up Time Calculations								
Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
t(f,base)	2.20					3.50		3.30
t(f,HV)	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
P(HV)	31					75		40
t(f)	2.5					4.2		3.7

Worksheet 5-Effect of Upstream Signals

Computation 1-Queue Clearance Time at Upstream Signal				
	Movement 2		Movement 5	
	V(t)	V(l,prot)	V(t)	V(l,prot)
V prog				

Total Saturation Flow Rate, s (vph)
Arrival Type
Effective Green, g (sec)
Cycle Length, C (sec)
Rp (from Exhibit 16-11)
Proportion vehicles arriving on green P
g(q1)
g(q2)
g(q)

Computation 2-Proportion of TWSC Intersection Time blocked

	Movement 2		Movement 5	
	V(t)	V(l,prot)	V(t)	V(l,prot)

alpha
beta
Travel time, t(a) (sec)
Smoothing Factor, F
Proportion of conflicting flow, f
Max platooned flow, V(c,max)
Min platooned flow, V(c,min)
Duration of blocked period, t(p)
Proportion time blocked, p

	0.000	0.000
--	-------	-------

Computation 3-Platoon Event Periods

	Result
--	--------

p(2)	0.000
p(5)	0.000
p(dom)	
p(subo)	
Constrained or unconstrained?	

Proportion unblocked for minor movements, p(x)	(1) Single-stage Process	(2) Two-Stage Process Stage I	(3) Process Stage II
--	-----------------------------	-------------------------------------	----------------------------

p(1)
p(4)
p(7)
p(8)
p(9)
p(10)
p(11)
p(12)

Computation 4 and 5
Single-Stage Process
Movement

	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
V c, x	324					1156		318
S								
Px								
V c, u, x								
C r, x								
C plat, x								

Two-Stage Process

7	8	10	11
---	---	----	----

V(c,x)
s
P(x)
V(c,u,x)

1500

C(r,x)
C(plat,x)

Worksheet 6-Impedance and Capacity Equations

Step 1: RT from Minor St. 9 12

Conflicting Flows 318
Potential Capacity 643
Pedestrian Impedance Factor 1.00 1.00
Movement Capacity 643
Probability of Queue free St. 1.00 0.95

Step 2: LT from Major St. 4 1

Conflicting Flows 324
Potential Capacity 1089
Pedestrian Impedance Factor 1.00 1.00
Movement Capacity 1089
Probability of Queue free St. 1.00 0.97
Maj L-Shared Prob Q free St. 0.95

Step 3: TH from Minor St. 8 11

Conflicting Flows
Potential Capacity
Pedestrian Impedance Factor 1.00 1.00
Cap. Adj. factor due to Impeding mvmnt 0.95 0.95
Movement Capacity
Probability of Queue free St. 1.00 1.00

Step 4: LT from Minor St. 7 10

Conflicting Flows 1156
Potential Capacity 158
Pedestrian Impedance Factor 1.00 1.00
Maj. L, Min T Impedance factor 0.95
Maj. L, Min T Adj. Imp Factor. 0.96
Cap. Adj. factor due to Impeding mvmnt 0.91 0.97
Movement Capacity 154

Worksheet 7-Computation of the Effect of Two-stage Gap Acceptance

Step 3: TH from Minor St. 8 11

Part 1 - First Stage
Conflicting Flows
Potential Capacity
Pedestrian Impedance Factor
Cap. Adj. factor due to Impeding mvmnt
Movement Capacity
Probability of Queue free St.

Part 2 - Second Stage
Conflicting Flows
Potential Capacity
Pedestrian Impedance Factor
Cap. Adj. factor due to Impeding mvmnt
Movement Capacity

Part 3 - Single Stage
Conflicting Flows
Potential Capacity
Pedestrian Impedance Factor 1.00 1.00
Cap. Adj. factor due to Impeding mvmnt 0.95 0.95
Movement Capacity

Result for 2 stage process:

a
y
C t
Probability of Queue free St. 1.00 1.00

Step 4: LT from Minor St. 7 10

Part 1 - First Stage
Conflicting Flows
Potential Capacity
Pedestrian Impedance Factor
Cap. Adj. factor due to Impeding mvmnt
Movement Capacity

Part 2 - Second Stage
Conflicting Flows
Potential Capacity
Pedestrian Impedance Factor
Cap. Adj. factor due to Impeding mvmnt
Movement Capacity

Part 3 - Single Stage
Conflicting Flows 1156
Potential Capacity 158
Pedestrian Impedance Factor 1.00 1.00
Maj. L, Min T Impedance factor 0.95
Maj. L, Min T Adj. Imp Factor. 0.96
Cap. Adj. factor due to Impeding mvmnt 0.91 0.97
Movement Capacity 154

Results for Two-stage process:

a
y
C t 154

Worksheet 8-Shared Lane Calculations

Movement	7 L	8 T	9 R	10 L	11 T	12 R
Volume (vph)				13		35
Movement Capacity (vph)				154		643
Shared Lane Capacity (vph)					346	

Worksheet 9-Computation of Effect of Flared Minor Street Approaches

Movement	7 L	8 T	9 R	10 L	11 T	12 R
C sep				154		643
Volume				13		35
Delay						
Q sep						
Q sep +1						
round (Qsep +1)						
n max						
C sh					346	
SUM C sep						
n						
C act						

Worksheet 10-Delay, Queue Length, and Level of Service

Movement	1	4	7	8	9	10	11	12
Lane Config	LT						LR	
v (vph)	28						48	
C(m) (vph)	1089						346	
v/c	0.03						0.14	
95% queue length	0.08						0.48	
Control Delay	8.4						17.1	
LOS	A						C	
Approach Delay							17.1	
Approach LOS							C	

Worksheet 11-Shared Major LT Impedance and Delay

	Movement 2	Movement 5
p(oj)	0.97	1.00
v(il), Volume for stream 2 or 5	782	
v(i2), Volume for stream 3 or 6	0	
s(il), Saturation flow rate for stream 2 or 5	1700	
s(i2), Saturation flow rate for stream 3 or 6	1700	
P*(oj)	0.95	
d(M,LT), Delay for stream 1 or 4	8.4	
N, Number of major street through lanes	1	
d(rank,1) Delay for stream 2 or 5	0.4	

HCS+: Unsignalized Intersections Release 5.6

Phone:
E-Mail:

Fax:

TWO-WAY STOP CONTROL(TWSC) ANALYSIS

Analyst: CMaddox
 Agency/Co.: SEI
 Date Performed: 3/3/2014
 Analysis Time Period: PM Peak
 Intersection: Riverside Pkwy & White Rd
 Jurisdiction: Cobb Co.
 Units: U. S. Customary
 Analysis Year: 2014
 Project ID:
 East/West Street: Riverside Pkwy
 North/South Street: White Rd
 Intersection Orientation: EW

Study period (hrs): 0.25

Vehicle Volumes and Adjustments

Major Street Movements	1 L	2 T	3 R	4 L	5 T	6 R
Volume	17	316			550	28
Peak-Hour Factor, PHF	0.92	0.92			0.92	0.92
Peak-15 Minute Volume	5	86			149	8
Hourly Flow Rate, HFR	18	343			597	30
Percent Heavy Vehicles	53	--	--		--	--
Median Type/Storage	Undivided			/		
RT Channelized?						
Lanes	0	1			1	0
Configuration	LT				TR	
Upstream Signal?		No			No	
Minor Street Movements	7 L	8 T	9 R	10 L	11 T	12 R

Volume				14		40
Peak Hour Factor, PHF				0.92		0.92
Peak-15 Minute Volume				4		11
Hourly Flow Rate, HFR				15		43
Percent Heavy Vehicles				72		13
Percent Grade (%)		0			0	
Flared Approach: Exists?/Storage				/		No /
RT Channelized?						
Lanes				0		0
Configuration					LR	

Pedestrian Volumes and Adjustments

Movements	13	14	15	16
Flow (ped/hr)	0	0	0	0

Lane Width (ft)	12.0	12.0	12.0	12.0
Walking Speed (ft/sec)	4.0	4.0	4.0	4.0
Percent Blockage	0	0	0	0

Upstream Signal Data							
	Prog. Flow vph	Sat Flow vph	Arrival Type	Green Time sec	Cycle Length sec	Prog. Speed mph	Distance to Signal feet
S2 Left-Turn Through							
S5 Left-Turn Through							

Worksheet 3-Data for Computing Effect of Delay to Major Street Vehicles

	Movement 2	Movement 5
Shared ln volume, major th vehicles:	343	
Shared ln volume, major rt vehicles:	0	
Sat flow rate, major th vehicles:	1700	
Sat flow rate, major rt vehicles:	1700	
Number of major street through lanes:	1	

Worksheet 4-Critical Gap and Follow-up Time Calculation

Critical Gap Calculation								
Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
t(c,base)	4.1					7.1		6.2
t(c,hv)	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
P(hv)	53					72		13
t(c,g)			0.20	0.20	0.10	0.20	0.20	0.10
Percent Grade			0.00	0.00	0.00	0.00	0.00	0.00
t(3,lt)	0.00					0.70		0.00
t(c,T): 1-stage	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
2-stage	0.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
t(c) 1-stage	4.6					7.1		6.3
2-stage								

Follow-Up Time Calculations								
Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
t(f,base)	2.20					3.50		3.30
t(f,HV)	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
P(HV)	53					72		13
t(f)	2.7					4.1		3.4

Worksheet 5-Effect of Upstream Signals

Computation 1-Queue Clearance Time at Upstream Signal				
	Movement 2		Movement 5	
	V(t)	V(l,prot)	V(t)	V(l,prot)
V prog				

Total Saturation Flow Rate, s (vph)
Arrival Type
Effective Green, g (sec)
Cycle Length, C (sec)
Rp (from Exhibit 16-11)
Proportion vehicles arriving on green P
g(q1)
g(q2)
g(q)

Computation 2-Proportion of TWSC Intersection Time blocked

	Movement 2		Movement 5	
	V(t)	V(l,prot)	V(t)	V(l,prot)

alpha
beta
Travel time, t(a) (sec)
Smoothing Factor, F
Proportion of conflicting flow, f
Max platooned flow, V(c,max)
Min platooned flow, V(c,min)
Duration of blocked period, t(p)
Proportion time blocked, p

	0.000	0.000
--	-------	-------

Computation 3-Platoon Event Periods Result

p(2)	0.000
p(5)	0.000
p(dom)	
p(subo)	
Constrained or unconstrained?	

Proportion unblocked for minor movements, p(x)	(1) Single-stage Process	(2) Two-Stage Process Stage I	(3) Process Stage II
--	-----------------------------	-------------------------------------	----------------------------

p(1)
p(4)
p(7)
p(8)
p(9)
p(10)
p(11)
p(12)

Computation 4 and 5
Single-Stage Process

Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
V c, x	627					991		612
s								
Px								
V c, u, x								
C r, x								
C plat, x								

Two-Stage Process

7	8	10	11
---	---	----	----

Stage1	Stage2	Stage1	Stage2	Stage1	Stage2	Stage1	Stage2
--------	--------	--------	--------	--------	--------	--------	--------

V(c,x)							
s					1500		
P(x)							
V(c,u,x)							

C(r,x)
C(plat,x)

Worksheet 6-Impedance and Capacity Equations

Step 1: RT from Minor St.	9	12
---------------------------	---	----

Conflicting Flows		612
Potential Capacity		474
Pedestrian Impedance Factor	1.00	1.00
Movement Capacity		474
Probability of Queue free St.	1.00	0.91

Step 2: LT from Major St.	4	1
---------------------------	---	---

Conflicting Flows		627
Potential Capacity		751
Pedestrian Impedance Factor	1.00	1.00
Movement Capacity		751
Probability of Queue free St.	1.00	0.98
Maj L-Shared Prob Q free St.		0.97

Step 3: TH from Minor St.	8	11
---------------------------	---	----

Conflicting Flows		
Potential Capacity		
Pedestrian Impedance Factor	1.00	1.00
Cap. Adj. factor due to Impeding mvmnt	0.97	0.97
Movement Capacity		
Probability of Queue free St.	1.00	1.00

Step 4: LT from Minor St.	7	10
---------------------------	---	----

Conflicting Flows		991
Potential Capacity		205
Pedestrian Impedance Factor	1.00	1.00
Maj. L, Min T Impedance factor	0.97	
Maj. L, Min T Adj. Imp Factor.	0.98	
Cap. Adj. factor due to Impeding mvmnt	0.89	0.98
Movement Capacity		200

Worksheet 7-Computation of the Effect of Two-stage Gap Acceptance

Step 3: TH from Minor St.	8	11
---------------------------	---	----

Part 1 - First Stage
Conflicting Flows
Potential Capacity
Pedestrian Impedance Factor
Cap. Adj. factor due to Impeding mvmnt
Movement Capacity
Probability of Queue free St.

Part 2 - Second Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor
 Cap. Adj. factor due to Impeding mvmnt
 Movement Capacity

Part 3 - Single Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor 1.00 1.00
 Cap. Adj. factor due to Impeding mvmnt 0.97 0.97
 Movement Capacity

Result for 2 stage process:
 a
 y
 C t
 Probability of Queue free St. 1.00 1.00

Step 4: LT from Minor St. 7 10

Part 1 - First Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor
 Cap. Adj. factor due to Impeding mvmnt
 Movement Capacity

Part 2 - Second Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor
 Cap. Adj. factor due to Impeding mvmnt
 Movement Capacity

Part 3 - Single Stage
 Conflicting Flows 991
 Potential Capacity 205
 Pedestrian Impedance Factor 1.00 1.00
 Maj. L, Min T Impedance factor 0.97
 Maj. L, Min T Adj. Imp Factor. 0.98
 Cap. Adj. factor due to Impeding mvmnt 0.89 0.98
 Movement Capacity 200

Results for Two-stage process:
 a
 y
 C t 200

Worksheet 8-Shared Lane Calculations

Movement	7	8	9	10	11	12
	L	T	R	L	T	R
Volume (vph)				15		43
Movement Capacity (vph)				200		474
Shared Lane Capacity (vph)					350	

Worksheet 9-Computation of Effect of Flared Minor Street Approaches

Movement	7 L	8 T	9 R	10 L	11 T	12 R
C sep				200		474
Volume				15		43
Delay						
Q sep						
Q sep +1						
round (Qsep +1)						
n max						
C sh					350	
SUM C sep						
n						
C act						

Worksheet 10-Delay, Queue Length, and Level of Service

Movement	1	4	7	8	9	10	11	12
Lane Config	LT						LR	
v (vph)	18						58	
C(m) (vph)	751						350	
v/c	0.02						0.17	
95% queue length	0.07						0.59	
Control Delay	9.9						17.3	
LOS	A						C	
Approach Delay							17.3	
Approach LOS							C	

Worksheet 11-Shared Major LT Impedance and Delay

	Movement 2	Movement 5
p(oj)	0.98	1.00
v(il), Volume for stream 2 or 5	343	
v(i2), Volume for stream 3 or 6	0	
s(il), Saturation flow rate for stream 2 or 5	1700	
s(i2), Saturation flow rate for stream 3 or 6	1700	
P*(oj)	0.97	
d(M,LT), Delay for stream 1 or 4	9.9	
N, Number of major street through lanes	1	
d(rank,1) Delay for stream 2 or 5	0.3	

Appendix E: Year-2016 Background ICAS without the Development

TWO-WAY STOP CONTROL SUMMARY

Analyst: CMaddox
 Agency/Co.: SEI
 Date Performed: 3/3/2014
 Analysis Time Period: AM Peak
 Intersection: Factory Shoals Rd & White Rd
 Jurisdiction: Cobb Co.
 Units: U. S. Customary
 Analysis Year: 2016 Background
 Project ID:
 East/West Street: Factory Shoals Rd
 North/South Street: White Rd
 Intersection Orientation: EW

Study period (hrs): 0.25

Vehicle Volumes and Adjustments

Major Street:	Approach Movement	Eastbound				Westbound		
		1 L	2 T	3 R		4 L	5 T	6 R
Volume			383	9		16	201	
Peak-Hour Factor, PHF			0.92	0.92		0.92	0.92	
Hourly Flow Rate, HFR			416	9		17	218	
Percent Heavy Vehicles			--	--		2	--	--
Median Type/Storage		Undivided			/			
RT Channelized?								
Lanes			1	0		0	1	
Configuration			TR			LT		
Upstream Signal?			No			No		
Minor Street:	Approach Movement	Northbound				Southbound		
		7 L	8 T	9 R		10 L	11 T	12 R
Volume		4		8				
Peak Hour Factor, PHF		0.92		0.92				
Hourly Flow Rate, HFR		4		8				
Percent Heavy Vehicles		25		75				
Percent Grade (%)			0				0	
Flared Approach: Exists?/Storage		No			/			
Lanes		0		0				
Configuration			LR					

Delay, Queue Length, and Level of Service

Approach	EB	WB	Northbound			Southbound		
Movement	1	4	7	8	9	10	11	12
Lane Config		LT		LR				
v (vph)		17		12				
C(m) (vph)		1134		455				
v/c		0.01		0.03				
95% queue length		0.05		0.08				
Control Delay		8.2		13.1				
LOS		A		B				
Approach Delay				13.1				
Approach LOS				B				

HCS+: Unsignalized Intersections Release 5.6

Phone:
E-Mail:

Fax:

TWO-WAY STOP CONTROL(TWSC) ANALYSIS

Analyst: CMaddox
 Agency/Co.: SEI
 Date Performed: 3/3/2014
 Analysis Time Period: AM Peak
 Intersection: Factory Shoals Rd & White Rd
 Jurisdiction: Cobb Co.
 Units: U. S. Customary
 Analysis Year: 2016 Background
 Project ID:
 East/West Street: Factory Shoals Rd
 North/South Street: White Rd
 Intersection Orientation: EW

Study period (hrs): 0.25

Vehicle Volumes and Adjustments

Major Street Movements	1 L	2 T	3 R	4 L	5 T	6 R
Volume		383	9	16	201	
Peak-Hour Factor, PHF		0.92	0.92	0.92	0.92	
Peak-15 Minute Volume		104	2	4	55	
Hourly Flow Rate, HFR		416	9	17	218	
Percent Heavy Vehicles		--	--	2	--	--
Median Type/Storage	Undivided			/		
RT Channelized?						
Lanes		1	0	0	1	
Configuration			TR		LT	
Upstream Signal?		No			No	
Minor Street Movements	7 L	8 T	9 R	10 L	11 T	12 R

Volume	4		8			
Peak Hour Factor, PHF	0.92		0.92			
Peak-15 Minute Volume	1		2			
Hourly Flow Rate, HFR	4		8			
Percent Heavy Vehicles	25		75			
Percent Grade (%)		0			0	
Flared Approach: Exists?/Storage			No	/		/
RT Channelized?						
Lanes	0		0			
Configuration		LR				

Pedestrian Volumes and Adjustments

Movements	13	14	15	16
Flow (ped/hr)	0	0	0	0

Lane Width (ft)	12.0	12.0	12.0	12.0
Walking Speed (ft/sec)	4.0	4.0	4.0	4.0
Percent Blockage	0	0	0	0

Upstream Signal Data							
	Prog. Flow vph	Sat Flow vph	Arrival Type	Green Time sec	Cycle Length sec	Prog. Speed mph	Distance to Signal feet
S2 Left-Turn Through							
S5 Left-Turn Through							

Worksheet 3-Data for Computing Effect of Delay to Major Street Vehicles

	Movement 2	Movement 5
Shared ln volume, major th vehicles:		218
Shared ln volume, major rt vehicles:		0
Sat flow rate, major th vehicles:		1700
Sat flow rate, major rt vehicles:		1700
Number of major street through lanes:		1

Worksheet 4-Critical Gap and Follow-up Time Calculation

Critical Gap Calculation								
Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
t(c,base)		4.1	7.1		6.2			
t(c,hv)	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
P(hv)		2	25		75			
t(c,g)			0.20	0.20	0.10	0.20	0.20	0.10
Percent Grade			0.00	0.00	0.00	0.00	0.00	0.00
t(3,lt)		0.00	0.70		0.00			
t(c,T): 1-stage	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
2-stage	0.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
t(c) 1-stage		4.1	6.7		6.9			
2-stage								

Follow-Up Time Calculations								
Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
t(f,base)		2.20	3.50		3.30			
t(f,HV)	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
P(HV)		2	25		75			
t(f)		2.2	3.7		4.0			

Worksheet 5-Effect of Upstream Signals

Computation 1-Queue Clearance Time at Upstream Signal				
	Movement 2		Movement 5	
	V(t)	V(l,prot)	V(t)	V(l,prot)
V prog				

Total Saturation Flow Rate, s (vph)
Arrival Type
Effective Green, g (sec)
Cycle Length, C (sec)
Rp (from Exhibit 16-11)
Proportion vehicles arriving on green P
g(q1)
g(q2)
g(q)

Computation 2-Proportion of TWSC Intersection Time blocked

	Movement 2		Movement 5	
	V(t)	V(l,prot)	V(t)	V(l,prot)

alpha
beta
Travel time, t(a) (sec)
Smoothing Factor, F
Proportion of conflicting flow, f
Max platooned flow, V(c,max)
Min platooned flow, V(c,min)
Duration of blocked period, t(p)
Proportion time blocked, p

	0.000	0.000
--	-------	-------

Computation 3-Platoon Event Periods Result

p(2)	0.000
p(5)	0.000
p(dom)	
p(subo)	
Constrained or unconstrained?	

Proportion unblocked for minor movements, p(x)	(1) Single-stage Process	(2) Two-Stage Process Stage I	(3) Process Stage II
--	-----------------------------	-------------------------------------	----------------------------

p(1)
p(4)
p(7)
p(8)
p(9)
p(10)
p(11)
p(12)

Computation 4 and 5
Single-Stage Process
Movement

	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
--	--------	--------	--------	--------	--------	---------	---------	---------

V c, x		425	672		420			
s								
Px								
V c, u, x								

C r, x
C plat, x

Two-Stage Process	7	8	10	11
-------------------	---	---	----	----

	Stage1	Stage2	Stage1	Stage2	Stage1	Stage2	Stage1	Stage2
--	--------	--------	--------	--------	--------	--------	--------	--------

V(c,x)								
s		1500						
P(x)								
V(c,u,x)								

C(r,x)								
C(plat,x)								

Worksheet 6-Impedance and Capacity Equations

Step 1: RT from Minor St.	9	12
---------------------------	---	----

Conflicting Flows	420	
Potential Capacity	503	
Pedestrian Impedance Factor	1.00	1.00
Movement Capacity	503	
Probability of Queue free St.	0.98	1.00

Step 2: LT from Major St.	4	1
---------------------------	---	---

Conflicting Flows	425	
Potential Capacity	1134	
Pedestrian Impedance Factor	1.00	1.00
Movement Capacity	1134	
Probability of Queue free St.	0.99	1.00
Maj L-Shared Prob Q free St.	0.98	

Step 3: TH from Minor St.	8	11
---------------------------	---	----

Conflicting Flows		
Potential Capacity		
Pedestrian Impedance Factor	1.00	1.00
Cap. Adj. factor due to Impeding mvmnt	0.98	0.98
Movement Capacity		
Probability of Queue free St.	1.00	1.00

Step 4: LT from Minor St.	7	10
---------------------------	---	----

Conflicting Flows	672	
Potential Capacity	388	
Pedestrian Impedance Factor	1.00	1.00
Maj. L, Min T Impedance factor		0.98
Maj. L, Min T Adj. Imp Factor.		0.99
Cap. Adj. factor due to Impeding mvmnt	0.99	0.97
Movement Capacity	382	

Worksheet 7-Computation of the Effect of Two-stage Gap Acceptance

Step 3: TH from Minor St.	8	11
---------------------------	---	----

Part 1 - First Stage	
Conflicting Flows	
Potential Capacity	
Pedestrian Impedance Factor	
Cap. Adj. factor due to Impeding mvmnt	
Movement Capacity	
Probability of Queue free St.	

Part 2 - Second Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor
 Cap. Adj. factor due to Impeding mvmnt
 Movement Capacity

Part 3 - Single Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor 1.00 1.00
 Cap. Adj. factor due to Impeding mvmnt 0.98 0.98
 Movement Capacity

Result for 2 stage process:
 a
 y
 C t
 Probability of Queue free St. 1.00 1.00

Step 4: LT from Minor St. 7 10

Part 1 - First Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor
 Cap. Adj. factor due to Impeding mvmnt
 Movement Capacity

Part 2 - Second Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor
 Cap. Adj. factor due to Impeding mvmnt
 Movement Capacity

Part 3 - Single Stage
 Conflicting Flows 672
 Potential Capacity 388
 Pedestrian Impedance Factor 1.00 1.00
 Maj. L, Min T Impedance factor 0.98
 Maj. L, Min T Adj. Imp Factor. 0.99
 Cap. Adj. factor due to Impeding mvmnt 0.99 0.97
 Movement Capacity 382

Results for Two-stage process:
 a
 y
 C t 382

Worksheet 8-Shared Lane Calculations

Movement	7 L	8 T	9 R	10 L	11 T	12 R
Volume (vph)	4		8			
Movement Capacity (vph)	382		503			
Shared Lane Capacity (vph)		455				

Worksheet 9-Computation of Effect of Flared Minor Street Approaches

Movement	7 L	8 T	9 R	10 L	11 T	12 R
C sep	382		503			
Volume	4		8			
Delay						
Q sep						
Q sep +1 round (Qsep +1)						
n max						
C sh		455				
SUM C sep						
n						
C act						

Worksheet 10-Delay, Queue Length, and Level of Service

Movement	1	4	7	8	9	10	11	12
Lane Config		LT		LR				
v (vph)		17		12				
C(m) (vph)		1134		455				
v/c		0.01		0.03				
95% queue length		0.05		0.08				
Control Delay		8.2		13.1				
LOS		A		B				
Approach Delay				13.1				
Approach LOS				B				

Worksheet 11-Shared Major LT Impedance and Delay

	Movement 2	Movement 5
p(oj)	1.00	0.99
v(il), Volume for stream 2 or 5		218
v(i2), Volume for stream 3 or 6		0
s(il), Saturation flow rate for stream 2 or 5		1700
s(i2), Saturation flow rate for stream 3 or 6		1700
P*(oj)		0.98
d(M,LT), Delay for stream 1 or 4		8.2
N, Number of major street through lanes		1
d(rank,1) Delay for stream 2 or 5		0.1

TWO-WAY STOP CONTROL SUMMARY

Analyst: CMaddox
 Agency/Co.: SEI
 Date Performed: 3/3/2014
 Analysis Time Period: PM Peak
 Intersection: Factory Shoals Rd & White Rd
 Jurisdiction: Cobb Co.
 Units: U. S. Customary
 Analysis Year: 2016 Background
 Project ID:
 East/West Street: Factory Shoals Rd
 North/South Street: White Rd
 Intersection Orientation: EW

Study period (hrs): 0.25

Vehicle Volumes and Adjustments

Major Street:	Approach Movement	Eastbound				Westbound		
		1 L	2 T	3 R		4 L	5 T	6 R
Volume			237	10		33	292	
Peak-Hour Factor, PHF			0.92	0.92		0.92	0.92	
Hourly Flow Rate, HFR			257	10		35	317	
Percent Heavy Vehicles			--	--		2	--	--
Median Type/Storage		Undivided			/			
RT Channelized?								
Lanes			1	0		0	1	
Configuration			TR			LT		
Upstream Signal?			No				No	
Minor Street:	Approach Movement	Northbound				Southbound		
		7 L	8 T	9 R		10 L	11 T	12 R
Volume		15		12				
Peak Hour Factor, PHF		0.92		0.92				
Hourly Flow Rate, HFR		16		13				
Percent Heavy Vehicles		14		2				
Percent Grade (%)			0				0	
Flared Approach: Exists?/Storage					/			
Lanes		0		0				
Configuration			LR					

Delay, Queue Length, and Level of Service

Approach	EB	WB	Northbound			Southbound		
Movement	1	4	7	8	9	10	11	12
Lane Config		LT		LR				
v (vph)		35		29				
C(m) (vph)		1297		516				
v/c		0.03		0.06				
95% queue length		0.08		0.18				
Control Delay		7.9		12.4				
LOS		A		B				
Approach Delay				12.4				
Approach LOS				B				

HCS+: Unsignalized Intersections Release 5.6

Phone:
E-Mail:

Fax:

TWO-WAY STOP CONTROL(TWSC) ANALYSIS

Analyst: CMaddox
 Agency/Co.: SEI
 Date Performed: 3/3/2014
 Analysis Time Period: PM Peak
 Intersection: Factory Shoals Rd & White Rd
 Jurisdiction: Cobb Co.
 Units: U. S. Customary
 Analysis Year: 2016 Background
 Project ID:
 East/West Street: Factory Shoals Rd
 North/South Street: White Rd
 Intersection Orientation: EW

Study period (hrs): 0.25

Vehicle Volumes and Adjustments

Major Street Movements	1 L	2 T	3 R	4 L	5 T	6 R
Volume		237	10	33	292	
Peak-Hour Factor, PHF		0.92	0.92	0.92	0.92	
Peak-15 Minute Volume		64	3	9	79	
Hourly Flow Rate, HFR		257	10	35	317	
Percent Heavy Vehicles		--	--	2	--	--
Median Type/Storage	Undivided			/		
RT Channelized?						
Lanes		1	0	0	1	
Configuration			TR		LT	
Upstream Signal?		No			No	
Minor Street Movements	7 L	8 T	9 R	10 L	11 T	12 R

Volume	15		12			
Peak Hour Factor, PHF	0.92		0.92			
Peak-15 Minute Volume	4		3			
Hourly Flow Rate, HFR	16		13			
Percent Heavy Vehicles	14		2			
Percent Grade (%)		0			0	
Flared Approach: Exists?/Storage			No	/		/
RT Channelized?						
Lanes	0		0			
Configuration		LR				

Pedestrian Volumes and Adjustments

Movements	13	14	15	16
Flow (ped/hr)	0	0	0	0

Lane Width (ft)	12.0	12.0	12.0	12.0
Walking Speed (ft/sec)	4.0	4.0	4.0	4.0
Percent Blockage	0	0	0	0

Upstream Signal Data							
	Prog. Flow vph	Sat Flow vph	Arrival Type	Green Time sec	Cycle Length sec	Prog. Speed mph	Distance to Signal feet
S2 Left-Turn Through							
S5 Left-Turn Through							

Worksheet 3-Data for Computing Effect of Delay to Major Street Vehicles

	Movement 2	Movement 5
Shared ln volume, major th vehicles:		317
Shared ln volume, major rt vehicles:		0
Sat flow rate, major th vehicles:		1700
Sat flow rate, major rt vehicles:		1700
Number of major street through lanes:		1

Worksheet 4-Critical Gap and Follow-up Time Calculation

Critical Gap Calculation								
Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
t(c,base)		4.1	7.1		6.2			
t(c,hv)	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
P(hv)		2	14		2			
t(c,g)			0.20	0.20	0.10	0.20	0.20	0.10
Percent Grade			0.00	0.00	0.00	0.00	0.00	0.00
t(3,lt)		0.00	0.70		0.00			
t(c,T): 1-stage	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
2-stage	0.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
t(c) 1-stage		4.1	6.5		6.2			
2-stage								

Follow-Up Time Calculations								
Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
t(f,base)		2.20	3.50		3.30			
t(f,HV)	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
P(HV)		2	14		2			
t(f)		2.2	3.6		3.3			

Worksheet 5-Effect of Upstream Signals

Computation 1-Queue Clearance Time at Upstream Signal				
	Movement 2		Movement 5	
	V(t)	V(l,prot)	V(t)	V(l,prot)
V prog				

Total Saturation Flow Rate, s (vph)
Arrival Type
Effective Green, g (sec)
Cycle Length, C (sec)
Rp (from Exhibit 16-11)
Proportion vehicles arriving on green P
g(q1)
g(q2)
g(q)

Computation 2-Proportion of TWSC Intersection Time blocked

	Movement 2		Movement 5	
	V(t)	V(l,prot)	V(t)	V(l,prot)

alpha
beta
Travel time, t(a) (sec)
Smoothing Factor, F
Proportion of conflicting flow, f
Max platooned flow, V(c,max)
Min platooned flow, V(c,min)
Duration of blocked period, t(p)
Proportion time blocked, p

	0.000	0.000
--	-------	-------

Computation 3-Platoon Event Periods Result

p(2)	0.000
p(5)	0.000
p(dom)	
p(subo)	
Constrained or unconstrained?	

Proportion unblocked for minor movements, p(x)	(1) Single-stage Process	(2) Two-Stage Stage I	(3) Process Stage II
--	-----------------------------	--------------------------	-------------------------

p(1)
p(4)
p(7)
p(8)
p(9)
p(10)
p(11)
p(12)

Computation 4 and 5
Single-Stage Process
Movement

	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
--	--------	--------	--------	--------	--------	---------	---------	---------

V c, x		267	649		262			
s								
Px								
V c, u, x								

C r, x
C plat, x

Two-Stage Process	7	8	10	11
-------------------	---	---	----	----

	Stage1	Stage2	Stage1	Stage2	Stage1	Stage2	Stage1	Stage2
--	--------	--------	--------	--------	--------	--------	--------	--------

V(c,x)								
s		1500						
P(x)								
V(c,u,x)								

C(r,x)								
C(plat,x)								

Worksheet 6-Impedance and Capacity Equations

Step 1: RT from Minor St.	9	12
---------------------------	---	----

Conflicting Flows	262	
Potential Capacity	777	
Pedestrian Impedance Factor	1.00	1.00
Movement Capacity	777	
Probability of Queue free St.	0.98	1.00

Step 2: LT from Major St.	4	1
---------------------------	---	---

Conflicting Flows	267	
Potential Capacity	1297	
Pedestrian Impedance Factor	1.00	1.00
Movement Capacity	1297	
Probability of Queue free St.	0.97	1.00
Maj L-Shared Prob Q free St.	0.97	

Step 3: TH from Minor St.	8	11
---------------------------	---	----

Conflicting Flows		
Potential Capacity		
Pedestrian Impedance Factor	1.00	1.00
Cap. Adj. factor due to Impeding mvmnt	0.97	0.97
Movement Capacity		
Probability of Queue free St.	1.00	1.00

Step 4: LT from Minor St.	7	10
---------------------------	---	----

Conflicting Flows	649	
Potential Capacity	416	
Pedestrian Impedance Factor	1.00	1.00
Maj. L, Min T Impedance factor		0.97
Maj. L, Min T Adj. Imp Factor.		0.97
Cap. Adj. factor due to Impeding mvmnt	0.97	0.96
Movement Capacity	405	

Worksheet 7-Computation of the Effect of Two-stage Gap Acceptance

Step 3: TH from Minor St.	8	11
---------------------------	---	----

Part 1 - First Stage		
Conflicting Flows		
Potential Capacity		
Pedestrian Impedance Factor		
Cap. Adj. factor due to Impeding mvmnt		
Movement Capacity		
Probability of Queue free St.		

Part 2 - Second Stage
Conflicting Flows
Potential Capacity
Pedestrian Impedance Factor
Cap. Adj. factor due to Impeding mvmnt
Movement Capacity

Part 3 - Single Stage		
Conflicting Flows		
Potential Capacity		
Pedestrian Impedance Factor	1.00	1.00
Cap. Adj. factor due to Impeding mvmnt	0.97	0.97
Movement Capacity		

Result for 2 stage process:		
a		
y		
C t		
Probability of Queue free St.	1.00	1.00

Step 4: LT from Minor St.	7	10
---------------------------	---	----

Part 1 - First Stage
Conflicting Flows
Potential Capacity
Pedestrian Impedance Factor
Cap. Adj. factor due to Impeding mvmnt
Movement Capacity

Part 2 - Second Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor
 Cap. Adj. factor due to Impeding mvmnt
 Movement Capacity

Part 3 - Single Stage		
Conflicting Flows	649	
Potential Capacity	416	
Pedestrian Impedance Factor	1.00	1.00
Maj. L, Min T Impedance factor		0.97
Maj. L, Min T Adj. Imp Factor.		0.97
Cap. Adj. factor due to Impeding mvmnt	0.97	0.96
Movement Capacity	405	

```
Results for Two-stage process:
a
y
C t                                405
```

Worksheet 8-Shared Lane Calculations

Movement	7 L	8 T	9 R	10 L	11 T	12 R
Volume (vph)	16		13			
Movement Capacity (vph)	405		777			
Shared Lane Capacity (vph)		516				

Worksheet 9-Computation of Effect of Flared Minor Street Approaches

Movement	7 L	8 T	9 R	10 L	11 T	12 R
C sep	405		777			
Volume	16		13			
Delay						
Q sep						
Q sep +1						
round (Qsep +1)						
n max						
C sh		516				
SUM C sep						
n						
C act						

Worksheet 10-Delay, Queue Length, and Level of Service

Movement	1	4	7	8	9	10	11	12
Lane Config		LT		LR				
v (vph)		35		29				
C(m) (vph)		1297		516				
v/c		0.03		0.06				
95% queue length		0.08		0.18				
Control Delay		7.9		12.4				
LOS		A		B				
Approach Delay				12.4				
Approach LOS				B				

Worksheet 11-Shared Major LT Impedance and Delay

	Movement 2	Movement 5
p(oj)	1.00	0.97
v(il), Volume for stream 2 or 5		317
v(i2), Volume for stream 3 or 6		0
s(il), Saturation flow rate for stream 2 or 5		1700
s(i2), Saturation flow rate for stream 3 or 6		1700
P*(oj)		0.97
d(M,LT), Delay for stream 1 or 4		7.9
N, Number of major street through lanes		1
d(rank,1) Delay for stream 2 or 5		0.3

HCS+: Unsignalized Intersections Release 5.6

Phone:
E-Mail:

Fax:

TWO-WAY STOP CONTROL(TWSC) ANALYSIS

Analyst: CMaddox
 Agency/Co.: SEI
 Date Performed: 3/3/2014
 Analysis Time Period: AM Peak
 Intersection: Riverside Pkwy & White Rd
 Jurisdiction: Cobb Co.
 Units: U. S. Customary
 Analysis Year: 2016 Background
 Project ID:
 East/West Street: Riverside Pkwy
 North/South Street: White Rd
 Intersection Orientation: EW

Study period (hrs): 0.25

Vehicle Volumes and Adjustments

Major Street Movements	1 L	2 T	3 R	4 L	5 T	6 R
Volume	27	734			294	11
Peak-Hour Factor, PHF	0.92	0.92			0.92	0.92
Peak-15 Minute Volume	7	199			80	3
Hourly Flow Rate, HFR	29	797			319	11
Percent Heavy Vehicles	31	--	--		--	--
Median Type/Storage	Undivided			/		
RT Channelized?						
Lanes	0	1			1	0
Configuration	LT				TR	
Upstream Signal?		No			No	
Minor Street Movements	7 L	8 T	9 R	10 L	11 T	12 R

Volume				12		34
Peak Hour Factor, PHF				0.92		0.92
Peak-15 Minute Volume				3		9
Hourly Flow Rate, HFR				13		36
Percent Heavy Vehicles				75		40
Percent Grade (%)		0			0	
Flared Approach: Exists?/Storage				/		No /
RT Channelized?						
Lanes				0		0
Configuration					LR	

Pedestrian Volumes and Adjustments

Movements	13	14	15	16
Flow (ped/hr)	0	0	0	0

Lane Width (ft)	12.0	12.0	12.0	12.0
Walking Speed (ft/sec)	4.0	4.0	4.0	4.0
Percent Blockage	0	0	0	0

Upstream Signal Data							
	Prog. Flow vph	Sat Flow vph	Arrival Type	Green Time sec	Cycle Length sec	Prog. Speed mph	Distance to Signal feet
S2 Left-Turn Through							
S5 Left-Turn Through							

Worksheet 3-Data for Computing Effect of Delay to Major Street Vehicles

	Movement 2	Movement 5
Shared ln volume, major th vehicles:	797	
Shared ln volume, major rt vehicles:	0	
Sat flow rate, major th vehicles:	1700	
Sat flow rate, major rt vehicles:	1700	
Number of major street through lanes:	1	

Worksheet 4-Critical Gap and Follow-up Time Calculation

Critical Gap Calculation								
Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
t(c,base)	4.1					7.1		6.2
t(c,hv)	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
P(hv)	31					75		40
t(c,g)			0.20	0.20	0.10	0.20	0.20	0.10
Percent Grade			0.00	0.00	0.00	0.00	0.00	0.00
t(3,lt)	0.00					0.70		0.00
t(c,T): 1-stage	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
2-stage	0.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
t(c) 1-stage	4.4					7.2		6.6
2-stage								

Follow-Up Time Calculations								
Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
t(f,base)	2.20					3.50		3.30
t(f,HV)	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
P(HV)	31					75		40
t(f)	2.5					4.2		3.7

Worksheet 5-Effect of Upstream Signals

Computation 1-Queue Clearance Time at Upstream Signal				
	Movement 2		Movement 5	
	V(t)	V(l,prot)	V(t)	V(l,prot)
V prog				

Total Saturation Flow Rate, s (vph)
Arrival Type
Effective Green, g (sec)
Cycle Length, C (sec)
Rp (from Exhibit 16-11)
Proportion vehicles arriving on green P
g(q1)
g(q2)
g(q)

Computation 2-Proportion of TWSC Intersection Time blocked

	Movement 2		Movement 5	
	V(t)	V(l,prot)	V(t)	V(l,prot)

alpha
beta
Travel time, t(a) (sec)
Smoothing Factor, F
Proportion of conflicting flow, f
Max platooned flow, V(c,max)
Min platooned flow, V(c,min)
Duration of blocked period, t(p)
Proportion time blocked, p

	0.000	0.000
--	-------	-------

Computation 3-Platoon Event Periods

	Result
--	--------

p(2)	0.000
p(5)	0.000
p(dom)	
p(subo)	
Constrained or unconstrained?	

Proportion unblocked for minor movements, p(x)	(1) Single-stage Process	(2) Two-Stage Process Stage I	(3) Process Stage II
--	-----------------------------	-------------------------------------	----------------------------

p(1)
p(4)
p(7)
p(8)
p(9)
p(10)
p(11)
p(12)

Computation 4 and 5
Single-Stage Process
Movement

	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
V c, x	330					1179		324
s								
Px								
V c, u, x								
C r, x								
C plat, x								

Two-Stage Process

7	8	10	11
---	---	----	----

V(c,x)
s
P(x)
V(c,u,x)

1500

C(r,x)
C(plat,x)

Worksheet 6-Impedance and Capacity Equations

Step 1: RT from Minor St. 9 12

Conflicting Flows 324
Potential Capacity 637
Pedestrian Impedance Factor 1.00 1.00
Movement Capacity 637
Probability of Queue free St. 1.00 0.94

Step 2: LT from Major St. 4 1

Conflicting Flows 330
Potential Capacity 1084
Pedestrian Impedance Factor 1.00 1.00
Movement Capacity 1084
Probability of Queue free St. 1.00 0.97
Maj L-Shared Prob Q free St. 0.95

Step 3: TH from Minor St. 8 11

Conflicting Flows
Potential Capacity
Pedestrian Impedance Factor 1.00 1.00
Cap. Adj. factor due to Impeding mvmnt 0.95 0.95
Movement Capacity
Probability of Queue free St. 1.00 1.00

Step 4: LT from Minor St. 7 10

Conflicting Flows 1179
Potential Capacity 152
Pedestrian Impedance Factor 1.00 1.00
Maj. L, Min T Impedance factor 0.95
Maj. L, Min T Adj. Imp Factor. 0.96
Cap. Adj. factor due to Impeding mvmnt 0.91 0.97
Movement Capacity 148

Worksheet 7-Computation of the Effect of Two-stage Gap Acceptance

Step 3: TH from Minor St. 8 11

Part 1 - First Stage
Conflicting Flows
Potential Capacity
Pedestrian Impedance Factor
Cap. Adj. factor due to Impeding mvmnt
Movement Capacity
Probability of Queue free St.

Part 2 - Second Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor
 Cap. Adj. factor due to Impeding mvmnt
 Movement Capacity

Part 3 - Single Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor 1.00 1.00
 Cap. Adj. factor due to Impeding mvmnt 0.95 0.95
 Movement Capacity

Result for 2 stage process:
 a
 y
 C t
 Probability of Queue free St. 1.00 1.00

Step 4: LT from Minor St. 7 10

Part 1 - First Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor
 Cap. Adj. factor due to Impeding mvmnt
 Movement Capacity

Part 2 - Second Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor
 Cap. Adj. factor due to Impeding mvmnt
 Movement Capacity

Part 3 - Single Stage
 Conflicting Flows 1179
 Potential Capacity 152
 Pedestrian Impedance Factor 1.00 1.00
 Maj. L, Min T Impedance factor 0.95
 Maj. L, Min T Adj. Imp Factor. 0.96
 Cap. Adj. factor due to Impeding mvmnt 0.91 0.97
 Movement Capacity 148

Results for Two-stage process:
 a
 y
 C t 148

Worksheet 8-Shared Lane Calculations

Movement	7	8	9	10	11	12
	L	T	R	L	T	R
Volume (vph)				13		36
Movement Capacity (vph)				148		637
Shared Lane Capacity (vph)					339	

Worksheet 9-Computation of Effect of Flared Minor Street Approaches

Movement	7 L	8 T	9 R	10 L	11 T	12 R
C sep				148		637
Volume				13		36
Delay						
Q sep						
Q sep +1						
round (Qsep +1)						
n max						
C sh					339	
SUM C sep						
n						
C act						

Worksheet 10-Delay, Queue Length, and Level of Service

Movement	1	4	7	8	9	10	11	12
Lane Config	LT						LR	
v (vph)	29						49	
C(m) (vph)	1084						339	
v/c	0.03						0.14	
95% queue length	0.08						0.50	
Control Delay	8.4						17.4	
LOS	A						C	
Approach Delay							17.4	
Approach LOS							C	

Worksheet 11-Shared Major LT Impedance and Delay

	Movement 2	Movement 5
p(oj)	0.97	1.00
v(il), Volume for stream 2 or 5	797	
v(i2), Volume for stream 3 or 6	0	
s(il), Saturation flow rate for stream 2 or 5	1700	
s(i2), Saturation flow rate for stream 3 or 6	1700	
P*(oj)	0.95	
d(M,LT), Delay for stream 1 or 4	8.4	
N, Number of major street through lanes	1	
d(rank,1) Delay for stream 2 or 5	0.4	

HCS+: Unsignalized Intersections Release 5.6

Phone:
E-Mail:

Fax:

TWO-WAY STOP CONTROL(TWSC) ANALYSIS

Analyst: CMaddox
 Agency/Co.: SEI
 Date Performed: 3/3/2014
 Analysis Time Period: PM Peak
 Intersection: Riverside Pkwy & White Rd
 Jurisdiction: Cobb Co.
 Units: U. S. Customary
 Analysis Year: 2016 Background
 Project ID:
 East/West Street: Riverside Pkwy
 North/South Street: White Rd
 Intersection Orientation: EW

Study period (hrs): 0.25

Vehicle Volumes and Adjustments

Major Street Movements	1 L	2 T	3 R	4 L	5 T	6 R
Volume	31	322			561	51
Peak-Hour Factor, PHF	0.92	0.92			0.92	0.92
Peak-15 Minute Volume	8	88			152	14
Hourly Flow Rate, HFR	33	349			609	55
Percent Heavy Vehicles	53	--	--		--	--
Median Type/Storage	Undivided			/		
RT Channelized?						
Lanes	0	1			1	0
Configuration	LT				TR	
Upstream Signal?		No			No	
Minor Street Movements	7 L	8 T	9 R	10 L	11 T	12 R

Volume				54		154
Peak Hour Factor, PHF				0.92		0.92
Peak-15 Minute Volume				15		42
Hourly Flow Rate, HFR				58		167
Percent Heavy Vehicles				72		13
Percent Grade (%)		0			0	
Flared Approach: Exists?/Storage				/		No /
RT Channelized?						
Lanes				0		0
Configuration					LR	

Pedestrian Volumes and Adjustments

Movements	13	14	15	16
Flow (ped/hr)	0	0	0	0

Lane Width (ft)	12.0	12.0	12.0	12.0
Walking Speed (ft/sec)	4.0	4.0	4.0	4.0
Percent Blockage	0	0	0	0

Upstream Signal Data							
	Prog. Flow vph	Sat Flow vph	Arrival Type	Green Time sec	Cycle Length sec	Prog. Speed mph	Distance to Signal feet
S2 Left-Turn Through							
S5 Left-Turn Through							

Worksheet 3-Data for Computing Effect of Delay to Major Street Vehicles

	Movement 2	Movement 5
Shared ln volume, major th vehicles:	349	
Shared ln volume, major rt vehicles:	0	
Sat flow rate, major th vehicles:	1700	
Sat flow rate, major rt vehicles:	1700	
Number of major street through lanes:	1	

Worksheet 4-Critical Gap and Follow-up Time Calculation

Critical Gap Calculation								
Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
t(c,base)	4.1					7.1		6.2
t(c,hv)	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
P(hv)	53					72		13
t(c,g)			0.20	0.20	0.10	0.20	0.20	0.10
Percent Grade			0.00	0.00	0.00	0.00	0.00	0.00
t(3,lt)	0.00					0.70		0.00
t(c,T): 1-stage	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
2-stage	0.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
t(c) 1-stage	4.6					7.1		6.3
2-stage								

Follow-Up Time Calculations								
Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
t(f,base)	2.20					3.50		3.30
t(f,HV)	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
P(HV)	53					72		13
t(f)	2.7					4.1		3.4

Worksheet 5-Effect of Upstream Signals

Computation 1-Queue Clearance Time at Upstream Signal				
	Movement 2		Movement 5	
	V(t)	V(l,prot)	V(t)	V(l,prot)
V prog				

Total Saturation Flow Rate, s (vph)
Arrival Type
Effective Green, g (sec)
Cycle Length, C (sec)
Rp (from Exhibit 16-11)
Proportion vehicles arriving on green P
g(q1)
g(q2)
g(q)

Computation 2-Proportion of TWSC Intersection Time blocked

	Movement 2		Movement 5	
	V(t)	V(l,prot)	V(t)	V(l,prot)

alpha
beta
Travel time, t(a) (sec)
Smoothing Factor, F
Proportion of conflicting flow, f
Max platooned flow, V(c,max)
Min platooned flow, V(c,min)
Duration of blocked period, t(p)
Proportion time blocked, p

	0.000	0.000
--	-------	-------

Computation 3-Platoon Event Periods Result

p(2)	0.000
p(5)	0.000
p(dom)	
p(subo)	
Constrained or unconstrained?	

Proportion unblocked for minor movements, p(x)	(1) Single-stage Process	(2) Two-Stage Process Stage I	(3) Process Stage II
--	-----------------------------	-------------------------------------	----------------------------

p(1)
p(4)
p(7)
p(8)
p(9)
p(10)
p(11)
p(12)

Computation 4 and 5
Single-Stage Process
Movement

	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
V c, x	664					1051		636
s								
Px								
V c, u, x								
C r, x								
C plat, x								

Two-Stage Process

7	8	10	11
---	---	----	----

	Stage1	Stage2	Stage1	Stage2	Stage1	Stage2	Stage1	Stage2
--	--------	--------	--------	--------	--------	--------	--------	--------

V(c,x)								
S						1500		
P(x)								
V(c,u,x)								

C(r,x)								
C(plat,x)								

Worksheet 6-Impedance and Capacity Equations

Step 1: RT from Minor St.	9	12
---------------------------	---	----

Conflicting Flows		636
Potential Capacity		459
Pedestrian Impedance Factor	1.00	1.00
Movement Capacity		459
Probability of Queue free St.	1.00	0.64

Step 2: LT from Major St.	4	1
---------------------------	---	---

Conflicting Flows		664
Potential Capacity		725
Pedestrian Impedance Factor	1.00	1.00
Movement Capacity		725
Probability of Queue free St.	1.00	0.95
Maj L-Shared Prob Q free St.		0.94

Step 3: TH from Minor St.	8	11
---------------------------	---	----

Conflicting Flows		
Potential Capacity		
Pedestrian Impedance Factor	1.00	1.00
Cap. Adj. factor due to Impeding mvmnt	0.94	0.94
Movement Capacity		
Probability of Queue free St.	1.00	1.00

Step 4: LT from Minor St.	7	10
---------------------------	---	----

Conflicting Flows		1051
Potential Capacity		187
Pedestrian Impedance Factor	1.00	1.00
Maj. L, Min T Impedance factor	0.94	
Maj. L, Min T Adj. Imp Factor.	0.96	
Cap. Adj. factor due to Impeding mvmnt	0.61	0.95
Movement Capacity		178

Worksheet 7-Computation of the Effect of Two-stage Gap Acceptance

Step 3: TH from Minor St.	8	11
---------------------------	---	----

Part 1 - First Stage		
Conflicting Flows		
Potential Capacity		
Pedestrian Impedance Factor		
Cap. Adj. factor due to Impeding mvmnt		
Movement Capacity		
Probability of Queue free St.		

Part 2 - Second Stage
Conflicting Flows
Potential Capacity
Pedestrian Impedance Factor
Cap. Adj. factor due to Impeding mvmnt
Movement Capacity

Part 3 - Single Stage
Conflicting Flows
Potential Capacity
Pedestrian Impedance Factor 1.00 1.00
Cap. Adj. factor due to Impeding mvmnt 0.94 0.94
Movement Capacity

Result for 2 stage process:

a
y
C t
Probability of Queue free St. 1.00 1.00

Step 4: LT from Minor St. 7 10

Part 1 - First Stage
Conflicting Flows
Potential Capacity
Pedestrian Impedance Factor
Cap. Adj. factor due to Impeding mvmnt
Movement Capacity

Part 2 - Second Stage
Conflicting Flows
Potential Capacity
Pedestrian Impedance Factor
Cap. Adj. factor due to Impeding mvmnt
Movement Capacity

Part 3 - Single Stage
Conflicting Flows 1051
Potential Capacity 187
Pedestrian Impedance Factor 1.00 1.00
Maj. L, Min T Impedance factor 0.94
Maj. L, Min T Adj. Imp Factor. 0.96
Cap. Adj. factor due to Impeding mvmnt 0.61 0.95
Movement Capacity 178

Results for Two-stage process:

a
y
C t 178

Worksheet 8-Shared Lane Calculations

Movement	7	8	9	10	11	12
	L	T	R	L	T	R
Volume (vph)				58		167
Movement Capacity (vph)				178		459
Shared Lane Capacity (vph)					326	

Worksheet 9-Computation of Effect of Flared Minor Street Approaches

Movement	7 L	8 T	9 R	10 L	11 T	12 R
C sep				178		459
Volume				58		167
Delay						
Q sep						
Q sep +1						
round (Qsep +1)						
n max						
C sh					326	
SUM C sep						
n						
C act						

Worksheet 10-Delay, Queue Length, and Level of Service

Movement	1	4	7	8	9	10	11	12
Lane Config	LT						LR	
v (vph)	33						225	
C(m) (vph)	725						326	
v/c	0.05						0.69	
95% queue length	0.14						4.83	
Control Delay	10.2						37.4	
LOS	B						E	
Approach Delay							37.4	
Approach LOS							E	

Worksheet 11-Shared Major LT Impedance and Delay

	Movement 2	Movement 5
p(oj)	0.95	1.00
v(il), Volume for stream 2 or 5	349	
v(i2), Volume for stream 3 or 6	0	
s(il), Saturation flow rate for stream 2 or 5	1700	
s(i2), Saturation flow rate for stream 3 or 6	1700	
P*(oj)	0.94	
d(M,LT), Delay for stream 1 or 4	10.2	
N, Number of major street through lanes	1	
d(rank,1) Delay for stream 2 or 5	0.6	

Appendix F: Year-2016 ICAS with the Development

TWO-WAY STOP CONTROL SUMMARY

Analyst: CMaddox
 Agency/Co.: SEI
 Date Performed: 3/3/2014
 Analysis Time Period: AM Peak
 Intersection: Factory Shoals Rd & White Rd
 Jurisdiction: Cobb Co.
 Units: U. S. Customary
 Analysis Year: 2016 Developed
 Project ID:
 East/West Street: Factory Shoals Rd
 North/South Street: White Rd
 Intersection Orientation: EW

Study period (hrs): 0.25

Vehicle Volumes and Adjustments

Major Street:	Approach Movement	Eastbound				Westbound		
		1 L	2 T	3 R		4 L	5 T	6 R
Volume			383	21		38	201	
Peak-Hour Factor, PHF			0.92	0.92		0.92	0.92	
Hourly Flow Rate, HFR			416	22		41	218	
Percent Heavy Vehicles			--	--		2	--	--
Median Type/Storage		Undivided			/			
RT Channelized?								
Lanes			1	0		0	1	
Configuration			TR			LT		
Upstream Signal?			No			No		

Minor Street:	Approach Movement	Northbound				Southbound		
		7 L	8 T	9 R		10 L	11 T	12 R
Volume		10		20				
Peak Hour Factor, PHF		0.92		0.92				
Hourly Flow Rate, HFR		10		21				
Percent Heavy Vehicles		25		75				
Percent Grade (%)			0			0		
Flared Approach: Exists?/Storage		No			/			
Lanes		0		0				
Configuration			LR					

Delay, Queue Length, and Level of Service

Approach	EB	WB	Northbound			Southbound				
Movement	1	4		7	8	9		10	11	12
Lane Config		LT			LR					
v (vph)		41			31					
C(m) (vph)		1122			436					
v/c		0.04			0.07					
95% queue length		0.11			0.23					
Control Delay		8.3			13.9					
LOS		A			B					
Approach Delay					13.9					
Approach LOS					B					

HCS+: Unsignalized Intersections Release 5.6

Phone:
E-Mail:

Fax:

TWO-WAY STOP CONTROL(TWSC) ANALYSIS

Analyst: CMaddox
 Agency/Co.: SEI
 Date Performed: 3/3/2014
 Analysis Time Period: AM Peak
 Intersection: Factory Shoals Rd & White Rd
 Jurisdiction: Cobb Co.
 Units: U. S. Customary
 Analysis Year: 2016 Developed
 Project ID:
 East/West Street: Factory Shoals Rd
 North/South Street: White Rd
 Intersection Orientation: EW

Study period (hrs): 0.25

Vehicle Volumes and Adjustments

Major Street Movements	1 L	2 T	3 R	4 L	5 T	6 R
Volume		383	21	38	201	
Peak-Hour Factor, PHF		0.92	0.92	0.92	0.92	
Peak-15 Minute Volume		104	6	10	55	
Hourly Flow Rate, HFR		416	22	41	218	
Percent Heavy Vehicles		--	--	2	--	--
Median Type/Storage	Undivided			/		
RT Channelized?						
Lanes		1	0	0	1	
Configuration			TR		LT	
Upstream Signal?		No			No	
Minor Street Movements	7 L	8 T	9 R	10 L	11 T	12 R

Volume	10		20			
Peak Hour Factor, PHF	0.92		0.92			
Peak-15 Minute Volume	3		5			
Hourly Flow Rate, HFR	10		21			
Percent Heavy Vehicles	25		75			
Percent Grade (%)		0			0	
Flared Approach: Exists?/Storage			No	/		/
RT Channelized?						
Lanes	0		0			
Configuration		LR				

Pedestrian Volumes and Adjustments

Movements	13	14	15	16
Flow (ped/hr)	0	0	0	0

Lane Width (ft)	12.0	12.0	12.0	12.0
Walking Speed (ft/sec)	4.0	4.0	4.0	4.0
Percent Blockage	0	0	0	0

Upstream Signal Data							
	Prog. Flow vph	Sat Flow vph	Arrival Type	Green Time sec	Cycle Length sec	Prog. Speed mph	Distance to Signal feet
S2 Left-Turn Through							
S5 Left-Turn Through							

Worksheet 3-Data for Computing Effect of Delay to Major Street Vehicles

	Movement 2	Movement 5
Shared ln volume, major th vehicles:		218
Shared ln volume, major rt vehicles:		0
Sat flow rate, major th vehicles:		1700
Sat flow rate, major rt vehicles:		1700
Number of major street through lanes:		1

Worksheet 4-Critical Gap and Follow-up Time Calculation

Critical Gap Calculation								
Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
t(c,base)		4.1	7.1		6.2			
t(c,hv)	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
P(hv)		2	25		75			
t(c,g)			0.20	0.20	0.10	0.20	0.20	0.10
Percent Grade			0.00	0.00	0.00	0.00	0.00	0.00
t(3,lt)		0.00	0.70		0.00			
t(c,T): 1-stage	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
2-stage	0.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
t(c) 1-stage		4.1	6.7		6.9			
2-stage								

Follow-Up Time Calculations								
Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
t(f,base)		2.20	3.50		3.30			
t(f,HV)	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
P(HV)		2	25		75			
t(f)		2.2	3.7		4.0			

Worksheet 5-Effect of Upstream Signals

Computation 1-Queue Clearance Time at Upstream Signal				
	Movement 2		Movement 5	
	V(t)	V(l,prot)	V(t)	V(l,prot)
V prog				

Total Saturation Flow Rate, s (vph)
Arrival Type
Effective Green, g (sec)
Cycle Length, C (sec)
Rp (from Exhibit 16-11)
Proportion vehicles arriving on green P
g(q1)
g(q2)
g(q)

Computation 2-Proportion of TWSC Intersection Time blocked

	Movement 2		Movement 5	
	V(t)	V(l,prot)	V(t)	V(l,prot)

alpha
beta
Travel time, t(a) (sec)
Smoothing Factor, F
Proportion of conflicting flow, f
Max platooned flow, V(c,max)
Min platooned flow, V(c,min)
Duration of blocked period, t(p)
Proportion time blocked, p

	0.000	0.000
--	-------	-------

Computation 3-Platoon Event Periods Result

p(2)	0.000
p(5)	0.000
p(dom)	
p(subo)	
Constrained or unconstrained?	

Proportion unblocked for minor movements, p(x)	(1) Single-stage Process	(2) Two-Stage Stage I	(3) Process Stage II
---	--------------------------------	-----------------------------	----------------------------

p(1)
p(4)
p(7)
p(8)
p(9)
p(10)
p(11)
p(12)

Computation 4 and 5
Single-Stage Process

Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
----------	--------	--------	--------	--------	--------	---------	---------	---------

V c, x		438	727		427			
s								
Px								
V c, u, x								

C r, x
C plat, x

Two-Stage Process	7	8	10	11
-------------------	---	---	----	----

	Stage1	Stage2	Stage1	Stage2	Stage1	Stage2	Stage1	Stage2
--	--------	--------	--------	--------	--------	--------	--------	--------

V(c,x)
s
P(x)
V(c,u,x)

1500

C(r,x)
C(plat,x)

Worksheet 6-Impedance and Capacity Equations

Step 1: RT from Minor St.	9	12
---------------------------	---	----

Conflicting Flows	427	
Potential Capacity	498	
Pedestrian Impedance Factor	1.00	1.00
Movement Capacity	498	
Probability of Queue free St.	0.96	1.00

Step 2: LT from Major St.	4	1
---------------------------	---	---

Conflicting Flows	438	
Potential Capacity	1122	
Pedestrian Impedance Factor	1.00	1.00
Movement Capacity	1122	
Probability of Queue free St.	0.96	1.00
Maj L-Shared Prob Q free St.	0.96	

Step 3: TH from Minor St.	8	11
---------------------------	---	----

Conflicting Flows		
Potential Capacity		
Pedestrian Impedance Factor	1.00	1.00
Cap. Adj. factor due to Impeding mvmnt	0.96	0.96
Movement Capacity		
Probability of Queue free St.	1.00	1.00

Step 4: LT from Minor St.	7	10
---------------------------	---	----

Conflicting Flows	727	
Potential Capacity	359	
Pedestrian Impedance Factor	1.00	1.00
Maj. L, Min T Impedance factor		0.96
Maj. L, Min T Adj. Imp Factor.		0.97
Cap. Adj. factor due to Impeding mvmnt	0.96	0.93
Movement Capacity	346	

Worksheet 7-Computation of the Effect of Two-stage Gap Acceptance

Step 3: TH from Minor St.	8	11
---------------------------	---	----

Part 1 - First Stage
Conflicting Flows
Potential Capacity
Pedestrian Impedance Factor
Cap. Adj. factor due to Impeding mvmnt
Movement Capacity
Probability of Queue free St.

Part 2 - Second Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor
 Cap. Adj. factor due to Impeding mvmnt
 Movement Capacity

Part 3 - Single Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor 1.00 1.00
 Cap. Adj. factor due to Impeding mvmnt 0.96 0.96
 Movement Capacity

Result for 2 stage process:
 a
 y
 C t
 Probability of Queue free St. 1.00 1.00

Step 4: LT from Minor St. 7 10

Part 1 - First Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor
 Cap. Adj. factor due to Impeding mvmnt
 Movement Capacity

Part 2 - Second Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor
 Cap. Adj. factor due to Impeding mvmnt
 Movement Capacity

Part 3 - Single Stage
 Conflicting Flows 727
 Potential Capacity 359
 Pedestrian Impedance Factor 1.00 1.00
 Maj. L, Min T Impedance factor 0.96
 Maj. L, Min T Adj. Imp Factor. 0.97
 Cap. Adj. factor due to Impeding mvmnt 0.96 0.93
 Movement Capacity 346

Results for Two-stage process:
 a
 y
 C t 346

Worksheet 8-Shared Lane Calculations

Movement	7 L	8 T	9 R	10 L	11 T	12 R
Volume (vph)	10		21			
Movement Capacity (vph)	346		498			
Shared Lane Capacity (vph)		436				

Worksheet 9-Computation of Effect of Flared Minor Street Approaches

Movement	7 L	8 T	9 R	10 L	11 T	12 R
C sep	346		498			
Volume	10		21			
Delay						
Q sep						
Q sep +1						
round (Qsep +1)						
n max						
C sh		436				
SUM C sep						
n						
C act						

Worksheet 10-Delay, Queue Length, and Level of Service

Movement	1	4	7	8	9	10	11	12
Lane Config		LT		LR				
v (vph)		41		31				
C(m) (vph)		1122		436				
v/c		0.04		0.07				
95% queue length		0.11		0.23				
Control Delay		8.3		13.9				
LOS		A		B				
Approach Delay				13.9				
Approach LOS				B				

Worksheet 11-Shared Major LT Impedance and Delay

	Movement 2	Movement 5
p(oj)	1.00	0.96
v(il), Volume for stream 2 or 5		218
v(i2), Volume for stream 3 or 6		0
s(il), Saturation flow rate for stream 2 or 5		1700
s(i2), Saturation flow rate for stream 3 or 6		1700
P*(oj)		0.96
d(M,LT), Delay for stream 1 or 4		8.3
N, Number of major street through lanes		1
d(rank,1) Delay for stream 2 or 5		0.3

TWO-WAY STOP CONTROL SUMMARY

Analyst: CMaddox
 Agency/Co.: SEI
 Date Performed: 3/3/2014
 Analysis Time Period: PM Peak
 Intersection: Factory Shoals Rd & White Rd
 Jurisdiction: Cobb Co.
 Units: U. S. Customary
 Analysis Year: 2016 Developed
 Project ID:
 East/West Street: Factory Shoals Rd
 North/South Street: White Rd
 Intersection Orientation: EW

Study period (hrs): 0.25

Vehicle Volumes and Adjustments

Major Street:	Approach Movement	Eastbound				Westbound		
		1 L	2 T	3 R		4 L	5 T	6 R
Volume		238	14			47	292	
Peak-Hour Factor, PHF		0.92	0.92			0.92	0.92	
Hourly Flow Rate, HFR		258	15			51	317	
Percent Heavy Vehicles		--	--			2	--	--
Median Type/Storage		Undivided			/			
RT Channelized?								
Lanes		1	0			0	1	
Configuration		TR				LT		
Upstream Signal?		No				No		

Minor Street:	Approach Movement	Northbound				Southbound		
		7 L	8 T	9 R		10 L	11 T	12 R
Volume		57		45				
Peak Hour Factor, PHF		0.92		0.92				
Hourly Flow Rate, HFR		61		48				
Percent Heavy Vehicles		14		2				
Percent Grade (%)			0				0	
Flared Approach: Exists?/Storage		No			/			
Lanes		0	0					
Configuration		LR						

Delay, Queue Length, and Level of Service

Approach	EB	WB	Northbound			Southbound				
Movement	1	4		7	8	9		10	11	12
Lane Config		LT			LR					
v (vph)		51			109					
C(m) (vph)		1290			490					
v/c		0.04			0.22					
95% queue length		0.12			0.84					
Control Delay		7.9			14.4					
LOS		A			B					
Approach Delay					14.4					
Approach LOS					B					

HCS+: Unsignalized Intersections Release 5.6

Phone:
E-Mail:

Fax:

TWO-WAY STOP CONTROL(TWSC) ANALYSIS

Analyst: CMaddox
 Agency/Co.: SEI
 Date Performed: 3/3/2014
 Analysis Time Period: PM Peak
 Intersection: Factory Shoals Rd & White Rd
 Jurisdiction: Cobb Co.
 Units: U. S. Customary
 Analysis Year: 2016 Developed
 Project ID:
 East/West Street: Factory Shoals Rd
 North/South Street: White Rd
 Intersection Orientation: EW

Study period (hrs): 0.25

Vehicle Volumes and Adjustments

Major Street Movements	1 L	2 T	3 R	4 L	5 T	6 R
Volume		238	14	47	292	
Peak-Hour Factor, PHF		0.92	0.92	0.92	0.92	
Peak-15 Minute Volume		65	4	13	79	
Hourly Flow Rate, HFR		258	15	51	317	
Percent Heavy Vehicles		--	--	2	--	--
Median Type/Storage	Undivided			/		
RT Channelized?						
Lanes		1	0	0	1	
Configuration			TR		LT	
Upstream Signal?		No			No	
Minor Street Movements	7 L	8 T	9 R	10 L	11 T	12 R

Volume	57		45			
Peak Hour Factor, PHF	0.92		0.92			
Peak-15 Minute Volume	15		12			
Hourly Flow Rate, HFR	61		48			
Percent Heavy Vehicles	14		2			
Percent Grade (%)		0			0	
Flared Approach: Exists?/Storage			No	/		/
RT Channelized?						
Lanes	0		0			
Configuration		LR				

Pedestrian Volumes and Adjustments

Movements	13	14	15	16
Flow (ped/hr)	0	0	0	0

Lane Width (ft)	12.0	12.0	12.0	12.0
Walking Speed (ft/sec)	4.0	4.0	4.0	4.0
Percent Blockage	0	0	0	0

Upstream Signal Data							
	Prog. Flow vph	Sat Flow vph	Arrival Type	Green Time sec	Cycle Length sec	Prog. Speed mph	Distance to Signal feet
S2 Left-Turn Through							
S5 Left-Turn Through							

Worksheet 3-Data for Computing Effect of Delay to Major Street Vehicles

	Movement 2	Movement 5
Shared ln volume, major th vehicles:		317
Shared ln volume, major rt vehicles:		0
Sat flow rate, major th vehicles:		1700
Sat flow rate, major rt vehicles:		1700
Number of major street through lanes:		1

Worksheet 4-Critical Gap and Follow-up Time Calculation

Critical Gap Calculation								
Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
t(c,base)		4.1	7.1		6.2			
t(c,hv)	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
P(hv)		2	14		2			
t(c,g)			0.20	0.20	0.10	0.20	0.20	0.10
Percent Grade			0.00	0.00	0.00	0.00	0.00	0.00
t(3,lt)		0.00	0.70		0.00			
t(c,T): 1-stage	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
2-stage	0.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
t(c) 1-stage		4.1	6.5		6.2			
2-stage								

Follow-Up Time Calculations								
Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
t(f,base)		2.20	3.50		3.30			
t(f,HV)	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
P(HV)		2	14		2			
t(f)		2.2	3.6		3.3			

Worksheet 5-Effect of Upstream Signals

Computation 1-Queue Clearance Time at Upstream Signal				
	Movement 2		Movement 5	
	V(t)	V(l,prot)	V(t)	V(l,prot)
V prog				

Total Saturation Flow Rate, s (vph)
Arrival Type
Effective Green, g (sec)
Cycle Length, C (sec)
Rp (from Exhibit 16-11)
Proportion vehicles arriving on green P
g(q1)
g(q2)
g(q)

Computation 2-Proportion of TWSC Intersection Time blocked

	Movement 2		Movement 5	
	V(t)	V(l,prot)	V(t)	V(l,prot)

alpha
beta
Travel time, t(a) (sec)
Smoothing Factor, F
Proportion of conflicting flow, f
Max platooned flow, V(c,max)
Min platooned flow, V(c,min)
Duration of blocked period, t(p)
Proportion time blocked, p

	0.000	0.000
--	-------	-------

Computation 3-Platoon Event Periods Result

p(2)	0.000
p(5)	0.000
p(dom)	
p(subo)	
Constrained or unconstrained?	

Proportion unblocked for minor movements, p(x)	(1) Single-stage Process	(2) Two-Stage Stage I	(3) Process Stage II
--	-----------------------------	--------------------------	-------------------------

p(1)
p(4)
p(7)
p(8)
p(9)
p(10)
p(11)
p(12)

Computation 4 and 5
Single-Stage Process

Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
----------	--------	--------	--------	--------	--------	---------	---------	---------

V c, x		273	685		266			
s								
Px								
V c, u, x								

C r, x
C plat, x

Two-Stage Process	7	8	10	11
-------------------	---	---	----	----

	Stage1	Stage2	Stage1	Stage2	Stage1	Stage2	Stage1	Stage2
--	--------	--------	--------	--------	--------	--------	--------	--------

V(c,x)
s
P(x)
V(c,u,x)

1500

C(r,x)
C(plat,x)

Worksheet 6-Impedance and Capacity Equations

Step 1: RT from Minor St.	9	12
---------------------------	---	----

Conflicting Flows	266	
Potential Capacity	773	
Pedestrian Impedance Factor	1.00	1.00
Movement Capacity	773	
Probability of Queue free St.	0.94	1.00

Step 2: LT from Major St.	4	1
---------------------------	---	---

Conflicting Flows	273	
Potential Capacity	1290	
Pedestrian Impedance Factor	1.00	1.00
Movement Capacity	1290	
Probability of Queue free St.	0.96	1.00
Maj L-Shared Prob Q free St.	0.95	

Step 3: TH from Minor St.	8	11
---------------------------	---	----

Conflicting Flows		
Potential Capacity		
Pedestrian Impedance Factor	1.00	1.00
Cap. Adj. factor due to Impeding mvmnt	0.95	0.95
Movement Capacity		
Probability of Queue free St.	1.00	1.00

Step 4: LT from Minor St.	7	10
---------------------------	---	----

Conflicting Flows	685	
Potential Capacity	396	
Pedestrian Impedance Factor	1.00	1.00
Maj. L, Min T Impedance factor		0.95
Maj. L, Min T Adj. Imp Factor.		0.96
Cap. Adj. factor due to Impeding mvmnt	0.96	0.90
Movement Capacity	380	

Worksheet 7-Computation of the Effect of Two-stage Gap Acceptance

Step 3: TH from Minor St.	8	11
---------------------------	---	----

Part 1 - First Stage
Conflicting Flows
Potential Capacity
Pedestrian Impedance Factor
Cap. Adj. factor due to Impeding mvmnt
Movement Capacity
Probability of Queue free St.

Part 2 - Second Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor
 Cap. Adj. factor due to Impeding mvmnt
 Movement Capacity

Part 3 - Single Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor 1.00 1.00
 Cap. Adj. factor due to Impeding mvmnt 0.95 0.95
 Movement Capacity

Result for 2 stage process:

a
 y
 C t
 Probability of Queue free St. 1.00 1.00

Step 4: LT from Minor St. 7 10

Part 1 - First Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor
 Cap. Adj. factor due to Impeding mvmnt
 Movement Capacity

Part 2 - Second Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor
 Cap. Adj. factor due to Impeding mvmnt
 Movement Capacity

Part 3 - Single Stage
 Conflicting Flows 685
 Potential Capacity 396
 Pedestrian Impedance Factor 1.00 1.00
 Maj. L, Min T Impedance factor 0.95
 Maj. L, Min T Adj. Imp Factor. 0.96
 Cap. Adj. factor due to Impeding mvmnt 0.96 0.90
 Movement Capacity 380

Results for Two-stage process:

a
 y
 C t 380

Worksheet 8-Shared Lane Calculations

Movement	7 L	8 T	9 R	10 L	11 T	12 R
Volume (vph)	61		48			
Movement Capacity (vph)	380		773			
Shared Lane Capacity (vph)		490				

Worksheet 9-Computation of Effect of Flared Minor Street Approaches

Movement	7 L	8 T	9 R	10 L	11 T	12 R
C sep	380		773			
Volume	61		48			
Delay						
Q sep						
Q sep +1						
round (Qsep +1)						
n max						
C sh		490				
SUM C sep						
n						
C act						

Worksheet 10-Delay, Queue Length, and Level of Service

Movement	1	4	7	8	9	10	11	12
Lane Config		LT		LR				
v (vph)		51		109				
C(m) (vph)		1290		490				
v/c		0.04		0.22				
95% queue length		0.12		0.84				
Control Delay		7.9		14.4				
LOS		A		B				
Approach Delay				14.4				
Approach LOS				B				

Worksheet 11-Shared Major LT Impedance and Delay

	Movement 2	Movement 5
p(oj)	1.00	0.96
v(il), Volume for stream 2 or 5		317
v(i2), Volume for stream 3 or 6		0
s(il), Saturation flow rate for stream 2 or 5		1700
s(i2), Saturation flow rate for stream 3 or 6		1700
P*(oj)		0.95
d(M,LT), Delay for stream 1 or 4		7.9
N, Number of major street through lanes		1
d(rank,1) Delay for stream 2 or 5		0.4

HCS+: Unsignalized Intersections Release 5.6

Phone:
E-Mail:

Fax:

TWO-WAY STOP CONTROL(TWSC) ANALYSIS

Analyst: CMaddox
Agency/Co.: SEI
Date Performed: 3/3/2014
Analysis Time Period: AM Peak
Intersection: Riverside Pkwy & White Rd
Jurisdiction: Cobb Co.
Units: U. S. Customary
Analysis Year: 2016 Developed
Project ID:
East/West Street: Riverside Pkwy
North/South Street: White Rd
Intersection Orientation: EW

Study period (hrs): 0.25

Vehicle Volumes and Adjustments

Major Street Movements	1 L	2 T	3 R	4 L	5 T	6 R
Volume	123	734			294	52
Peak-Hour Factor, PHF	0.92	0.92			0.92	0.92
Peak-15 Minute Volume	33	199			80	14
Hourly Flow Rate, HFR	133	797			319	56
Percent Heavy Vehicles	31	--	--		--	--
Median Type/Storage	Undivided			/		
RT Channelized?						
Lanes	0	1			1	0
Configuration	LT				TR	
Upstream Signal?		No			No	
Minor Street Movements	7 L	8 T	9 R	10 L	11 T	12 R

Volume				32		88
Peak Hour Factor, PHF				0.92		0.92
Peak-15 Minute Volume				9		24
Hourly Flow Rate, HFR				34		95
Percent Heavy Vehicles				75		40
Percent Grade (%)		0			0	
Flared Approach: Exists?/Storage				/		No /
RT Channelized?						
Lanes				0		0
Configuration					LR	

Pedestrian Volumes and Adjustments

Movements	13	14	15	16
Flow (ped/hr)	0	0	0	0

Lane Width (ft)	12.0	12.0	12.0	12.0
Walking Speed (ft/sec)	4.0	4.0	4.0	4.0
Percent Blockage	0	0	0	0

Upstream Signal Data							
	Prog. Flow vph	Sat Flow vph	Arrival Type	Green Time sec	Cycle Length sec	Prog. Speed mph	Distance to Signal feet
S2 Left-Turn Through							
S5 Left-Turn Through							

Worksheet 3-Data for Computing Effect of Delay to Major Street Vehicles

	Movement 2	Movement 5
Shared ln volume, major th vehicles:	797	
Shared ln volume, major rt vehicles:	0	
Sat flow rate, major th vehicles:	1700	
Sat flow rate, major rt vehicles:	1700	
Number of major street through lanes:	1	

Worksheet 4-Critical Gap and Follow-up Time Calculation

Critical Gap Calculation								
Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
t(c,base)	4.1					7.1		6.2
t(c,hv)	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
P(hv)	31					75		40
t(c,g)			0.20	0.20	0.10	0.20	0.20	0.10
Percent Grade			0.00	0.00	0.00	0.00	0.00	0.00
t(3,lt)	0.00					0.70		0.00
t(c,T): 1-stage	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
2-stage	0.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
t(c) 1-stage	4.4					7.2		6.6
2-stage								

Follow-Up Time Calculations								
Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
t(f,base)	2.20					3.50		3.30
t(f,HV)	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
P(HV)	31					75		40
t(f)	2.5					4.2		3.7

Worksheet 5-Effect of Upstream Signals

Computation 1-Queue Clearance Time at Upstream Signal				
	Movement 2		Movement 5	
	V(t)	V(l,prot)	V(t)	V(l,prot)
V prog				

Total Saturation Flow Rate, s (vph)
Arrival Type
Effective Green, g (sec)
Cycle Length, C (sec)
Rp (from Exhibit 16-11)
Proportion vehicles arriving on green P
g(q1)
g(q2)
g(q)

Computation 2-Proportion of TWSC Intersection Time blocked

	Movement 2		Movement 5	
	V(t)	V(l,prot)	V(t)	V(l,prot)

alpha
beta
Travel time, t(a) (sec)
Smoothing Factor, F
Proportion of conflicting flow, f
Max platooned flow, V(c,max)
Min platooned flow, V(c,min)
Duration of blocked period, t(p)
Proportion time blocked, p

	0.000	0.000
--	-------	-------

Computation 3-Platoon Event Periods Result

p(2)	0.000
p(5)	0.000
p(dom)	
p(subo)	
Constrained or unconstrained?	

Proportion unblocked for minor movements, p(x)	(1) Single-stage Process	(2) Two-Stage Process Stage I	(3) Process Stage II
--	-----------------------------	-------------------------------------	----------------------------

p(1)
p(4)
p(7)
p(8)
p(9)
p(10)
p(11)
p(12)

Computation 4 and 5
Single-Stage Process

Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
V c, x	375					1410		347
S								
Px								
V c, u, x								
C r, x								
C plat, x								

Two-Stage Process

7	8	10	11
---	---	----	----

V(c,x)								
s						1500		
P(x)								
V(c,u,x)								

C(r,x)								
C(plat,x)								

Worksheet 6-Impedance and Capacity Equations

Step 1: RT from Minor St.	9	12
---------------------------	---	----

Conflicting Flows		347
Potential Capacity		618
Pedestrian Impedance Factor	1.00	1.00
Movement Capacity		618
Probability of Queue free St.	1.00	0.85

Step 2: LT from Major St.	4	1
---------------------------	---	---

Conflicting Flows		375
Potential Capacity		1041
Pedestrian Impedance Factor	1.00	1.00
Movement Capacity		1041
Probability of Queue free St.	1.00	0.87
Maj L-Shared Prob Q free St.		0.76

Step 3: TH from Minor St.	8	11
---------------------------	---	----

Conflicting Flows		
Potential Capacity		
Pedestrian Impedance Factor	1.00	1.00
Cap. Adj. factor due to Impeding mvmnt	0.76	0.76
Movement Capacity		
Probability of Queue free St.	1.00	1.00

Step 4: LT from Minor St.	7	10
---------------------------	---	----

Conflicting Flows		1410
Potential Capacity		106
Pedestrian Impedance Factor	1.00	1.00
Maj. L, Min T Impedance factor	0.76	
Maj. L, Min T Adj. Imp Factor.	0.81	
Cap. Adj. factor due to Impeding mvmnt	0.69	0.87
Movement Capacity		92

Worksheet 7-Computation of the Effect of Two-stage Gap Acceptance

Step 3: TH from Minor St.	8	11
---------------------------	---	----

Part 1 - First Stage		
Conflicting Flows		
Potential Capacity		
Pedestrian Impedance Factor		
Cap. Adj. factor due to Impeding mvmnt		
Movement Capacity		
Probability of Queue free St.		

Part 2 - Second Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor
 Cap. Adj. factor due to Impeding mvmnt
 Movement Capacity

Part 3 - Single Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor 1.00 1.00
 Cap. Adj. factor due to Impeding mvmnt 0.76 0.76
 Movement Capacity

Result for 2 stage process:
 a
 y
 C t
 Probability of Queue free St. 1.00 1.00

Step 4: LT from Minor St. 7 10

Part 1 - First Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor
 Cap. Adj. factor due to Impeding mvmnt
 Movement Capacity

Part 2 - Second Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor
 Cap. Adj. factor due to Impeding mvmnt
 Movement Capacity

Part 3 - Single Stage
 Conflicting Flows 1410
 Potential Capacity 106
 Pedestrian Impedance Factor 1.00 1.00
 Maj. L, Min T Impedance factor 0.76
 Maj. L, Min T Adj. Imp Factor. 0.81
 Cap. Adj. factor due to Impeding mvmnt 0.69 0.87
 Movement Capacity 92

Results for Two-stage process:
 a
 y
 C t 92

Worksheet 8-Shared Lane Calculations

Movement	7 L	8 T	9 R	10 L	11 T	12 R
Volume (vph)				34		95
Movement Capacity (vph)				92		618
Shared Lane Capacity (vph)					247	

Worksheet 9-Computation of Effect of Flared Minor Street Approaches

Movement	7 L	8 T	9 R	10 L	11 T	12 R
C sep				92		618
Volume				34		95
Delay						
Q sep						
Q sep +1						
round (Qsep +1)						
n max						
C sh					247	
SUM C sep						
n						
C act						

Worksheet 10-Delay, Queue Length, and Level of Service

Movement	1	4	7	8	9	10	11	12
Lane Config	LT						LR	
v (vph)	133						129	
C(m) (vph)	1041						247	
v/c	0.13						0.52	
95% queue length	0.44						2.76	
Control Delay	9.0						34.5	
LOS	A						D	
Approach Delay							34.5	
Approach LOS							D	

Worksheet 11-Shared Major LT Impedance and Delay

	Movement 2	Movement 5
p(oj)	0.87	1.00
v(il), Volume for stream 2 or 5	797	
v(i2), Volume for stream 3 or 6	0	
s(il), Saturation flow rate for stream 2 or 5	1700	
s(i2), Saturation flow rate for stream 3 or 6	1700	
P*(oj)	0.76	
d(M,LT), Delay for stream 1 or 4	9.0	
N, Number of major street through lanes	1	
d(rank,1) Delay for stream 2 or 5	2.2	

HCS+: Unsignalized Intersections Release 5.6

Phone:
E-Mail:

Fax:

TWO-WAY STOP CONTROL(TWSC) ANALYSIS

Analyst: CMaddox
 Agency/Co.: SEI
 Date Performed: 3/3/2014
 Analysis Time Period: PM Peak
 Intersection: Riverside Pkwy & White Rd
 Jurisdiction: Cobb Co.
 Units: U. S. Customary
 Analysis Year: 2016 Developed
 Project ID:
 East/West Street: Riverside Pkwy
 North/South Street: White Rd
 Intersection Orientation: EW

Study period (hrs): 0.25

Vehicle Volumes and Adjustments

Major Street Movements	1 L	2 T	3 R	4 L	5 T	6 R
Volume	31	322			561	51
Peak-Hour Factor, PHF	0.92	0.92			0.92	0.92
Peak-15 Minute Volume	8	88			152	14
Hourly Flow Rate, HFR	33	349			609	55
Percent Heavy Vehicles	53	--	--		--	--
Median Type/Storage	Undivided			/		
RT Channelized?						
Lanes	0	1			1	0
Configuration	LT				TR	
Upstream Signal?		No			No	
Minor Street Movements	7 L	8 T	9 R	10 L	11 T	12 R

Volume				54		154
Peak Hour Factor, PHF				0.92		0.92
Peak-15 Minute Volume				15		42
Hourly Flow Rate, HFR				58		167
Percent Heavy Vehicles				72		13
Percent Grade (%)		0			0	
Flared Approach: Exists?/Storage				/		No /
RT Channelized?						
Lanes				0		0
Configuration					LR	

Pedestrian Volumes and Adjustments

Movements	13	14	15	16
Flow (ped/hr)	0	0	0	0

Lane Width (ft)	12.0	12.0	12.0	12.0
Walking Speed (ft/sec)	4.0	4.0	4.0	4.0
Percent Blockage	0	0	0	0

Upstream Signal Data							
	Prog. Flow vph	Sat Flow vph	Arrival Type	Green Time sec	Cycle Length sec	Prog. Speed mph	Distance to Signal feet
S2 Left-Turn Through							
S5 Left-Turn Through							

Worksheet 3-Data for Computing Effect of Delay to Major Street Vehicles

	Movement 2	Movement 5
Shared ln volume, major th vehicles:	349	
Shared ln volume, major rt vehicles:	0	
Sat flow rate, major th vehicles:	1700	
Sat flow rate, major rt vehicles:	1700	
Number of major street through lanes:	1	

Worksheet 4-Critical Gap and Follow-up Time Calculation

Critical Gap Calculation								
Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
t(c,base)	4.1					7.1		6.2
t(c,hv)	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
P(hv)	53					72		13
t(c,g)			0.20	0.20	0.10	0.20	0.20	0.10
Percent Grade			0.00	0.00	0.00	0.00	0.00	0.00
t(3,lt)	0.00					0.70		0.00
t(c,T): 1-stage	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
2-stage	0.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
t(c) 1-stage	4.6					7.1		6.3
2-stage								

Follow-Up Time Calculations								
Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
t(f,base)	2.20					3.50		3.30
t(f,HV)	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
P(HV)	53					72		13
t(f)	2.7					4.1		3.4

Worksheet 5-Effect of Upstream Signals

Computation 1-Queue Clearance Time at Upstream Signal				
	Movement 2		Movement 5	
	V(t)	V(l,prot)	V(t)	V(l,prot)
V prog				

Total Saturation Flow Rate, s (vph)
Arrival Type
Effective Green, g (sec)
Cycle Length, C (sec)
Rp (from Exhibit 16-11)
Proportion vehicles arriving on green P
g(q1)
g(q2)
g(q)

Computation 2-Proportion of TWSC Intersection Time blocked

	Movement 2		Movement 5	
	V(t)	V(l,prot)	V(t)	V(l,prot)

alpha
beta
Travel time, t(a) (sec)
Smoothing Factor, F
Proportion of conflicting flow, f
Max platooned flow, V(c,max)
Min platooned flow, V(c,min)
Duration of blocked period, t(p)
Proportion time blocked, p

	0.000	0.000
--	-------	-------

Computation 3-Platoon Event Periods Result

p(2)	0.000
p(5)	0.000
p(dom)	
p(subo)	
Constrained or unconstrained?	

Proportion unblocked for minor movements, p(x)	(1) Single-stage Process	(2) Two-Stage Stage I	(3) Process Stage II
---	--------------------------------	-----------------------------	----------------------------

p(1)
p(4)
p(7)
p(8)
p(9)
p(10)
p(11)
p(12)

Computation 4 and 5
Single-Stage Process
Movement

	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
V c, x	664					1051		636
s								
Px								
V c, u, x								
C r, x								
C plat, x								

Two-Stage Process

7	8	10	11
---	---	----	----

	Stage1	Stage2	Stage1	Stage2	Stage1	Stage2	Stage1	Stage2
--	--------	--------	--------	--------	--------	--------	--------	--------

V(c,x)								
S						1500		
P(x)								
V(c,u,x)								

C(r,x)								
C(plat,x)								

Worksheet 6-Impedance and Capacity Equations

Step 1: RT from Minor St.	9	12
---------------------------	---	----

Conflicting Flows		636
Potential Capacity		459
Pedestrian Impedance Factor	1.00	1.00
Movement Capacity		459
Probability of Queue free St.	1.00	0.64

Step 2: LT from Major St.	4	1
---------------------------	---	---

Conflicting Flows		664
Potential Capacity		725
Pedestrian Impedance Factor	1.00	1.00
Movement Capacity		725
Probability of Queue free St.	1.00	0.95
Maj L-Shared Prob Q free St.		0.94

Step 3: TH from Minor St.	8	11
---------------------------	---	----

Conflicting Flows		
Potential Capacity		
Pedestrian Impedance Factor	1.00	1.00
Cap. Adj. factor due to Impeding mvmnt	0.94	0.94
Movement Capacity		
Probability of Queue free St.	1.00	1.00

Step 4: LT from Minor St.	7	10
---------------------------	---	----

Conflicting Flows		1051
Potential Capacity		187
Pedestrian Impedance Factor	1.00	1.00
Maj. L, Min T Impedance factor	0.94	
Maj. L, Min T Adj. Imp Factor.	0.96	
Cap. Adj. factor due to Impeding mvmnt	0.61	0.95
Movement Capacity		178

Worksheet 7-Computation of the Effect of Two-stage Gap Acceptance

Step 3: TH from Minor St.	8	11
---------------------------	---	----

Part 1 - First Stage		
Conflicting Flows		
Potential Capacity		
Pedestrian Impedance Factor		
Cap. Adj. factor due to Impeding mvmnt		
Movement Capacity		
Probability of Queue free St.		

Worksheet 9-Computation of Effect of Flared Minor Street Approaches

Movement	7 L	8 T	9 R	10 L	11 T	12 R
C sep				178		459
Volume				58		167
Delay						
Q sep						
Q sep +1						
round (Qsep +1)						
n max						
C sh					326	
SUM C sep						
n						
C act						

Worksheet 10-Delay, Queue Length, and Level of Service

Movement	1	4	7	8	9	10	11	12
Lane Config	LT						LR	
v (vph)	33						225	
C(m) (vph)	725						326	
v/c	0.05						0.69	
95% queue length	0.14						4.83	
Control Delay	10.2						37.4	
LOS	B						E	
Approach Delay							37.4	
Approach LOS							E	

Worksheet 11-Shared Major LT Impedance and Delay

	Movement 2	Movement 5
p(oj)	0.95	1.00
v(il), Volume for stream 2 or 5	349	
v(i2), Volume for stream 3 or 6	0	
s(il), Saturation flow rate for stream 2 or 5	1700	
s(i2), Saturation flow rate for stream 3 or 6	1700	
P*(oj)	0.94	
d(M,LT), Delay for stream 1 or 4	10.2	
N, Number of major street through lanes	1	
d(rank,1) Delay for stream 2 or 5	0.6	

HCS+: Unsignalized Intersections Release 5.6

Phone:
E-Mail:

Fax:

TWO-WAY STOP CONTROL(TWSC) ANALYSIS

Analyst: CMaddox
 Agency/Co.: SEI
 Date Performed: 3/3/2014
 Analysis Time Period: AM Peak
 Intersection: Riverside Pkwy & White Rd
 Jurisdiction: Cobb Co.
 Units: U. S. Customary
 Analysis Year: 2016 Developed Improved
 Project ID:
 East/West Street: Riverside Pkwy
 North/South Street: White Rd
 Intersection Orientation: EW

Study period (hrs): 0.25

Vehicle Volumes and Adjustments

Major Street Movements	1 L	2 T	3 R	4 L	5 T	6 R
Volume	123	734			294	52
Peak-Hour Factor, PHF	0.92	0.92			0.92	0.92
Peak-15 Minute Volume	33	199			80	14
Hourly Flow Rate, HFR	133	797			319	56
Percent Heavy Vehicles	31	--	--		--	--
Median Type/Storage	Undivided			/		
RT Channelized?						
Lanes	0	1			1	0
Configuration	LT				TR	
Upstream Signal?		No			No	
Minor Street Movements	7 L	8 T	9 R	10 L	11 T	12 R

Volume			32		88
Peak Hour Factor, PHF			0.92		0.92
Peak-15 Minute Volume			9		24
Hourly Flow Rate, HFR			34		95
Percent Heavy Vehicles			75		40
Percent Grade (%)		0		0	
Flared Approach: Exists?/Storage			/		Yes /1
RT Channelized?					
Lanes			0		0
Configuration				LR	

Pedestrian Volumes and Adjustments

Movements	13	14	15	16
Flow (ped/hr)	0	0	0	0

Lane Width (ft)	12.0	12.0	12.0	12.0
Walking Speed (ft/sec)	4.0	4.0	4.0	4.0
Percent Blockage	0	0	0	0

Upstream Signal Data							
	Prog. Flow vph	Sat Flow vph	Arrival Type	Green Time sec	Cycle Length sec	Prog. Speed mph	Distance to Signal feet
S2 Left-Turn Through							
S5 Left-Turn Through							

Worksheet 3-Data for Computing Effect of Delay to Major Street Vehicles

	Movement 2	Movement 5
Shared ln volume, major th vehicles:	797	
Shared ln volume, major rt vehicles:	0	
Sat flow rate, major th vehicles:	1700	
Sat flow rate, major rt vehicles:	1700	
Number of major street through lanes:	1	

Worksheet 4-Critical Gap and Follow-up Time Calculation

Critical Gap Calculation								
Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
t(c,base)	4.1					7.1		6.2
t(c,hv)	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
P(hv)	31					75		40
t(c,g)			0.20	0.20	0.10	0.20	0.20	0.10
Percent Grade			0.00	0.00	0.00	0.00	0.00	0.00
t(3,lt)	0.00					0.70		0.00
t(c,T): 1-stage	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
2-stage	0.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
t(c) 1-stage	4.4					7.2		6.6
2-stage								

Follow-Up Time Calculations								
Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
t(f,base)	2.20					3.50		3.30
t(f,HV)	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
P(HV)	31					75		40
t(f)	2.5					4.2		3.7

Worksheet 5-Effect of Upstream Signals

Computation 1-Queue Clearance Time at Upstream Signal				
	Movement 2		Movement 5	
	V(t)	V(l,prot)	V(t)	V(l,prot)
V prog				

Total Saturation Flow Rate, s (vph)
Arrival Type
Effective Green, g (sec)
Cycle Length, C (sec)
Rp (from Exhibit 16-11)
Proportion vehicles arriving on green P
g(q1)
g(q2)
g(q)

Computation 2-Proportion of TWSC Intersection Time blocked

	Movement 2		Movement 5	
	V(t)	V(l,prot)	V(t)	V(l,prot)

alpha
beta
Travel time, t(a) (sec)
Smoothing Factor, F
Proportion of conflicting flow, f
Max platooned flow, V(c,max)
Min platooned flow, V(c,min)
Duration of blocked period, t(p)
Proportion time blocked, p

	0.000	0.000
--	-------	-------

Computation 3-Platoon Event Periods Result

p(2)	0.000
p(5)	0.000
p(dom)	
p(subo)	
Constrained or unconstrained?	

Proportion unblocked for minor movements, p(x)	(1) Single-stage Process	(2) Two-Stage Stage I	(3) Process Stage II
---	--------------------------------	-----------------------------	----------------------------

p(1)
p(4)
p(7)
p(8)
p(9)
p(10)
p(11)
p(12)

Computation 4 and 5
Single-Stage Process

Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
V c, x	375					1410		347
s								
Px								
V c, u, x								
C r, x								
C plat, x								

Two-Stage Process

7	8	10	11
---	---	----	----

V(c,x)								
s						1500		
P(x)								
V(c,u,x)								

C(r,x)								
C(plat,x)								

Worksheet 6-Impedance and Capacity Equations

Step 1: RT from Minor St.	9	12
---------------------------	---	----

Conflicting Flows		347
Potential Capacity		618
Pedestrian Impedance Factor	1.00	1.00
Movement Capacity		618
Probability of Queue free St.	1.00	0.85

Step 2: LT from Major St.	4	1
---------------------------	---	---

Conflicting Flows		375
Potential Capacity		1041
Pedestrian Impedance Factor	1.00	1.00
Movement Capacity		1041
Probability of Queue free St.	1.00	0.87
Maj L-Shared Prob Q free St.		0.76

Step 3: TH from Minor St.	8	11
---------------------------	---	----

Conflicting Flows		
Potential Capacity		
Pedestrian Impedance Factor	1.00	1.00
Cap. Adj. factor due to Impeding mvmnt	0.76	0.76
Movement Capacity		
Probability of Queue free St.	1.00	1.00

Step 4: LT from Minor St.	7	10
---------------------------	---	----

Conflicting Flows		1410
Potential Capacity		106
Pedestrian Impedance Factor	1.00	1.00
Maj. L, Min T Impedance factor	0.76	
Maj. L, Min T Adj. Imp Factor.	0.81	
Cap. Adj. factor due to Impeding mvmnt	0.69	0.87
Movement Capacity		92

Worksheet 7-Computation of the Effect of Two-stage Gap Acceptance

Step 3: TH from Minor St.	8	11
---------------------------	---	----

Part 1 - First Stage		
Conflicting Flows		
Potential Capacity		
Pedestrian Impedance Factor		
Cap. Adj. factor due to Impeding mvmnt		
Movement Capacity		
Probability of Queue free St.		

Part 2 - Second Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor
 Cap. Adj. factor due to Impeding mvmnt
 Movement Capacity

Part 3 - Single Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor 1.00 1.00
 Cap. Adj. factor due to Impeding mvmnt 0.76 0.76
 Movement Capacity

Result for 2 stage process:
 a
 y
 C t
 Probability of Queue free St. 1.00 1.00

Step 4: LT from Minor St. 7 10

Part 1 - First Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor
 Cap. Adj. factor due to Impeding mvmnt
 Movement Capacity

Part 2 - Second Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor
 Cap. Adj. factor due to Impeding mvmnt
 Movement Capacity

Part 3 - Single Stage
 Conflicting Flows 1410
 Potential Capacity 106
 Pedestrian Impedance Factor 1.00 1.00
 Maj. L, Min T Impedance factor 0.76
 Maj. L, Min T Adj. Imp Factor. 0.81
 Cap. Adj. factor due to Impeding mvmnt 0.69 0.87
 Movement Capacity 92

Results for Two-stage process:
 a
 y
 C t 92

Worksheet 8-Shared Lane Calculations

Movement	7 L	8 T	9 R	10 L	11 T	12 R
Volume (vph)				34		95
Movement Capacity (vph)				92		618
Shared Lane Capacity (vph)					247	

Worksheet 9-Computation of Effect of Flared Minor Street Approaches

Movement	7 L	8 T	9 R	10 L	11 T	12 R
C sep				92		618
Volume				34		95
Delay				65.5		11.9
Q sep				0.62		0.31
Q sep +1				1.62		1.31
round (Qsep +1)				2		1
n max					2	
C sh					247	
SUM C sep					349	
n					1	
C act					298	

Worksheet 10-Delay, Queue Length, and Level of Service

Movement	1	4	7	8	9	10	11	12
Lane Config	LT						LR	
v (vph)	133						129	
C(m) (vph)	1041						298	
v/c	0.13						0.43	
95% queue length	0.44						2.08	
Control Delay	9.0						26.0	
LOS	A						D	
Approach Delay							26.0	
Approach LOS							D	

Worksheet 11-Shared Major LT Impedance and Delay

	Movement 2	Movement 5
p(oj)	0.87	1.00
v(il), Volume for stream 2 or 5	797	
v(i2), Volume for stream 3 or 6	0	
s(il), Saturation flow rate for stream 2 or 5	1700	
s(i2), Saturation flow rate for stream 3 or 6	1700	
P*(oj)	0.76	
d(M,LT), Delay for stream 1 or 4	9.0	
N, Number of major street through lanes	1	
d(rank,1) Delay for stream 2 or 5	2.2	

HCS+: Unsignalized Intersections Release 5.6

Phone:
E-Mail:

Fax:

TWO-WAY STOP CONTROL(TWSC) ANALYSIS

Analyst: CMaddox
 Agency/Co.: SEI
 Date Performed: 3/3/2014
 Analysis Time Period: PM Peak
 Intersection: Riverside Pkwy & White Rd
 Jurisdiction: Cobb Co.
 Units: U. S. Customary
 Analysis Year: 2016 Developed Improved
 Project ID:
 East/West Street: Riverside Pkwy
 North/South Street: White Rd
 Intersection Orientation: EW

Study period (hrs): 0.25

Vehicle Volumes and Adjustments

Major Street Movements	1 L	2 T	3 R	4 L	5 T	6 R
Volume	31	322			561	51
Peak-Hour Factor, PHF	0.92	0.92			0.92	0.92
Peak-15 Minute Volume	8	88			152	14
Hourly Flow Rate, HFR	33	349			609	55
Percent Heavy Vehicles	53	--	--		--	--
Median Type/Storage	Undivided			/		
RT Channelized?						
Lanes	0	1			1	0
Configuration	LT				TR	
Upstream Signal?		No			No	
Minor Street Movements	7 L	8 T	9 R	10 L	11 T	12 R

Volume		54		154
Peak Hour Factor, PHF		0.92		0.92
Peak-15 Minute Volume		15		42
Hourly Flow Rate, HFR		58		167
Percent Heavy Vehicles		72		13
Percent Grade (%)	0		0	
Flared Approach: Exists?/Storage		/		Yes /1
RT Channelized?				
Lanes		0		0
Configuration			LR	

Pedestrian Volumes and Adjustments

Movements	13	14	15	16
Flow (ped/hr)	0	0	0	0

Lane Width (ft)	12.0	12.0	12.0	12.0
Walking Speed (ft/sec)	4.0	4.0	4.0	4.0
Percent Blockage	0	0	0	0

Upstream Signal Data							
	Prog. Flow vph	Sat Flow vph	Arrival Type	Green Time sec	Cycle Length sec	Prog. Speed mph	Distance to Signal feet
S2 Left-Turn Through							
S5 Left-Turn Through							

Worksheet 3-Data for Computing Effect of Delay to Major Street Vehicles

	Movement 2	Movement 5
Shared ln volume, major th vehicles:	349	
Shared ln volume, major rt vehicles:	0	
Sat flow rate, major th vehicles:	1700	
Sat flow rate, major rt vehicles:	1700	
Number of major street through lanes:	1	

Worksheet 4-Critical Gap and Follow-up Time Calculation

Critical Gap Calculation								
Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
t(c,base)	4.1					7.1		6.2
t(c,hv)	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
P(hv)	53					72		13
t(c,g)			0.20	0.20	0.10	0.20	0.20	0.10
Percent Grade			0.00	0.00	0.00	0.00	0.00	0.00
t(3,lt)	0.00					0.70		0.00
t(c,T): 1-stage	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
2-stage	0.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
t(c) 1-stage	4.6					7.1		6.3
2-stage								

Follow-Up Time Calculations								
Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
t(f,base)	2.20					3.50		3.30
t(f,HV)	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
P(HV)	53					72		13
t(f)	2.7					4.1		3.4

Worksheet 5-Effect of Upstream Signals

Computation 1-Queue Clearance Time at Upstream Signal				
	Movement 2		Movement 5	
	V(t)	V(l,prot)	V(t)	V(l,prot)
V prog				

Total Saturation Flow Rate, s (vph)
Arrival Type
Effective Green, g (sec)
Cycle Length, C (sec)
Rp (from Exhibit 16-11)
Proportion vehicles arriving on green P
g(q1)
g(q2)
g(q)

Computation 2-Proportion of TWSC Intersection Time blocked

	Movement 2		Movement 5	
	V(t)	V(l,prot)	V(t)	V(l,prot)

alpha
beta
Travel time, t(a) (sec)
Smoothing Factor, F
Proportion of conflicting flow, f
Max platooned flow, V(c,max)
Min platooned flow, V(c,min)
Duration of blocked period, t(p)
Proportion time blocked, p

	0.000	0.000
--	-------	-------

Computation 3-Platoon Event Periods Result

p(2)	0.000
p(5)	0.000
p(dom)	
p(subo)	
Constrained or unconstrained?	

Proportion unblocked for minor movements, p(x)	(1) Single-stage Process	(2) Two-Stage Stage I	(3) Process Stage II
---	--------------------------------	-----------------------------	----------------------------

p(1)
p(4)
p(7)
p(8)
p(9)
p(10)
p(11)
p(12)

Computation 4 and 5
Single-Stage Process

Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
V c, x	664					1051		636
s								
Px								
V c, u, x								
C r, x								
C plat, x								

Two-Stage Process	7	8	10	11
-------------------	---	---	----	----

	Stage1	Stage2	Stage1	Stage2	Stage1	Stage2	Stage1	Stage2
--	--------	--------	--------	--------	--------	--------	--------	--------

V(c,x)								
S						1500		
P(x)								
V(c,u,x)								

C(r,x)								
C(plat,x)								

Worksheet 6-Impedance and Capacity Equations

Step 1: RT from Minor St.	9	12
---------------------------	---	----

Conflicting Flows		636
Potential Capacity		459
Pedestrian Impedance Factor	1.00	1.00
Movement Capacity		459
Probability of Queue free St.	1.00	0.64

Step 2: LT from Major St.	4	1
---------------------------	---	---

Conflicting Flows		664
Potential Capacity		725
Pedestrian Impedance Factor	1.00	1.00
Movement Capacity		725
Probability of Queue free St.	1.00	0.95
Maj L-Shared Prob Q free St.		0.94

Step 3: TH from Minor St.	8	11
---------------------------	---	----

Conflicting Flows		
Potential Capacity		
Pedestrian Impedance Factor	1.00	1.00
Cap. Adj. factor due to Impeding mvmnt	0.94	0.94
Movement Capacity		
Probability of Queue free St.	1.00	1.00

Step 4: LT from Minor St.	7	10
---------------------------	---	----

Conflicting Flows		1051
Potential Capacity		187
Pedestrian Impedance Factor	1.00	1.00
Maj. L, Min T Impedance factor	0.94	
Maj. L, Min T Adj. Imp Factor.	0.96	
Cap. Adj. factor due to Impeding mvmnt	0.61	0.95
Movement Capacity		178

Worksheet 7-Computation of the Effect of Two-stage Gap Acceptance

Step 3: TH from Minor St.	8	11
---------------------------	---	----

Part 1 - First Stage		
Conflicting Flows		
Potential Capacity		
Pedestrian Impedance Factor		
Cap. Adj. factor due to Impeding mvmnt		
Movement Capacity		
Probability of Queue free St.		

Worksheet 9-Computation of Effect of Flared Minor Street Approaches

Movement	7 L	8 T	9 R	10 L	11 T	12 R
C sep				178		459
Volume				58		167
Delay				34.7		17.3
Q sep				0.56		0.80
Q sep +1				1.56		1.80
round (Qsep +1)				2		2
n max					2	
C sh					326	
SUM C sep					618	
n					1	
C act					472	

Worksheet 10-Delay, Queue Length, and Level of Service

Movement	1	4	7	8	9	10	11	12
Lane Config	LT						LR	
v (vph)	33						225	
C(m) (vph)	725						472	
v/c	0.05						0.48	
95% queue length	0.14						2.53	
Control Delay	10.2						19.4	
LOS	B						C	
Approach Delay							19.4	
Approach LOS							C	

Worksheet 11-Shared Major LT Impedance and Delay

	Movement 2	Movement 5
p(oj)	0.95	1.00
v(il), Volume for stream 2 or 5	349	
v(i2), Volume for stream 3 or 6	0	
s(il), Saturation flow rate for stream 2 or 5	1700	
s(i2), Saturation flow rate for stream 3 or 6	1700	
P*(oj)	0.94	
d(M,LT), Delay for stream 1 or 4	10.2	
N, Number of major street through lanes	1	
d(rank,1) Delay for stream 2 or 5	0.6	

TWO-WAY STOP CONTROL SUMMARY

Analyst: CMaddox
 Agency/Co.: SEI
 Date Performed: 3/3/2014
 Analysis Time Period: AM Peak
 Intersection: Oakmont Drwy & White Rd
 Jurisdiction: Cobb Co.
 Units: U. S. Customary
 Analysis Year: 2016 Developed
 Project ID:
 East/West Street: Oakmont Drwy
 North/South Street: White Rd
 Intersection Orientation: EW

Study period (hrs): 0.25

Vehicle Volumes and Adjustments

Major Street:	Approach Movement	Eastbound				Westbound		
		1 L	2 T	3 R		4 L	5 T	6 R
Volume						74	0	18
Peak-Hour Factor, PHF						0.92	0.92	0.92
Hourly Flow Rate, HFR						80	0	19
Percent Heavy Vehicles		--	--			50	--	--
Median Type/Storage		Undivided			/			
RT Channelized?								
Lanes						0	0	0
Configuration						LTRLR		
Upstream Signal?		No				No		

Minor Street:	Approach Movement	Northbound				Southbound		
		7 L	8 T	9 R		10 L	11 T	12 R
Volume		12	137			34	46	
Peak Hour Factor, PHF		0.92	0.92			0.92	0.92	
Hourly Flow Rate, HFR		13	148			36	49	
Percent Heavy Vehicles		2	50			50	2	
Percent Grade (%)		0					0	
Flared Approach: Exists?/Storage		No			/			
Lanes		1	0			0	1	
Configuration		TR				LT		

Delay, Queue Length, and Level of Service

Approach	EB	WB	Northbound				Southbound	
Movement	1	4	7	8	9		10	11
Lane Config		LTR			TR		LT	12
v (vph)		80			161		85	
C(m) (vph)		1358			928		584	
v/c		0.06			0.17		0.15	
95% queue length		0.19			0.63		0.51	
Control Delay		7.8			9.7		12.2	
LOS		A			A		B	
Approach Delay				9.7				12.2
Approach LOS				A				B

HCS+: Unsignalized Intersections Release 5.6

Phone:
E-Mail:

Fax:

TWO-WAY STOP CONTROL(TWSC) ANALYSIS

Analyst: CMaddox
 Agency/Co.: SEI
 Date Performed: 3/3/2014
 Analysis Time Period: AM Peak
 Intersection: Oakmont Drwy & White Rd
 Jurisdiction: Cobb Co.
 Units: U. S. Customary
 Analysis Year: 2016 Developed
 Project ID:
 East/West Street: Oakmont Drwy
 North/South Street: White Rd
 Intersection Orientation: EW

Study period (hrs): 0.25

Vehicle Volumes and Adjustments

Major Street Movements	1 L	2 T	3 R	4 L	5 T	6 R
Volume				74	0	18
Peak-Hour Factor, PHF				0.92	0.92	0.92
Peak-15 Minute Volume				20	0	5
Hourly Flow Rate, HFR				80	0	19
Percent Heavy Vehicles	--	--	--	50	--	--
Median Type/Storage	Undivided			/		
RT Channelized?						
Lanes				0	0	0
Configuration				LTRLR		
Upstream Signal?		No			No	
Minor Street Movements	7 L	8 T	9 R	10 L	11 T	12 R
Volume		12	137	34	46	
Peak Hour Factor, PHF		0.92	0.92	0.92	0.92	
Peak-15 Minute Volume		3	37	9	12	
Hourly Flow Rate, HFR		13	148	36	49	
Percent Heavy Vehicles		2	50	50	2	
Percent Grade (%)		0			0	
Flared Approach: Exists?/Storage			No	/		/
RT Channelized?						
Lanes		1	0	0	1	
Configuration			TR		LT	

Pedestrian Volumes and Adjustments

Movements	13	14	15	16
Flow (ped/hr)	0	0	0	0

Lane Width (ft)	12.0	12.0	12.0	12.0
Walking Speed (ft/sec)	4.0	4.0	4.0	4.0
Percent Blockage	0	0	0	0

Upstream Signal Data							
	Prog. Flow vph	Sat Flow vph	Arrival Type	Green Time sec	Cycle Length sec	Prog. Speed mph	Distance to Signal feet
S2 Left-Turn Through							
S5 Left-Turn Through							

Worksheet 3-Data for Computing Effect of Delay to Major Street Vehicles

	Movement 2	Movement 5
Shared ln volume, major th vehicles:		0
Shared ln volume, major rt vehicles:		0
Sat flow rate, major th vehicles:		1700
Sat flow rate, major rt vehicles:		1700
Number of major street through lanes:		0

Worksheet 4-Critical Gap and Follow-up Time Calculation

Critical Gap Calculation								
Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
t(c,base)		4.1		6.5	6.2	7.1	6.5	
t(c,hv)	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
P(hv)		50		2	50	50	2	
t(c,g)			0.20	0.20	0.10	0.20	0.20	0.10
Percent Grade			0.00	0.00	0.00	0.00	0.00	0.00
t(3,lt)		0.00		0.00	0.00	0.00	0.00	
t(c,T): 1-stage	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
2-stage	0.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
t(c) 1-stage		4.6		6.5	6.7	7.6	6.5	
2-stage								

Follow-Up Time Calculations								
Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
t(f,base)		2.20		4.00	3.30	3.50	4.00	
t(f,HV)	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
P(HV)		50		2	50	50	2	
t(f)		2.7		4.0	3.8	4.0	4.0	

Worksheet 5-Effect of Upstream Signals

Computation 1-Queue Clearance Time at Upstream Signal				
	Movement 2		Movement 5	
	V(t)	V(l,prot)	V(t)	V(l,prot)
V prog				

Total Saturation Flow Rate, s (vph)
Arrival Type
Effective Green, g (sec)
Cycle Length, C (sec)
Rp (from Exhibit 16-11)
Proportion vehicles arriving on green P
g(q1)
g(q2)
g(q)

Computation 2-Proportion of TWSC Intersection Time blocked

	Movement 2		Movement 5	
	V(t)	V(l,prot)	V(t)	V(l,prot)

alpha
beta
Travel time, t(a) (sec)
Smoothing Factor, F
Proportion of conflicting flow, f
Max platooned flow, V(c,max)
Min platooned flow, V(c,min)
Duration of blocked period, t(p)
Proportion time blocked, p

	0.000	0.000
--	-------	-------

Computation 3-Platoon Event Periods Result

p(2)	0.000
p(5)	0.000
p(dom)	
p(subo)	
Constrained or unconstrained?	

Proportion unblocked for minor movements, p(x)	(1) Single-stage Process	(2) Two-Stage Stage I	(3) Process Stage II
--	-----------------------------	--------------------------	-------------------------

p(1)
p(4)
p(7)
p(8)
p(9)
p(10)
p(11)
p(12)

Computation 4 and 5
Single-Stage Process

Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
----------	--------	--------	--------	--------	--------	---------	---------	---------

V c, x		0		179	0	250	170	
s								
Px								
V c, u, x								

C r, x
C plat, x

Two-Stage Process	7	8	10	11
-------------------	---	---	----	----

	Stage1	Stage2	Stage1	Stage2	Stage1	Stage2	Stage1	Stage2
--	--------	--------	--------	--------	--------	--------	--------	--------

V(c,x)								
s			0		0		0	
P(x)								
V(c,u,x)								

C(r,x)
C(plat,x)

Worksheet 6-Impedance and Capacity Equations

Step 1: RT from Minor St.	9	12
---------------------------	---	----

Conflicting Flows	0	
Potential Capacity	960	
Pedestrian Impedance Factor	1.00	1.00
Movement Capacity	960	
Probability of Queue free St.	0.85	1.00

Step 2: LT from Major St.	4	1
---------------------------	---	---

Conflicting Flows	0	
Potential Capacity	1358	
Pedestrian Impedance Factor	1.00	1.00
Movement Capacity	1358	
Probability of Queue free St.	0.94	1.00
Maj L-Shared Prob Q free St.	0.94	

Step 3: TH from Minor St.	8	11
---------------------------	---	----

Conflicting Flows	179	170
Potential Capacity	715	723
Pedestrian Impedance Factor	1.00	1.00
Cap. Adj. factor due to Impeding mvmnt	0.94	0.94
Movement Capacity	673	680
Probability of Queue free St.	0.98	0.93

Step 4: LT from Minor St.	7	10
---------------------------	---	----

Conflicting Flows		250
Potential Capacity		615
Pedestrian Impedance Factor	1.00	1.00
Maj. L, Min T Impedance factor	0.87	0.92
Maj. L, Min T Adj. Imp Factor.	0.90	0.94
Cap. Adj. factor due to Impeding mvmnt	0.90	0.80
Movement Capacity		490

Worksheet 7-Computation of the Effect of Two-stage Gap Acceptance

Step 3: TH from Minor St.	8	11
---------------------------	---	----

Part 1 - First Stage
Conflicting Flows
Potential Capacity
Pedestrian Impedance Factor
Cap. Adj. factor due to Impeding mvmnt
Movement Capacity
Probability of Queue free St.

Part 2 - Second Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor
 Cap. Adj. factor due to Impeding mvmnt
 Movement Capacity

Part 3 - Single Stage

Conflicting Flows	179	170
Potential Capacity	715	723
Pedestrian Impedance Factor	1.00	1.00
Cap. Adj. factor due to Impeding mvmnt	0.94	0.94
Movement Capacity	673	680

Result for 2 stage process:

a		
y		
C t	673	680
Probability of Queue free St.	0.98	0.93

Step 4: LT from Minor St.	7	10
---------------------------	---	----

Part 1 - First Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor
 Cap. Adj. factor due to Impeding mvmnt
 Movement Capacity

Part 2 - Second Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor
 Cap. Adj. factor due to Impeding mvmnt
 Movement Capacity

Part 3 - Single Stage

Conflicting Flows		250
Potential Capacity		615
Pedestrian Impedance Factor	1.00	1.00
Maj. L, Min T Impedance factor	0.87	0.92
Maj. L, Min T Adj. Imp Factor.	0.90	0.94
Cap. Adj. factor due to Impeding mvmnt	0.90	0.80
Movement Capacity		490

Results for Two-stage process:

a	
y	
C t	490

Worksheet 8-Shared Lane Calculations

Movement	7 L	8 T	9 R	10 L	11 T	12 R
Volume (vph)		13	148	36	49	
Movement Capacity (vph)		673	960	490	680	
Shared Lane Capacity (vph)			928	584		

Worksheet 9-Computation of Effect of Flared Minor Street Approaches

Movement	7 L	8 T	9 R	10 L	11 T	12 R
C sep		673	960	490	680	
Volume		13	148	36	49	
Delay						
Q sep						
Q sep +1						
round (Qsep +1)						
n max						
C sh			928	584		
SUM C sep						
n						
C act						

Worksheet 10-Delay, Queue Length, and Level of Service

Movement	1	4	7	8	9	10	11	12
Lane Config		LTR			TR	LT		
v (vph)		80			161	85		
C(m) (vph)		1358			928	584		
v/c		0.06			0.17	0.15		
95% queue length		0.19			0.63	0.51		
Control Delay		7.8			9.7	12.2		
LOS		A			A	B		
Approach Delay				9.7			12.2	
Approach LOS				A			B	

Worksheet 11-Shared Major LT Impedance and Delay

	Movement 2	Movement 5
p(oj)	1.00	0.94
v(i1), Volume for stream 2 or 5		0
v(i2), Volume for stream 3 or 6		0
s(i1), Saturation flow rate for stream 2 or 5		1700
s(i2), Saturation flow rate for stream 3 or 6		1700
P*(oj)		0.94
d(M,LT), Delay for stream 1 or 4		7.8
N, Number of major street through lanes		0
d(rank,1) Delay for stream 2 or 5		

TWO-WAY STOP CONTROL SUMMARY

Analyst: CMaddox
 Agency/Co.: SEI
 Date Performed: 3/3/2014
 Analysis Time Period: PM Peak
 Intersection: Oakmont Drwy & White Rd
 Jurisdiction: Cobb Co.
 Units: U. S. Customary
 Analysis Year: 2016 Developed
 Project ID:
 East/West Street: Oakmont Drwy
 North/South Street: White Rd
 Intersection Orientation: EW

Study period (hrs): 0.25

Vehicle Volumes and Adjustments

Major Street:	Approach Movement	Eastbound				Westbound		
		1	2	3		4	5	6
		L	T	R		L	T	R
Volume						153	0	75
Peak-Hour Factor, PHF						0.92	0.92	0.92
Hourly Flow Rate, HFR						166	0	81
Percent Heavy Vehicles		--	--			50	--	--
Median Type/Storage		Undivided			/			
RT Channelized?								
Lanes						0	0	0
Configuration						LTRLR		
Upstream Signal?		No				No		

Minor Street:	Approach Movement	Northbound				Southbound		
		7	8	9		10	11	12
		L	T	R		L	T	R
Volume			27	36		17	55	
Peak Hour Factor, PHF			0.92	0.92		0.92	0.92	
Hourly Flow Rate, HFR			29	39		18	59	
Percent Heavy Vehicles			2	50		50	2	
Percent Grade (%)			0				0	
Flared Approach: Exists?/Storage				No	/			/
Lanes			1	0		0	1	
Configuration			TR			LT		

Delay, Queue Length, and Level of Service

Approach	EB	WB	Northbound			Southbound		
Movement	1	4	7	8	9	10	11	12
Lane Config		LTR			TR	LT		
v (vph)		166			68	77		
C(m) (vph)		1358			659	465		
v/c		0.12			0.10	0.17		
95% queue length		0.42			0.34	0.59		
Control Delay		8.0			11.1	14.3		
LOS		A			B	B		
Approach Delay				11.1			14.3	
Approach LOS				B			B	

HCS+: Unsignalized Intersections Release 5.6

Phone:
E-Mail:

Fax:

TWO-WAY STOP CONTROL(TWSC) ANALYSIS

Analyst: CMaddox
 Agency/Co.: SEI
 Date Performed: 3/3/2014
 Analysis Time Period: PM Peak
 Intersection: Oakmont Drwy & White Rd
 Jurisdiction: Cobb Co.
 Units: U. S. Customary
 Analysis Year: 2016 Developed
 Project ID:
 East/West Street: Oakmont Drwy
 North/South Street: White Rd
 Intersection Orientation: EW

Study period (hrs): 0.25

Vehicle Volumes and Adjustments

Major Street Movements	1 L	2 T	3 R	4 L	5 T	6 R
Volume				153	0	75
Peak-Hour Factor, PHF				0.92	0.92	0.92
Peak-15 Minute Volume				42	0	20
Hourly Flow Rate, HFR				166	0	81
Percent Heavy Vehicles	--	--	--	50	--	--
Median Type/Storage	Undivided			/		
RT Channelized?						
Lanes				0	0	0
Configuration				LTRLR		
Upstream Signal?	No			No		

Minor Street Movements	7 L	8 T	9 R	10 L	11 T	12 R
Volume		27	36	17	55	
Peak Hour Factor, PHF		0.92	0.92	0.92	0.92	
Peak-15 Minute Volume		7	10	5	15	
Hourly Flow Rate, HFR		29	39	18	59	
Percent Heavy Vehicles		2	50	50	2	
Percent Grade (%)		0			0	
Flared Approach: Exists?/Storage			No	/		/
RT Channelized?						
Lanes		1	0	0	1	
Configuration			TR		LT	

Pedestrian Volumes and Adjustments

Movements	13	14	15	16
Flow (ped/hr)	0	0	0	0

Lane Width (ft)	12.0	12.0	12.0	12.0
Walking Speed (ft/sec)	4.0	4.0	4.0	4.0
Percent Blockage	0	0	0	0

Upstream Signal Data							
	Prog. Flow vph	Sat Flow vph	Arrival Type	Green Time sec	Cycle Length sec	Prog. Speed mph	Distance to Signal feet
S2 Left-Turn Through							
S5 Left-Turn Through							

Worksheet 3-Data for Computing Effect of Delay to Major Street Vehicles

	Movement 2	Movement 5
Shared ln volume, major th vehicles:		0
Shared ln volume, major rt vehicles:		0
Sat flow rate, major th vehicles:		1700
Sat flow rate, major rt vehicles:		1700
Number of major street through lanes:		0

Worksheet 4-Critical Gap and Follow-up Time Calculation

Critical Gap Calculation								
Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
t(c,base)		4.1		6.5	6.2	7.1	6.5	
t(c,hv)	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
P(hv)		50		2	50	50	2	
t(c,g)			0.20	0.20	0.10	0.20	0.20	0.10
Percent Grade			0.00	0.00	0.00	0.00	0.00	0.00
t(3,lt)		0.00		0.00	0.00	0.00	0.00	
t(c,T): 1-stage	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
2-stage	0.00	0.00	1.00	1.00	0.00	1.00	1.00	0.00
t(c) 1-stage		4.6		6.5	6.7	7.6	6.5	
2-stage								

Follow-Up Time Calculations								
Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
t(f,base)		2.20		4.00	3.30	3.50	4.00	
t(f,HV)	0.90	0.90	0.90	0.90	0.90	0.90	0.90	0.90
P(HV)		50		2	50	50	2	
t(f)		2.7		4.0	3.8	4.0	4.0	

Worksheet 5-Effect of Upstream Signals

Computation 1-Queue Clearance Time at Upstream Signal				
	Movement 2		Movement 5	
	V(t)	V(l,prot)	V(t)	V(l,prot)
V prog				

Total Saturation Flow Rate, s (vph)
Arrival Type
Effective Green, g (sec)
Cycle Length, C (sec)
Rp (from Exhibit 16-11)
Proportion vehicles arriving on green P
g(q1)
g(q2)
g(q)

Computation 2-Proportion of TWSC Intersection Time blocked

	Movement 2		Movement 5	
	V(t)	V(l,prot)	V(t)	V(l,prot)

alpha
beta
Travel time, t(a) (sec)
Smoothing Factor, F
Proportion of conflicting flow, f
Max platooned flow, V(c,max)
Min platooned flow, V(c,min)
Duration of blocked period, t(p)
Proportion time blocked, p

	0.000	0.000
--	-------	-------

Computation 3-Platoon Event Periods

	Result
--	--------

p(2)	0.000
p(5)	0.000
p(dom)	
p(subo)	
Constrained or unconstrained?	

Proportion unblocked for minor movements, p(x)	(1) Single-stage Process	(2) Two-Stage Process Stage I	(3) Process Stage II
--	-----------------------------	-------------------------------------	----------------------------

p(1)
p(4)
p(7)
p(8)
p(9)
p(10)
p(11)
p(12)

Computation 4 and 5
Single-Stage Process

Movement	1 L	4 L	7 L	8 T	9 R	10 L	11 T	12 R
----------	--------	--------	--------	--------	--------	---------	---------	---------

V c, x		0		413	0	406	372	
s								
Px								
V c, u, x								

C r, x
C plat, x

Two-Stage Process	7	8	10	11
-------------------	---	---	----	----

	Stage1	Stage2	Stage1	Stage2	Stage1	Stage2	Stage1	Stage2
--	--------	--------	--------	--------	--------	--------	--------	--------

V(c,x)								
s			0		0		0	
P(x)								
V(c,u,x)								

C(r,x)
C(plat,x)

Worksheet 6-Impedance and Capacity Equations

Step 1: RT from Minor St.	9	12
---------------------------	---	----

Conflicting Flows	0	
Potential Capacity	960	
Pedestrian Impedance Factor	1.00	1.00
Movement Capacity	960	
Probability of Queue free St.	0.96	1.00

Step 2: LT from Major St.	4	1
---------------------------	---	---

Conflicting Flows	0	
Potential Capacity	1358	
Pedestrian Impedance Factor	1.00	1.00
Movement Capacity	1358	
Probability of Queue free St.	0.88	1.00
Maj L-Shared Prob Q free St.	0.88	

Step 3: TH from Minor St.	8	11
---------------------------	---	----

Conflicting Flows	413	372
Potential Capacity	529	558
Pedestrian Impedance Factor	1.00	1.00
Cap. Adj. factor due to Impeding mvmnt	0.88	0.88
Movement Capacity	464	490
Probability of Queue free St.	0.94	0.88

Step 4: LT from Minor St.	7	10
---------------------------	---	----

Conflicting Flows		406
Potential Capacity		479
Pedestrian Impedance Factor	1.00	1.00
Maj. L, Min T Impedance factor	0.77	0.82
Maj. L, Min T Adj. Imp Factor.	0.82	0.86
Cap. Adj. factor due to Impeding mvmnt	0.82	0.83
Movement Capacity		397

Worksheet 7-Computation of the Effect of Two-stage Gap Acceptance

Step 3: TH from Minor St.	8	11
---------------------------	---	----

Part 1 - First Stage
Conflicting Flows
Potential Capacity
Pedestrian Impedance Factor
Cap. Adj. factor due to Impeding mvmnt
Movement Capacity
Probability of Queue free St.

Part 2 - Second Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor
 Cap. Adj. factor due to Impeding mvmnt
 Movement Capacity

Part 3 - Single Stage

Conflicting Flows	413	372
Potential Capacity	529	558
Pedestrian Impedance Factor	1.00	1.00
Cap. Adj. factor due to Impeding mvmnt	0.88	0.88
Movement Capacity	464	490

Result for 2 stage process:

a
 y
 C t

	464	490
Probability of Queue free St.	0.94	0.88

Step 4: LT from Minor St.	7	10
---------------------------	---	----

Part 1 - First Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor
 Cap. Adj. factor due to Impeding mvmnt
 Movement Capacity

Part 2 - Second Stage
 Conflicting Flows
 Potential Capacity
 Pedestrian Impedance Factor
 Cap. Adj. factor due to Impeding mvmnt
 Movement Capacity

Part 3 - Single Stage

Conflicting Flows		406
Potential Capacity		479
Pedestrian Impedance Factor	1.00	1.00
Maj. L, Min T Impedance factor	0.77	0.82
Maj. L, Min T Adj. Imp Factor.	0.82	0.86
Cap. Adj. factor due to Impeding mvmnt	0.82	0.83
Movement Capacity		397

Results for Two-stage process:

a
 y
 C t

		397
--	--	-----

Worksheet 8-Shared Lane Calculations

Movement	7 L	8 T	9 R	10 L	11 T	12 R
Volume (vph)		29	39	18	59	
Movement Capacity (vph)		464	960	397	490	
Shared Lane Capacity (vph)			659	465		

Worksheet 9-Computation of Effect of Flared Minor Street Approaches

Movement	7 L	8 T	9 R	10 L	11 T	12 R
C sep		464	960	397	490	
Volume		29	39	18	59	
Delay						
Q sep						
Q sep +1 round (Qsep +1)						
n max						
C sh			659	465		
SUM C sep						
n						
C act						

Worksheet 10-Delay, Queue Length, and Level of Service

Movement	1	4	7	8	9	10	11	12
Lane Config		LTR			TR	LT		
v (vph)		166			68	77		
C(m) (vph)		1358			659	465		
v/c		0.12			0.10	0.17		
95% queue length		0.42			0.34	0.59		
Control Delay		8.0			11.1	14.3		
LOS		A			B	B		
Approach Delay				11.1			14.3	
Approach LOS				B			B	

Worksheet 11-Shared Major LT Impedance and Delay

	Movement 2	Movement 5
p(oj)	1.00	0.88
v(i1), Volume for stream 2 or 5		0
v(i2), Volume for stream 3 or 6		0
s(i1), Saturation flow rate for stream 2 or 5		1700
s(i2), Saturation flow rate for stream 3 or 6		1700
P*(oj)		0.88
d(M,LT), Delay for stream 1 or 4		8.0
N, Number of major street through lanes		0
d(rank,1) Delay for stream 2 or 5		